



IPTC Standards



Specification Version 2.2 Power Conformance Level

Document Revision 1

International Press Telecommunications Council
Copyright © 2009. All Rights Reserved.
www.iptc.org



Copyrights

Copyright © 2009 by IPTC, the International Press Telecommunications Council. All Rights Reserved.

This project intends to use materials that are either in the public domain or are available by the permission for their respective copyright holders. Permissions of copyright holder will be obtained prior to use of protected material. All materials of this IPTC standard covered by copyright shall be licensable at no charge.

Acknowledgements

This documentation is the result of a team effort by members of the International Press Telecommunications Council, with input and assistance from other contributors.

The effort to develop NewsML-G2 was lead by Laurent Le Meur (Agence France Presse) and these persons contributed (ordered by family name): Mark Birbeck (x-port.net Ltd.), Dave Compton (Reuters), Jay Cousins (RivCom), Takahiro Fujiwara (EAST Co. Ltd.), Darko Gulija (HINA), Paul Harman (Press Association), Johan Lindgren (Tidningarnas Telegrambyrå), Jayson Lorenzen (BusinessWire), Stuart Myles (Dow Jones), Michael Steidl (IPTC Managing Director), Ulf Wingstedt (CNET), Misha Wolf (Reuters) .

The Technical Writer of this document was Scott Meltzer.

About the Standard

Specification Versioning History

Version	Issue Date	Approved by	Remarks
2.0	2008-01-31	IPTC Standards Committee	
2.1	2008-07-03	IPTC Standards Committee	
2.2	2008-10-08	IPTC Standards Committee	

Document Revision History

Revision	Issue Date	Author (revised by)	Remark
1	2009-03-31	Michael Steidl	Updated for specification versions 2.1 and 2.2.

About this Document

This document specifies the IPTC news exchange standard NewsML-G2 which is a conceptual and processing model making freely available the IPTC knowledge of the most effective ways to structure, describe, manage and exchange general news.

Status of this Document

This document is under the governance of the IPTC NewsML-G2 Working Group (NewsML-G2 WG) of the IPTC News Content Working Party (NCT WP).

This is a specification document which was endorsed by the IPTC members and may be updated, replaced or obsoleted by other documents at any time.

Public versions of this document and of related IPTC documents are available at:

<http://www.iptc.org/std/NewsML-G2/2.2/>

Public comments should be sent to the forum and mailing list at:

<http://tech.groups.yahoo.com/group/newsml-g2>

A page with all errata not covered by the latest version of the NewsML-G2 specification is available at:

<http://www.iptc.org/goto?NewsML-G2-Errata>



The Full Set of Specification Documents

The full set of specification documents for NewsML-G2 2.0 consists of (file names are added, # is to be substituted by the most current document revision number):

This Specification document - NewsML-G2_2.2_Specification_#.pdf

XML Schema files applicable to the Core Conformance Level (see [Conformance Levels](#) on page 12):

- ◆ NewsML-G2_2.2-spec-NewsItem-Core_#.xsd
- ◆ NAR_1.3-spec-PackageItem-Core_#.xsd
- ◆ NAR_1.3-spec-ConceptItem-Core_#.xsd
- ◆ NAR_1.3-spec-KnowledgeItem-Core_#.xsd
- ◆ NAR_1.3-spec-Framework-Core_#.xsd

XML Schema files applicable to the Power Conformance Level (see [Conformance Levels](#) on page 12):

- ◆ NewsML-G2_2.2-spec-NewsItem-Power_#.xsd
- ◆ NAR_1.3-spec-PackageItem-Power_#.xsd
- ◆ NAR_1.3-spec-ConceptItem-Power_#.xsd
- ◆ NAR_1.3-spec-KnowledgeItem-Power_#.xsd
- ◆ NAR_1.3-spec-Framework-Power_#.xsd

All files above can be obtained from:

<http://www.iptc.org/std/NewsML-G2/2.2/specification/>

Note on the XML Schema File Names

XML Schemas are revised for two reasons:

- ◆ The NewsML-G2 specifications have been changed: this results in a new version of the standard, this will be reflected by a new path to files and a new standard version number like NewsML-G2_2.5
- ◆ The XML Schema has been edited a) to fix errors and b) to change non-normative parts, like the wording of an element's annotation: this is reflected by a new revision number at the end of the file name like the "8" in NewsML-G2_2.2-spec-Framework-Core_8.xsd.

The XML Schema files without the document revision number (e.g. "_8") at the end of the file name are true copies of the latest document revision. This allows applying a persistent reference to the latest XML Schema file version regardless of any edits of the document.



License Agreement

This document is issued under the *Non-Exclusive License Agreement for International Press Telecommunications Council Specifications and Related Documentation*

Important: International Press Telecommunications Council (IPTC) standard specifications for news (the Specifications) and supporting software, documentation, technical reports, web sites and other material related to the Specifications (the Materials) including the document accompanying this license (the Document), whether in a paper or electronic format, are made available to you subject to the terms stated below. By obtaining, using and/or copying the Specifications or Materials, you (the licensee) agree that you have read, understood, and will comply with the following terms and conditions.

1. The Specifications and Materials are licensed for use only on the condition that you agree to be bound by the terms of this license. Subject to this and other licensing requirements contained herein, you may, on a non-exclusive basis, use the Specifications and Materials.
2. The IPTC openly provides the Specifications and Materials for voluntary use by individuals, partnerships, companies, corporations, organizations and any other entity for use at the entity's own risk. This disclaimer, license and release is intended to apply to the IPTC, its officers, directors, agents, representatives, members, contributors, affiliates, contractors, or co-venturers acting jointly or severally.
3. The Document and translations thereof may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the copyright and license notices and references to the IPTC appearing in the Document and the terms of this Specifications License Agreement are included on all such copies and derivative works. Further, upon the receipt of written permission from the IPTC, the Document may be modified for the purpose of developing applications that use IPTC Specifications or as required to translate the Document into languages other than English.
4. Any use, duplication, distribution, or exploitation of the Document and Specifications and Materials in any manner is at your own risk.
5. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, LEGALITY, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THE DOCUMENT OR IN ANY SPECIFICATION OR OTHER PRODUCT OR SERVICE PRODUCED OR SPONSORED BY THE IPTC. THE DOCUMENT AND THE INFORMATION CONTAINED HEREIN AND INCLUDED IN ANY SPECIFICATION OR OTHER PRODUCT OR SERVICE OF THE IPTC IS PROVIDED ON AN "AS IS" BASIS. THE IPTC DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY ACTUAL OR ASSERTED WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. NEITHER THE IPTC NOR ITS CONTRIBUTORS SHALL BE HELD LIABLE FOR ANY IMPROPER OR INCORRECT USE OF INFORMATION. NEITHER THE IPTC NOR ITS CONTRIBUTORS ASSUME ANY RESPONSIBILITY FOR ANYONE'S USE OF INFORMATION PROVIDED BY THE IPTC. IN NO EVENT SHALL THE IPTC OR ITS CONTRIBUTORS BE LIABLE TO ANYONE FOR DAMAGES OF ANY KIND, INCLUDING BUT NOT LIMITED TO, COMPENSATORY DAMAGES, LOST PROFITS, LOST DATA OR ANY FORM OF SPECIAL, INCIDENTAL, INDIRECT, CONSEQUENTIAL OR PUNITIVE DAMAGES OF ANY KIND WHETHER BASED ON BREACH OF CONTRACT OR WARRANTY, TORT, PRODUCT LIABILITY OR OTHERWISE.
6. The IPTC takes no position regarding the validity or scope of any Intellectual Property or other rights that might be claimed to pertain to the implementation or use of the technology described in the Document or the extent to which any license under such rights might or might not be available. The IPTC does not represent that it has made any effort to identify any such rights. Copies of claims of rights made available for publication, assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of the Specifications and Materials, can be obtained from the Managing Director of the IPTC.
7. By using the Specifications and Materials including the Document in any manner or for any purpose, you release the IPTC from all liabilities, claims, causes of action, allegations, losses, injuries, damages, or detriments of any nature arising from or relating to the use of the Specifications, Materials or any portion thereof. You further agree not to file a lawsuit, make a claim, or take any other formal or informal legal action against the IPTC, resulting from your acquisition, use, duplication, distribution, or exploitation of the Specifications, Materials or any portion thereof. Finally, you hereby agree that the IPTC is not liable for



any direct, indirect, special or consequential damages arising from or relating to your acquisition, use, duplication, distribution, or exploitation of the Specifications, Materials or any portion thereof.

8. Specifications and Materials may be downloaded or copied provided that ALL copies retain the ownership, copyright and license notices.

9. Materials may not be edited, modified, or presented in a context that creates a misleading or false impression or statement as to the positions, actions, or statements of the IPTC.

10. The name and trademarks of the IPTC may not be used in advertising, publicity, or in relation to products or services and their names without the specific, written prior permission of the IPTC. Any permitted use of the trademarks of the IPTC, whether registered or not, shall be accompanied by an appropriate mark and attribution, as agreed with the IPTC.

11. Specifications may be extended by both members and non-members to provide additional functionality (Extended Specifications) provided that there is a clear recognition of the IPTC IP and its ownership in the Extended Specifications and the related documentation and provided that the extensions are clearly identified and provided that a perpetual license is granted by the creator of the Extended Specifications for other members and non-members to use the Extended Specifications and to continue extensions of the Extended Specifications. The IPTC does not waive any of its rights in the Specifications and Materials in this context. The Extended Specifications may be considered the intellectual property of their creator. The IPTC expressly disclaims any responsibility for damage caused by an extension to the Specifications.

12. Specifications and Materials may be included in derivative work of both members and non-members provided that there is a clear recognition of the IPTC IP and its ownership in the derivative work and its related documentation. The IPTC does not waive any of its rights in the Specifications and Materials in this context. Derivative work in its entirety may be considered the intellectual property of the creator of the work. The IPTC expressly disclaims any responsibility for damage caused when its IP is used in a derivative context.

13. This Specifications License Agreement is perpetual subject to your conformance to the terms of this Agreement. The IPTC may terminate this Specifications License Agreement immediately upon your breach of this Agreement and, upon such termination you will cease all use, duplication, distribution, and/or exploitation in any manner of the Specifications and Materials.

14. This Specifications License Agreement reflects the entire agreement of the parties regarding the subject matter hereof and supersedes all prior agreements or representations regarding such matters, whether written or oral. To the extent any portion or provision of this Specifications License Agreement is found to be illegal or unenforceable, then the remaining provisions of this Specifications License Agreement will remain in full force and effect and the illegal or unenforceable provision will be construed to give it such effect as it may properly have that is consistent with the intentions of the parties.

15. This Specifications License Agreement may only be modified in writing signed by an authorized representative of the IPTC.

16. This Specifications License Agreement is governed by the law of United Kingdom, as such law is applied to contracts made and fully performed in the United Kingdom. Any disputes arising from or relating to this Specifications License Agreement will be resolved in the courts of the United Kingdom. You consent to the jurisdiction of such courts over you and covenant not to assert before such courts any objection to proceeding in such forums.

IF YOU DO NOT AGREE TO THESE TERMS YOU MUST CEASE ALL USE OF THE SPECIFICATIONS AND MATERIALS NOW. IF YOU HAVE ANY QUESTIONS ABOUT THESE TERMS, PLEASE CONTACT THE MANAGING DIRECTOR OF THE INTERNATIONAL PRESS TELECOMMUNICATION COUNCIL. AS OF THE DATE OF THIS REVISION OF THIS SPECIFICATIONS LICENSE AGREEMENT YOU MAY CONTACT THE IPTC at www.iptc.org.

License agreement version of: 30 January 2006



Contents

1 Introduction to NewsML-G2	12
1.1 History	12
1.2 Conformance Levels	12
2 Representing News - newsItem	13
2.1 Description	13
2.2 Indication of Compliance with a Standard and Conformance Level	13
2.3 Identification and Versioning	13
2.4 Catalog of Controlled Vocabularies	14
2.5 Signature Information	15
2.6 Rights Information	15
2.7 Item Metadata	16
2.7.1 Management Metadata	16
2.7.2 Processing the Publish Status of an Item	16
2.7.2.1 State Transition Diagram	17
2.7.2.2 Use Cases Associated with a Status of Withheld	17
2.7.2.3 Processing Model on the Recipient Side	17
2.7.3 Processing of versionCreated	18
2.8 Item Links	18
2.8.1 Processing Links	18
2.9 News Content Metadata	19
2.9.1 Administrative Metadata	19
2.9.1.1 Dates Processing Model	19
2.9.1.2 Audience Processing Model	20
2.9.2 Descriptive Metadata	20
2.9.3 Other Content Metadata	20
2.10 Part Metadata	21
2.10.1 Edit Units and Time Codes	21
2.10.2 Assertions About Concepts	22
2.11 References to Inline Concepts	22
2.12 newsItem Content	22
2.13 News Content Characteristics	23
2.14 Channels	23
3 Representing Concept Information - concept Component	24
3.1 Concept Component	24
3.2 Relationships Between Concepts	24
3.3 Details on Specific Entities	25
3.3.1 Contact Information	25
3.3.2 Postal Address	25
4 Managing Individual Concepts - conceptItem	26
4.1 Description	26
4.2 Structure of a conceptItem	26
4.3 Item Metadata	26
4.4 Concept related Metadata	26
4.5 conceptItem Content	26
5 Managing Sets of Concepts - knowledgeItem	27
5.1 Description	27
5.2 Structure of a knowledgeItem	27



5.3 Item Metadata	27
5.4 Knowledge Related Metadata	27
5.5 knowledgeItem Content	27
6 Packaging Items - packageItem	28
6.1 Structure of a packageItem	28
6.2 Item Metadata	28
6.3 Package Related Metadata	28
6.4 packageItem Content	28
7 Dealing with Controlled Values	30
7.1 {scheme, code} Pair, Scheme URI and Concept URI	30
7.2 Qualified Code (QCode)	31
7.2.1 Processing QCodes	31
7.3 Processing Catalogs	31
7.3.1 Structure of a Catalog	31
7.3.2 Processing Remote Catalogs	32
7.3.3 Caching a Catalog	32
7.3.4 Checking a Catalog	32
7.4 Processing Schemes	32
7.4.1 Evolution of Scheme URIs	32
7.4.2 Retrieving All Terms of a Scheme	32
7.5 Qualified and Typed Properties	33
7.6 Flexible Properties	33
7.7 Composite Concepts	34
7.8 Editing Attributes	34
8 Dealing with Labels and Blocks	35
8.1 Introduction	35
8.2 Internationalization Attributes	35
9 Exchanging Items - newsMessage	36
9.1 Message Information	36
9.2 About Using Schemes in a newsMessage	36
10 Specification Reference	37
10.1 Introduction to the Common Components	37
10.2 General Specifications	37
10.2.1 XML Namespaces	37
10.2.2 MIME Types	38
10.2.3 Extension Points in XML	38
10.3 Implementation Design Rules	38
10.4 Processing Model Terminology	38
10.5 Component Structure Format	39
10.6 Element Definitions	40
10.6.1 Access	40
10.6.2 Accountable Person	41
10.6.3 Address Line	42
10.6.4 Affiliation	43
10.6.5 Alternative Identifier	44
10.6.6 Alternative Locator	45
10.6.7 Alternative Representation	46
10.6.8 Anchor	47
10.6.9 Assertion	48



10.6.10 Audience 49

10.6.11 Bag 50

10.6.12 Bag Item 51

10.6.13 Broader 52

10.6.14 By 53

10.6.15 Capacity 54

10.6.16 Catalog 55

10.6.17 Channel of Remote Content 56

10.6.18 Channel for News Message 58

10.6.19 Concept 59

10.6.20 Concept Definition 60

10.6.21 Concept Identifier 61

10.6.22 Concept Item 62

10.6.23 Concept Name 63

10.6.24 Concept Set 64

10.6.25 Contact Information 65

10.6.26 Content Metadata for Concept Items 66

10.6.27 Content Metadata for Knowledge Items 67

10.6.28 Content Metadata for News Items 68

10.6.29 Content Metadata for Package Items 69

10.6.30 Content Provider 70

10.6.31 Content Set 71

10.6.32 Contributor 72

10.6.33 Copyright Holder 73

10.6.34 Copyright Notice 74

10.6.35 Country 75

10.6.36 Country Area 76

10.6.37 Creator 77

10.6.38 Credit Line 78

10.6.39 Date Content Created 79

10.6.40 Date Content Modified 80

10.6.41 Date Item Embargo Ends 81

10.6.42 Date Item First Created 82

10.6.43 Date Item Version Created 83

10.6.44 Date of Birth 84

10.6.45 Date of Death 85

10.6.46 Date of Dissolution 86

10.6.47 Date of Foundation 87

10.6.48 Date of Transmission 88

10.6.49 Dateline 89

10.6.50 Recurrence Group 89

10.6.51 Date Resource Created 90

10.6.52 Description 91

10.6.53 Destination 92

10.6.54 Editorial Note 93

10.6.55 Editorial Service 94

10.6.56 Email Address 95

10.6.57 Excluded Audience 96

10.6.58 Exclusion Date 97

10.6.59 Exclusion Rule 98

10.6.60 Facet 99

10.6.61 Fax Number 100

10.6.62 File Name 101

10.6.63 Generator Tool 102

10.6.64 Genre 103

10.6.65 Geographic Position 104

10.6.66 Geopolitical Area Details 105

10.6.67 Group 106



10.6.68 Group Reference	107
10.6.69 Group Set	108
10.6.70 Headline	109
10.6.71 Icon	110
10.6.72 Inline Concept Marker	111
10.6.73 Inline Data (NewsML-G2 Specific)	112
10.6.74 Inline Reference	114
10.6.75 Inline XML (NewsML-G2 Specific)	115
10.6.76 Instance Of	117
10.6.77 Instant Messaging Address	118
10.6.78 Information Source	119
10.6.79 Item Class	120
10.6.80 Item Metadata	121
10.6.81 Item Reference	122
10.6.82 Item Set	123
10.6.83 Item Title	124
10.6.84 Knowledge Item	125
10.6.85 Language	126
10.6.86 Line Break	127
10.6.87 Link	128
10.6.88 Locality	129
10.6.89 Located	130
10.6.90 Location	131
10.6.91 Location Details	132
10.6.92 Member Of	133
10.6.93 Message Header	134
10.6.94 Narrower	135
10.6.95 News Item (NewsML-G2 Specific)	136
10.6.96 News Message	137
10.6.97 Note	138
10.6.98 Object Details	139
10.6.99 Opening Hours	140
10.6.100 Origin	141
10.6.101 Organisation Details	142
10.6.102 Package Item	143
10.6.103 Part Meta	144
10.6.104 Person Details	146
10.6.105 Phone Number	147
10.6.106 POI Details	148
10.6.107 Postal Address	149
10.6.108 Postal Code	150
10.6.109 Priority	151
10.6.110 Profile	152
10.6.111 Property Value Name	153
10.6.112 Publish Status	154
10.6.113 Recurrence Date	155
10.6.114 Recurrence Rule	156
10.6.115 Related Concept	157
10.6.116 Remote Catalog Reference	158
10.6.117 Remote Content (NewsML-G2 Specific)	159
10.6.118 Rights Information	162
10.6.119 Role in the Workflow	163
10.6.120 Ruby	164
10.6.121 Ruby Base	165
10.6.122 Ruby Parenthesis	166
10.6.123 Ruby Text	167
10.6.124 Same As	168
10.6.125 Scheme Declaration	169



10.6.126	Sender	170
10.6.127	Signal	171
10.6.128	Slugline	172
10.6.129	Span	173
10.6.130	Subject	174
10.6.131	Time Delimiter	175
10.6.132	Timestamp	176
10.6.133	Transmission Identifier	177
10.6.134	Type of a Concept	178
10.6.135	Urgency	179
10.6.136	Usage Terms	180
10.6.137	Visual Region Delimiter	181
10.6.138	Web Address	182
10.7	Element Group Definitions	183
10.7.1	Concept Definition Group	183
10.7.2	Concept Relationships Group	183
10.7.3	Entity Details Group	183
10.7.4	Administrative Metadata Group	184
10.7.5	Knowledge Descriptive Metadata Group	184
10.7.6	Descriptive Metadata Group	184
10.7.7	Item Management Group	185
10.8	Datatype Definitions	186
10.8.1	Any Item Type	186
10.8.2	Approximate Date and Time Property Type	187
10.8.3	Audience Type	188
10.8.4	Block Type	189
10.8.5	Concept Identifier Type	190
10.8.6	Content Metadata Type	191
10.8.7	Date and Optional Time Property Type	192
10.8.8	Date and Optional Time Type	193
10.8.9	Date and Time Property Type	194
10.8.10	Electronic Address Type	195
10.8.11	Electronic Address Tech Type	196
10.8.12	Flexible 1 Concept Property Type	197
10.8.13	Flexible 1 Party Property Type	198
10.8.14	Flexible 1 Property Type	199
10.8.15	Flexible Location Property Type	200
10.8.16	Flexible Organisation Property Type	201
10.8.17	Flexible Party Property Type	202
10.8.18	Flex Person Property Type	203
10.8.19	Flexible Property Type	204
10.8.20	Integer 0 to 100 Type	205
10.8.21	Integer 1 to 9 Type	206
10.8.22	International String Type	207
10.8.23	IRI Type	208
10.8.24	Label 1 Type	209
10.8.25	Link 1 Type	210
10.8.26	QCode List Type	212
10.8.27	QCode Property Type	213
10.8.28	QCode Type	214
10.8.29	Qualified Property Type	215
10.8.30	Recurrence Rule Type	216
10.8.31	Related Concept Type	217
10.8.32	Rights Label Type	218
10.8.33	Truncated Date and Time Property Type	219
10.8.34	Truncated Date and Time Type	220
10.8.35	Typed Qualified Property Type	221



10.8.36 Versioned String Type	222
10.9 Attribute Group Definitions	223
10.9.1 Internationalization Attributes Group	223
10.9.2 Editing Attributes Group	223
10.9.3 Quantify Attributes Group	223
10.9.4 Time Validity Attributes Group	224
10.9.5 News Content Attributes	224
10.9.6 Target Resource Attributes Group	225
10.9.7 News Content Characteristics	225
11 Glossary	228
12 References	231
13 Index	232
13.1 Elements	232
13.2 Datatypes	234



1 Introduction to NewsML-G2

NewsML™ is a media-independent news exchange format for general news.

News exchange is a method of moving around not only the core news content, but also data that describe the content in an abstract way (i.e. metadata), information about how to handle news in an appropriate way (i.e. news management data), information about the packaging of news information, and finally information about the technical transfer itself.

1.1 History

The initial version of NewsML, version 1.0, was approved in October 2000. Since then it went along with minor revisions: version 1.1 was approved in October 2002; version 1.2 was approved in October 2003.

In 2004, the user-experience with NewsML was evaluated, and it was decided to create a consistent set of complementary standards as a comprehensive and interoperable way to move all types of data between media systems in order to make news exchange efficient and reliable. This set of standards is now the IPTC family of G2-Standards, and NewsML-G2 is a member of it.

The family of IPTC G2-Standards is built on a common structural and function framework called the IPTC News Architecture (NAR). For this reason many components of NewsML-G2 are common with other members of the G2-Standards, like e.g. EventsML-G2.

To better understand the terminology used in the G2-Standards specifications we recommend the [Glossary](#) (page 228) as a reference, as it provides an extensive set of terms and their definitions.

The NewsML-G2 Specification builds on:

- ◆ The NewsML 2 Business Requirements [NML-BR],
- ◆ The IPTC-G2 News Architecture Core Model [NAR-CM],
- ◆ The IPTC-G2 News Architecture Power Extensions Model [NAR-PM].

1.2 Conformance Levels

Different conformance levels are defined in the model, each of them related to a level of complexity (at the conceptual and processing level) of the related Items. This feature adds modularity to the model.

The current model defines two conformance levels named “core conformance level” (CCL) and “power conformance level” (PCL). The core conformance level is focused on simplicity and interoperability. The power conformance level is a superset of the core conformance level which gives more flexibility to providers who choose it, but the recipient processors are more complex to program to comply with PCL and interoperability is lower than for CCL as not all recipients will implement the power level.

A compliant processor must therefore assert supporting either “core” or “power” functionality.

As the “power” features are only an extension of the “core” features, a “core” compliant processor SHOULD process “power” Items by simply ignoring the information pertaining to the “power” level.



2 Representing News - newsItem

An XML Schema file corresponding to the specifications for this item is available (see [The Full Set of Specification Documents](#) on page 3).

2.1 Description

A newsItem aims to convey news with the sense of the reporting of a newsworthy event or fact. Its content is gathered by journalists, presented with a journalistic style, and updated according to the progression of the story.

Examples of newsItems are a news report, a picture, a graphical illustration of some event, a video clip or an illustrated biography.

Typical characteristics of a newsItem are:

- ◆ Its content may be of any media type or format, e.g., the thumbnail, preview and high definition renditions of a picture.
- ◆ It can also convey more structured news information, e.g., information about companies, sports events and general events, in instances when this information is related to an event or fact.
- ◆ Its content is of short term interest: newsItems are volatile, and interest in them fades as time passes (“nothing is older than yesterday’s news”).
- ◆ It is expressed via a set of alternative renditions of some media content.
- ◆ It will usually be updated only for a short period of time, as long as the covered event evolves, and then may be archived.
- ◆ It refers to an arbitrary set of concepts and entities.
- ◆ It may be associated with other newsItems or Web resources via typed links.

2.2 Indication of Compliance with a Standard and Conformance Level

The IPTC [newsItem](#) (page 136) *standard* attribute MUST be set to “NewsML-G2”.

The schema version to which the newsItem conforms MUST be indicated as an attribute. The current version is identified by the string “2.0”.

The IPTC conformance level to which the newsItem conforms in this specification MUST be indicated by the value “power”.

Sample:

```
<newsItem standard="NewsML-G2" standardversion="2.0"
  xmlns="http://iptc.org/std/nar/2006-10-01/" >
</newsItem>
```

2.3 Identification and Versioning

It is possible to positively identify a newsItem as it moves through the news workflow and is transferred from place to place and from system to system.

A newsItem MUST have a *guid* attribute, which is a persistent and globally unique identifier. The guid is required to be in the form of an IRI. Any IRI capable of acting as a globally unique identifier is accepted.

Note: The IPTC will provide the newsml-URN for this purpose, specified by a successor of RFC-3085.

A newsItem MAY have a *version* attribute, and this version MUST be incremented when the content of the Item is updated. The first version MUST be numbered 1: if the version is not explicitly set, this value must be assumed by the recipient of the Item.

The *standardversion* attribute must reflect the version of the standard as it is implemented by the corresponding XML Schema.



Sample:

```
<newsItem standard="NewsML-G2" standardversion="2.0"
  guid="urn:newsml:iptc.org:20071231:sample" version="2"
  xmlns="http://iptc.org/std/nar/2006-10-01/" >
</newsItem>
```

2.4 Catalog of Controlled Vocabularies

NewsML-G2 recommends the use of controlled values for most properties. Each news provider is free to use their own taxonomies of subjects, genres, geopolitical areas, organisations etc., and to use any value scheme it decides in the Items it provides. A provider must therefore indicate the list of the schemes he is using.

Cataloguing information **MUST** be included at the top of each Item.

A **catalog** (page 55) is defined as a set of scheme declarations in use by a news provider for a given Item.

Due to the large number of schemes potentially used in a single Item, and knowing that bandwidth is very important to the News industry, the catalog may be stored remotely (see **catalogRef** on page 158).

A remote catalog **MUST** have a *href* attribute which contains the URI of a remote catalog. A remote catalog takes the form of an XML file with a catalog element as root.

The URI of a remote catalog acts both as a locator and a global identifier, therefore:

- ◆ The URI of a remote catalog **MUST NOT** be relative.
- ◆ If a remote catalog is functionally changed, the IRI used to access it **MUST** be changed. Functional changes are:
 - the addition or removal of a scheme declaration,
 - a change to a scheme alias,
 - a change to a scheme URI.

One or more additional title for a catalog or catalogRef **MAY** be provided in different languages and variants.

As some required properties take a QCode as a value, at least one catalog or remoteCatalog **MUST** be present.

In general, a given provider will define a unique catalog of all used schemes, store it in a central repository and reference it from all Items it provides. A provider **MAY** declare several catalogs in the same Item. This may be especially useful for an aggregator which uses property values from different sources, but requires a way to avoid scheme alias clashes. In this case, catalog and remote catalog elements **MAY** appear in any order, and their order is not relevant.

Detailed information on the structure of catalogs and their processing is given in **Dealing with Controlled Values** (page 30).

Sample:

```
<newsItem standard="NewsML-G2" standardversion="2.0"
  guid="urn:newsml:iptc.org:20071231:sample" version="2" xmlns="http://
  iptc.org/std/nar/2006-10-01/" >
  <catalogRef href="http://aprovider.com/cv/newsml-g2-catalog-4.xml" />
  . . . .
</newsItem>
```



2.5 Signature Information

A digital signature may be associated with a whole Item or only parts of it. For example, it is possible to sign each individual news content component of a newsItem using their local identifiers as a local reference.

A digital signature is a unique seal placed on data. It is very difficult to forge and assures that any change made to the signed data cannot go undetected.

This specification supports the model and syntax defined by the W3C in [XMLDSIG], and introduced by the following: “XML Signatures provide integrity, message authentication, and/or signer authentication services for data of any type, whether located within the XML that includes the signature or elsewhere”.

This specification model excludes two functionalities defined by the W3C XML-Signature Processing Recommendation. These are: “Signed content included within an XML Signature Construct” and “Detached Signatures”.

Therefore this specification offers the following features:

- ◆ A Signature **MUST** be “enveloped” (the Signature Component is contained within the Item being signed).
- ◆ A Signature **MUST** sign the Item containing the Signature component or child components of the Item containing the Signature.
- ◆ The Signature **MUST NOT** be “enveloping” (it cannot sign content found within the signature itself).
- ◆ A Signature **MUST NOT** be “detached” (a detached Signature Component would not be contained within the Item being signed and could be external to the containing document).
- ◆ A Signature **MUST NOT** be related to Items and Components external to the enclosing document (via references).

2.6 Rights Information

The content of a newsItem is bound to a set of copyrights and licensing information.

A **rightsInfo** (page 162) wrapper element acts as a container for a set of properties related to rights, which offer a basic expression of the copyright and usage conditions associated with an Item.

This set is limited to an accountable person, a copyrightHolder and a set of copyrightNotices and usageTerms.

The order of the properties is flexible: The non-repeatable properties **MUST** come first, then the repeatable properties **MAY** be inserted in any order.

The expression of rights can be verbose, and the volume of information exchanged or stored may suffer from the repetition of such information. Therefore each property provides an *href* attribute as an alternative locator of a remote expression of rights. In the case where both inline and remote expression of rights is indicated, the inline expression **MUST** take precedence.

In some situations, different parts of the content are associated with different sets of rights; the rightsInfo element is therefore repeatable.

Each set of rights provides an optional reference attribute (*idrefs*) which indicates which part of content is bound to these rights. This can be achieved by referencing the id of a content component of an item, i.e. inlineXML, inlineData and remoteContent for a News Item, and concept for a Knowledge Item. Further this can be the *partid* of a partMeta component. The *idrefs* attribute **MAY** reference more than one component.

A same piece of content **MAY** have different set of rights associated with it; in this case the union of the rights applies to this content. In case of a logical clash, the recipient **SHOULD** consider it as an error and check with the provider.



The rightsInfo element also provides optional time validity attributes (*validfrom* and *validto*) which express the date and time between which the set of rights properties apply.

Each provider may add a set of metadata properties which have to be defined in a non-IPTC namespace. See also [XML Namespaces](#) (page 37) and [Extension Points in XML](#) (page 38).

2.7 Item Metadata

Such information is wrapped in the itemMeta wrapper element and split between news management metadata and Item links.

2.7.1 Management Metadata

Management metadata is bound to the Item as a whole and reflects its processing in a professional workflow.

The order of the properties in this set is imposed by the W3C XML schema.

Table 1. Item Management Group Elements

Element Title	Element Name	Card	Described on Page
Item Class	itemClass	(1)	120
Content Provider	provider	(1)	70
Date Item Version Created	versionCreated	(1)	83
Date Item First Created	firstCreated	(0..1)	82
Date Item Embargo Ends	embargoed	(0..1)	81
Publish Status	pubStatus	(0..1)	154
Role in the Workflow	role	(0..1)	163
File Name	filename	(0..1)	101
Generator Tool	generator	(0..1)	102
Profile	profile	(0..1)	152
Editorial Service	service	(0..unbounded)	94
Item Title	title	(0..unbounded)	124
Editorial Note	edNote	(0..unbounded)	93
Member Of	memberOf	(0..unbounded)	133
Instance Of	instanceOf	(0..unbounded)	117
Signal	signal	(0..unbounded)	171
Alternative Representation	altRep	(0..unbounded)	46

The IPTC provides a standardised scheme applicable to the [itemClass](#) (page 120) property of a news-Item, identified by the URI <http://cv.iptc.org/newscodes/ninature/>.

Each provider may add a set of metadata properties which have to be defined in a non-IPTC namespace. See also [XML Namespaces](#) (page 37) and [Extension Points in XML](#) (page 38).

2.7.2 Processing the Publish Status of an Item

The IPTC makes these values normative for the exchange of Items between a provider and its customers:


- ◆ Usable: The Item MAY be published without restriction.
- ◆ Withheld: Until further notice, the Item MUST NOT be published or used under any circumstances. If the Item has been published the publisher MUST take immediate action to withdraw or retract it.
- ◆ Canceled: The Item MUST NOT be published or used under any circumstances. If the Item has been published the publisher MUST take immediate action to withdraw or retract it.

Embargoes are managed by the embargoed property, which indicates the date of end of an embargo. This property is optional; if present, the date and time it contains must be compared with the current date and time before the Item is used. The Item must not be published before this time. The embargo overrides the usability of the Item, inferred from its status. If embargoed does not exist the item is not embargoed.

2.7.2.1 State Transition Diagram

This depicts the state transition diagram reflecting the ways in which the **pubStatus** (page 154) values are intended to be used. Thus, upon creation of an Item, allowed statuses are usable and withheld. It is possible to withhold a usable document; it is possible to release a withheld document; it is possible to cancel a usable or withheld document. Once an Item has had its status set to canceled, it has reached a final state.

Figure 1. State Transition Diagram



2.7.2.2 Use Cases Associated with a Status of Withheld

Use Case 1: A provider distributes a story as a newsItem (version 1) with the status usable. At a later stage he learns that there may be a problem with the information included in the Item. He sends a new version of the newsItem (version 2) with a status set to withheld. All recipient systems must display a warning on this newsItem, and recipient publishers must postpone the publication of the information contained in the newsItem until further notice. The news provider has confirmation that the information is false and decides to set the status to canceled (version 3).

Use Case 2: An eCommerce system proposes a large collection of illustrated articles managed as news items. The publisher managing the system sees that the information included in a newsItem (version 1) is not up to date anymore, and decides to hide this Item from its customers until it is properly revised. He set then its status to withheld (version 2), edits the newsItem and set its status back to usable (version 3).

2.7.2.3 Processing Model on the Recipient Side

Here is the processing model on the recipient side and relies on the **pubStatus** (page 154) and embargoed properties:

```

Test pubStatus = canceled:
    The Item must not be used, ever. Any usage of the Item must be prohibited, if needed by the way of alerts.
    Else: next
Test pubStatus = withheld:
    The Item must not be used until further notice. Any usage of the Item must be prohibited, if needed by the way of alerts.
    Else: next
Test pubStatus = usable:
    Test embargoed is not past: if yes, the live status is embargoed
    Else: The Item is usable and may be safely published
  
```

2.7.3 Processing of versionCreated

If the value provided by any date/time field does not conform to the appropriate syntax (e.g. format “YYYY-MM-DDTHH:MM:SS[+-]MM:SS”) it MUST be considered as being not existent.

In the case of the mandatory **versionCreated** (page 83) property the full Item MUST be considered as being void.

2.8 Item Links

A powerful feature of NewsML-G2 is the capability to associate Items via links. It is therefore possible to create a network of news resources, for management and navigation purposes.

The **link** (page 128) element offers a generic mechanism for linking Items within the NAR framework as well as creating links from Items to other Web resources.

The semantic of the link MAY be refined via a relationship attribute (*rel*). In the absence of such indicator, the implied meaning of the link is “see also” (i.e. a navigation link).

The IPTC provides a recommended scheme of link relationships identified by the URI <http://cv.iptc.org/newscodes/itemrelation/>.

To identify the target resource either the *residref* attribute or the *href* attribute MUST be set, optionally both MAY be used in parallel. The *residref* attribute identifies the target resource by its globally unique identifier (if the resource has such an identifier), while the *href* attribute identifies the location of the target resource in e.g. a (remote) file system. If the target resource is an Item and the *residref* attribute is used, a version attribute MAY indicate the target Item version; in the absence of version information, the target resource is the latest version available.

The content type, a.k.a. IANA MIME type of the target resource MAY be indicated by the *contenttype* attribute. It MAY be complemented by a *format* attribute to refine the MIME type information.

In order to ease the processing of a linked resource, the size in bytes of the target resource MAY be indicated. This feature is useful if the target on the link is a Web resource. If the target resource is an Item, the size which is given here MUST be the size of the XML representation of the Item.

A *rank* attribute may represent the rank of the link among other links.

This property also provides **timeValidityAttributes** (page 224) (*validfrom* and *validto*) which express the date and time between which the link is valid.

Supplemental metadata extracted from the target resource (usually an Item) may be added to the linking information as child elements. Such information is not constrained by the model. It may be part of the target Item Metadata (e.g. Publish Status, Alternative Location ...), Content Metadata (e.g. Intended Audience, Subject, Genre ...) or Characteristics of the content (e.g. Size, Content Type, Format, or specific characteristics like the Height and Width of a picture). Different sets of characteristics may be provided, corresponding to specialized content components.

All properties SHOULD be included directly under the link property, without wrapper element (e.g. neither **itemMeta** (page 121) nor *contentMeta*).

2.8.1 Processing Links

Link processing rules:

Link.1: Processor on the consumer side: If a *guid* and a *version* are provided, check whether the specific version of the Item is accessible using this information.

Processor on the provider side: If a *guid* and a *version* are provided deliver only the item version with the requested version number.

Link.2: Processor on the consumer side: If only a *guid* is available and no *version*, check whether an item is delivered by the provider. Consider a delivered version of the item as being the latest one.

Processor on the provider side: if only a *guid* is requested and not *version*, check if any version of the item exists, and if yes provide the one with the highest version number.



Link.3: Check whether the value of the *href* attribute allows some direct retrieval of the target resource via the Web (e.g. if the scheme is http: or ftp:), or an implicit resolution mechanism (e.g. DOI).

Link.4: Check whether an Alternative Representation (**altRep** (page 46)) is exposed in the link. This information may complement the *href* attribute and provide an immediate URI resolution mechanism for Items. Multiple locations may be given, as allowed in the Item Metadata component. In such a case the processor will use the role qualifier and URL scheme for choosing the most appropriate resource.

Link.5: Signal an error or ignore the link.

2.9 News Content Metadata

News Content Metadata is directly associated with the news information conveyed by the Item, independently of the processing of the Item in a professional workflow. Such information is wrapped in the *contentMeta* wrapper element and split between administrative and descriptive metadata.

2.9.1 Administrative Metadata

This is a set of properties associated with the administrative facet of content, i.e. data that cannot be inferred from “consuming” (reading, listening to, watching) the content.

All properties are optional. The order of the properties in this set is flexible: the non-repeatable properties MUST come first and then the repeatable properties may be inserted in any order.

Table 2. Administrative Metadata Group Elements

Element Title	Element Name	Card	Described on Page
Urgency	urgency	(0..1)	179
Date Content Created	contentCreated	(0..1)	79
Date Content Modified	contentModified	(0..1)	80
Located	located	(0..unbounded)	130
Information Source	infoSource	(0..unbounded)	119
Creator	creator	(0..unbounded)	77
Contributor	contributor	(0..unbounded)	72
Audience	audience	(0..unbounded)	49
Excluded Audience	exclAudience	(0..unbounded)	96
Alternative Identifier	altId	(0..unbounded)	44

2.9.1.1 Dates Processing Model

Two optional dates are associated with the content of an Item.

contentCreated (page 79) and **contentModified** (page 80) processing rules:

DatesGeneral.1: If the value provided by any date/time field does not conform to the appropriate syntax (e.g. format “YYYY-MM-DDTHH:MM:SS[+-]MM:SS”) it MUST be considered as being not existent.

DateValues.1: If *contentCreated* is present it MUST NOT be later than **versionCreated** (page 83).

Error handling if it is later: at the creator's site an error alert should be issued, on the receiver's site it should be set to *versionCreated*.

DateValues.2: If *contentModified* is present *contentCreated* SHOULD be present as well.

In this case *contentModified* MUST NOT be earlier than *contentCreated*.

Error handling if it is earlier: at the creator's site an error alert should be issued, on the receiver's site it should be set to *contentCreated*

DateValues.3: If *contentModified* is present it MUST NOT be later than *versionCreated*.



Error handling if it is later: at the creator's site an error alert should be issued, on the receiver's site it should be set to versionCreated.

DateProcessing.1: The recipient processor MUST first check if a contentModified element is present.

DateProcessing.2: If not it MUST check if a contentCreated element is present.

DateProcessing.3: If not it SHOULD assume that the content was created at the time indicated by versionCreated element in itemMeta.

2.9.1.2 Audience Processing Model

Audience processing may be used to form ad hoc groups of recipients for which the Item is particularly significant or to filter out some users from the list of intended recipients of an Item.

The audience is expressed as a set of “positive” values (**audience** (page 49) and a set of “negative” values. The logic is to make the content easy to find to the audience identified by the positive values, but keep this content away from the audience identified by the negative values. An attribute of each property may indicate the expected significance of the content for this specific audience, and acts as a threshold for recipient filters.

The model for the audience processing is only a part of the overall filter that is used to determine whether a particular recipient is entitled to have access to the Item. It could be combined with the processing of other properties to further narrow the number of Items that match the recipient profile.

The processing rule has to be considered as a function which returns TRUE to indicate the recipient is entitled to receive the content, FALSE in case he is not entitled and NULL if the item does not contain any audience statements that apply to the Recipient.

Audience processing rules:

Audience.1: If any of the exclAudience properties applies to the recipient: return FALSE

Audience.2: If any of the audience properties applies to the recipient: return TRUE.

Audience.3: Return NULL.

2.9.2 Descriptive Metadata

This is a set of properties associated with the descriptive facet of news content, i.e. data that can be inferred from “consuming” (reading, listening to, watching) the news.

All properties are optional, repeatable and may be inserted in any order.

Table 3. Descriptive Metadata Group Elements

Element Title	Element Name	Card	Described on Page
Language	language	(0..unbounded)	126
Genre	genre	(0..unbounded)	103
Subject	subject	(0..unbounded)	174
Slugline	slugline	(0..unbounded)	172
Headline	headline	(0..unbounded)	109
Dateline	dateline	(0..unbounded)	89
By	by	(0..unbounded)	53
CreditLine	creditline	(0..unbounded)	78
Description	description	(0..unbounded)	91

2.9.3 Other Content Metadata

Each provider may add a set of metadata properties which have to be defined in a non-IPTC namespace. See also **XML Namespaces** (page 37) and **Extension Points in XML** (page 38).



2.10 Part Metadata

Streamed content may be split into different sections (called “shots” in the video world). Images may also be split in regions.

A specific set of metadata MAY be associated with any individual content part. Such metadata is wrapped in a **partMeta** (page 144) element, which is repeatable in the newsItem and MUST be inserted after contentMeta.

Each part MAY have a part identifier (partId) and a sequence number (seq).

Each part MAY be illustrated by an icon - e.g. a keyframe of a video clip - which takes the form of an IRI. It is not mandatory for such icon to be a pure extraction of the content.

A section of a stream MAY be defined by a time delimiter (timeDelim). The time scope is expressed as *start* and *end* timestamp attributes plus an additional time unit (*timeunit*) attribute.

A region of an image MAY be defined by a region delimiter (*regionDelim*). In the current release, regions are limited to rectangles defined by {x, y, width, height} coordinates in pixels expressed as a set of attributes.

If, during the processing of the content, it appears that part delimiters do not correspond to any physical content, then the corresponding set of metadata MUST simply be discarded.

News Administrative and Descriptive Metadata may be applied to each part, in complement to the administrative and descriptive metadata applicable to the whole content.

Each provider may add a set of metadata properties which have to be defined in a non-IPTC namespace. See also **XML Namespaces** (page 37) and **Extension Points in XML** (page 38).

Note that partMeta is specific to the newsItem structure, and this feature is not present in other classes of Items.

2.10.1 Edit Units and Time Codes

It is recommended that time and durations are expressed in “edit units” (EditUnit), which represent the smallest editable portion of content, i.e. a video frame or an audio sample.

$\text{EditUnit} = 1 / \text{EditRate}$.

For video, the EditRate is the FrameRate.

For audio, the EditRate is the SampleRate.

The use of EditUnit is independent of the mode of representation of time (e.g. timecode) in editing devices. The timecode associates one value to each video frame or audio sample.

For video, the usual timecode format is HH:MM:SS:FF (Hours:Minutes:Seconds:Frames).

In the case of simple frame rates (e.g. 25 fps, 30 fps, 50 fps or 60 fps), the conversion of a number of EditUnits to timecode is simple.

However, there exist other frame rates (e.g. 29.97 fps, 59.94fps) for which this calculation requires more attention. A precise calculation would consist of replacing e.g. 29.97 fps by its exact value $1.001/30$ fps and multiplying the number of EditUnits by 1.001 before conversion on the basis of 30 fps. Another method consists of calculating the timecode using the drop frame method defined in SMPTE 12M. The drop frame method is an approximation based e.g. on 29.97 fps ($1.001001001/30$ fps). The drop frame timecode is not systematically used, particularly if content is of a short duration with insignificant drift with the actual clock time. SMPTE 12M will evolve as it doesn't address higher frame rates with progressive scanning.

For audio, the usual video timecode (HH:MM:SS:FF) is used if the content also contains video. A time restricted timecode (HH:MM:SS) is often used for audio only content, although it can be completed by a number of complementary frames or its conversion in hundredths or thousandths of a second.



The time reference will be the one of reception or edition in the production system, which should be able to locate content in time based on the number of EditUnits.

2.10.2 Assertions About Concepts

When a concept is used as the value of many properties, it may be useful to group supplemental information about this concept at a unique location.

The optional and repeatable `assert` property provides information about a concept identified by a qualified code. The information is given as a set of properties relative to the concept. Many assertions may be included in an Item.

Any property of the concept may be included at this point, especially its name, its relationships with other concepts, its definition.

Note: This information is only up to date at the time of last modification of the Item.

2.11 References to Inline Concepts

When the same concept appears as a string in several different labels or in the textual content of a newsItem, it may be useful to group information about this concept at a unique location.

The optional and repeatable `inlineRef` (page 114) property provides information about a concept found in some textual content. The string associated with the concept can be tagged by any element which provides an attribute of type ID. One or more local identifiers **MAY** be listed as value of the `idrefs` attribute of the `inlineRef` element.

The concept **MUST** be identified either by a qualified code or a literal value, and supplemental information **MAY** be given as a set of properties relative to the concept.

It is possible to offer alternative identifications of a concept if the concept extraction leads to ambiguous results. In this case several `inlineRef` properties will use the same local identifier.

It is possible to give values for the confidence with which the metadata has been assigned, the relevance of the metadata to the string to which it is attached, and why the metadata has been included.

2.12 newsItem Content

Content may be included by value or by reference, and useful characteristics are represented along with such content, in order to facilitate its processing.

Alternative renditions of the news content, i.e. different technical representation of the same logical content, are wrapped by a `contentSet` (page 71) wrapper element. Their order of appearance in `contentSet` is of no relevance. Their presence is optional: this allows for a lightweight and progressive representation of information.

Each rendition **SHOULD** be defined by a `rendition` attribute.

All alternative renditions **SHOULD** be derived from an original rendition by a software processor. For example: images in different resolutions, vector graphics and alternative bitmap images, text in different formats (e.g. NITF and PDF). The rendition from which all other renditions originate is indicated by the `original` attribute of `contentSet`; this attribute takes as a value the local identifier (`id`) of the original content component included in the `contentSet`.

They are three kinds of content components, inline XML, inline data and remote content:

- ◆ The `inlineXML` (page 115) wrapper element holds XML content which is directly embedded in the element. The root element of this structure must be the root element of the language. Content may belong to any XML language capable of expressing generic or specialized news information, e.g. NITF, XHTML, SportsML or XBRL. The XML vocabulary is identified by a content type attribute (`contenttype`).
- ◆ The `inlineData` (page 112) wrapper element holds plain-text or base64 encoded content. Plain text or CDATA content **MUST** be identified by the "text/plain" content type. Binary content, like images,



audio clips or even PDF or Word documents may be exchanged after proper encoding, but it is strongly recommended to use this structure for small assets only. The encoding algorithm MAY be indicated using the *encoding* attribute. In the absence of this attribute, the content must be plain text, and the content type must be set accordingly. Encoding is not constrained to base64 at this level of conformance.

- ◆ The **remoteContent** (page 159) wrapper element may be used for representing any kind of media and data format. The data is stored independently of the newsItem and is referenced via a hyperlink (*href*). The size in bytes of the remote content MAY be indicated. The element MAY also have **time-ValidityAttributes** (page 224) (*validfrom* and *validto*) which express the date and time between which the reference is active. The same rendition of content MAY be present at different remote locations. In such a case the same value of the *rendition* attribute MAY be given to several remote-Content elements.

The description of the content in each content component MAY be complemented by a content type (*contenttype*), a format acting as an optional refinement of the content type, an indication on the software tool used to generate the content (*generator*) and the date and time when the content was generated, plus additional news content characteristics.

2.13 News Content Characteristics

newsContentCharacteristics (page 225) are these physical properties of media content like the height and width of a picture, the word count of a news story or the duration of an audio clip, that help making selections among alternate renditions of news content.

The characteristics defined by the IPTC are a small and typical set of properties. Individual providers may add more characteristics they consider reasonable, i.e. audio data for professional broadcasting may require a different set from audio content for a podcast.

2.14 Channels

Some binary streams support the notion of channel or track: this is e.g. the case for DVD's, which are MPEG-2 encoded and provide several audio tracks in different languages. It may be important to indicate media characteristics on a per-channel level.

A repeatable **channel** (page 58) element MAY therefore be defined as a child of a **remoteContent** (page 159) element.

Each logical channel MAY have a local identifier (*chnid*), an indication of the media type of the data conveyed by the channel and an indication of the role the data plays in the scope of the full content, e.g. "voice over".

Each logical channel MAY be additionally described by the news content characteristics corresponding to the media conveyed in the channel.

3 Representing Concept Information - concept Component

3.1 Concept Component

Concepts fall in two broad categories: named entities and generic (or abstract) concepts. Generic concepts range from themes (e.g. soccer) to emotions (e.g. smiling, love); they have no specific property defined, beyond generic properties. Named entities are people, organisations, geopolitical areas, points of interest and objects for which a specific set of properties is defined for the purpose of a refined definition and improved search and processing capabilities.

The **concept** (page 59) element provides a set of properties shared by all concepts.

A concept can be identified in different schemes by different controlled values, this is why a concept identifier must be unambiguous, but cannot be unique: for example, a company is commonly identified by different ticker symbols. In the case of abstract topics, the strict sameness of two concepts may be subject to discussion, and therefore a notion of equivalence of concepts is preferred.

A concept **MUST** have a concept identifier, expressed as `conceptId` child elements.

The `conceptId` element **MUST** have a `qcode` attribute. It **MAY** have a `created` attribute and a `retired` attribute which limit the usage of the concept identifier in time.

A concept **MAY** have a `type` child element. The type of a concept reflects its nature, e.g. generic, person, organisation, geopolitical area, point of interest etc...

A concept **MAY** have a name and **MAY** be further defined in natural-language by a definition and note. These labels are repeatable and **MAY** be specified in multiple languages.

More detailed facets of a concept (e.g. that the concept “is” an artist, listed company, city, restaurant) **MAY** be expressed by a specific facet property. The facet property **MAY** have a `rel` attribute which specifies the exact facet which is described.

Different variants of a name are allowed. The `role` attribute the semantic of the property and takes values like “usual”, “official”, “married” (for a person) “acronym” (for an organisation), “synonym”, “adjectival” (e.g. French for France). The `part` attribute identifies the part of the name conveyed by the property, and takes values like “given”, “family” (for a person). Definitions and notes also support a role, which takes values like “history”, “change” (for a description), “editorial”, “scope” (for a note).

The descriptive elements name, definition and note and facet **MAY** have `validfrom` and `validto` attributes which limit the use of the property in time.

A concept **MAY** have a set of alternative identifiers, expressed as **sameAs** (page 168) child elements.

The `sameAs` element **MUST** have either a `qcode` or a literal attribute which identifies a concept. It **MAY** additionally have a `type` attribute which reflects the nature of the associated concept, and **MAY** have one or more names (see **Flexible 1 Property Type** (page 199)). `validfrom` and `validto` attributes **MAY** limit the relationship in time.

3.2 Relationships Between Concepts

A concept **MAY** be associated with other concepts in the form of a taxonomy (i.e. a hierarchy of concepts) or thesaurus (i.e. a set of concepts associated via standard relationships). A concept **MAY** have an indication of most standard relationships as **broader** (page 52), **narrower** (page 135) and **related** (page 157) child elements.

The `broader`, `narrower` and `related` properties **MUST** have either a `qcode` or a literal attribute which identifies a concept. They **MAY** additionally have a `type` attribute which reflects the nature of the associated concept, and **MAY** have one or more names (see **Flexible 1 Property Type** (page 199)).

The `broader`, `narrower` and `related` properties **MAY** also have `validfrom` and `validto` attributes which limit the relationship in time, a `rel` attribute which details the name given to the relationship and a `rank` attribute which specifies the rank of the current concept among concepts having a relationship to the target concept. They also have a `facet` child property for expressing an intrinsic property of the related concept.



The *related* property has a *bag* property for allowing the expression of composite concepts (see [Composite Concepts](#) on page 34).

3.3 Details on Specific Entities

Details associated with specific entities MAY additionally be defined. All have been chosen for their potential usefulness in the news industry.

personDetails (page 146) include a date of birth (*born*) and date of death (*died*) a repeatable indication of affiliation with an organisation and contact information (*contactInfo*).

organisationDetails (page 142) include a date of foundation (*founded*) and date of dissolution (*dissolved*), a repeatable location and contact information (*contactInfo*).

The registered address of an organisation is indicated as part of its contact information; in such a case this address may not be used for making direct contact with this company.

geoAreaDetails (page 105) include the geographic coordinates (*position*) of the place.

The position MUST have *latitude* and *longitude* attributes. It MAY have an indication of the altitude above the zero elevation reference level.

It MAY have an indication of coordinate reference system (*gpsdatum* attribute) expressed as a string. In the absence of this attribute, the WGS84 system is assumed.

POIDetails (page 148) include the geographic coordinates (*position*) of the place, plus practical information like opening hours (*openHours*), capacity, access information, details on the location (e.g. room number, stair number etc.), and contact information (*contactInfo*).

objectDetails (page 139) include a date of creation, a creator of the object and a copyright notice.

3.3.1 Contact Information

contactInfo (page 65) is repeatable in the definition of a person, an organisation and a Point of Interest, and each set of properties supports a *role* attribute which makes possible to group together all information belonging of the same nature.

Contact information include email addresses, instant messaging addresses (*im*), international phone numbers, international fax numbers, web addresses, postal addresses and notes.

E-mail and instant messaging addresses, phone and fax number are all electronic addresses. These are qualified by a *role* attribute which specifies the nature of the address, e.g. home or work.

3.3.2 Postal Address

The definition of a Postal Address (**address** (page 149)) includes free-text lines (in the format expected by a recipient postal service), the indication of a locality (i.e. city, town, village etc...), a subdivision of a country (*area*), a country and a postal code (*postalCode*).

A postal address is structured as a set of properties likely edited and displayed as a form. The relative order of its properties is not universal, and if used for traditional postal mail, presentation algorithms are to be developed which depend on the source and recipient countries.

The city, country area and country may be indicated as a name or as a controlled value. The use of an ISO compliant country code is particularly recommended.



4 Managing Individual Concepts - conceptItem

An XML Schema file corresponding to the specifications for this item is available (see [The Full Set of Specification Documents](#) on page 3).

4.1 Description

A [conceptItem](#) (page 62) aims to convey knowledge about a unique concept (a named entity such as an organisation or an abstract notion such as a news subject). Typically a conceptItem itself holds only rather short and structured information about the concept and about its relationships with other concepts.

Typical characteristics of a conceptItem are:

- ◆ It focuses on a single concept or entity.
- ◆ It will usually be updated infrequently but over a long period of time, when the information about the concept evolves.
- ◆ Its content is of long term interest.
- ◆ It may be referenced by other items.

Different conceptItems, managed by different providers, may contain structured information about the same concept.

4.2 Structure of a conceptItem

The model of a conceptItem is very similar to the model of a newsItem. Both share the same Indication of compliance with a standard and conformance level, Identification and versioning, Signature, Rights Information, Item Metadata, Item links. Please review the corresponding specification of a newsItem for more information.

Note that the globally unique guid of a conceptItem, which is used for management purposes, must not be confused with the unambiguous concept identifier ([conceptId](#) (page 61)) defined by an authority and conveyed as part of the content of the Item.

4.3 Item Metadata

The IPTC provides a standardised scheme applicable to the [itemClass](#) (page 120) property, identified by the URI: <http://cv.iptc.org/newscodes/cinature/>.

4.4 Concept related Metadata

The set of administrative metadata is common to all classes of Items. Please review [Representing News - newsItem](#) (page 13) for more information.

A conceptItem does not support descriptive metadata.

4.5 conceptItem Content

The content of a conceptItem is a concept component.

5 Managing Sets of Concepts - knowledgeltem

An XML Schema file corresponding to the specifications for this item is available (see [The Full Set of Specification Documents](#) on page 3).

5.1 Description

A **knowledgeltem** (page 125) bundles a set of concept components which are managed and exchanged as a whole. A knowledgeltem is used best where a provider wants to circulate a snapshot of a set of entries from one or more controlled vocabularies.

The concepts represented in a knowledgeltem can be of different types, and their identifiers may come from different schemes. A “scheme definition” is therefore a particular case of structure, where all concepts support a concept identifier from a same specific scheme.

Examples of knowledgeltems are the taxonomy of IPTC Subject NewsCodes or an authority list of people’s descriptions maintained by a given provider.

Typical characteristics of a knowledgeltem are:

- ◆ It contains a meaningful set of concepts components.
- ◆ It will usually be updated infrequently but over a long period of time, for example when a controlled vocabulary evolves.
- ◆ Its content is of long term interest.

5.2 Structure of a knowledgeltem

The model of a knowledgeltem is very similar to the model of a newsItem. Both share the same Indication of compliance with a standard and conformance level, Identification and Versioning, Signature, Rights Information, Item Metadata, Item links. Please review [Representing News - newsItem](#) (page 13) for more information.

5.3 Item Metadata

The IPTC provides a standardised scheme applicable to the **itemClass** (page 120) property, identified by the URI <http://cv.iptc.org/newscodes/cinature/>.

5.4 Knowledge Related Metadata

The set of administrative metadata is common to all classes of Items. Please review the corresponding specification of a newsItem for more information.

The set of descriptive metadata is listed below. All properties are optional, repeatable and may be inserted in any order.

Table 4. Knowledge Descriptive Metadata Group Elements

Element Title	Element Name	Card	Described on Page
Subject	subject	(0..unbounded)	174
Description	description	(0..unbounded)	91

Each provider may add a set of metadata properties which have to be defined in a non-IPTC namespace. See also [XML Namespaces](#) (page 37) and [Extension Points in XML](#) (page 38).

5.5 knowledgeltem Content

A **conceptSet** (page 64) wrapper element contains a set of concept components. Their order of appearance in conceptSet is not relevant.

Note: All concept definitions share the same catalog of schemes, declared at the top of the knowledgeltem.



6 Packaging Items - **packageltem**

An XML Schema file corresponding to the specifications for this item is available (see [The Full Set of Specification Documents](#) on page 3).

A **packageltem** (page 143) facilitates the packaging of all kinds of Items, from really simple constructs to the highly hierarchical structures created by some news providers.

Examples of **packageltems** are a collection of pictures, a “top ten” list of **newsItems**, an unordered set of **newsItems** relative to the same event, the representation of a newspaper section or page.

Typical characteristics of a Package Item are:

- ◆ It provides some structure to news related information, and is expressed via a hierarchy of items.
- ◆ The Items found in a **packageltem** stay independent from the package: they can be managed individually, and the package keeps only references to them.
- ◆ Its content is of medium term interest.

6.1 Structure of a **packageltem**

The model of a **packageltem** is very similar to the model of a **newsItem** (page 136). Both share the same Indication of compliance with a standard and conformance level, Identification and versioning, signature, rights information, Item metadata, Item links. Please review the corresponding specification of a **newsItem** for more information.

6.2 Item Metadata

The IPTC provides standardised schemes applicable to the **itemClass** property of a **packageltem**, identified by the URI <http://cv.iptc.org/newscodes/ninature/> and <http://cv.iptc.org/newscodes/cinature/>.

6.3 Package Related Metadata

The set of administrative and descriptive metadata is common between **packageltems** and **newsItems**. Please review [Representing News - newsItem](#) (page 13) for more information.

6.4 **packageltem** Content

A **groupSet** (page 108) represents a tree of Items. All Items of a package are included by reference, as physical inclusion would break the capability to manage inner Items independently of the outer Package Item.

The **groupSet** is optional. This allows for a lightweight and progressive representation of information.

There **MUST** be at least one group element in the **groupSet**. If there is more than one group in the **groupSet** element, a specific group acts as the root of the tree. In this case the value of *root* attribute of the **groupSet** element **MUST** be the local reference to the group acting as a root.

A group component contains references to other group components (**groupRef** (page 107) with its *idref* attribute) and references to Items or Web resource (**itemRef** (page 122) with its *guidref* and *href* attributes), in any order.

Each group **MAY** have a *role* attribute which indicates the part this group plays within its container.

The order of the sub-groups and references to Items **MAY** be significant; a *mode* attribute indicates whether the elements in the group are complementary and unordered, complementary and ordered or a set of alternative elements. In the absence of a *mode* attribute the group is treated as complementary and unordered.

The **itemRef** element **MAY** contain metadata extracted from the target Item or Web resource. All metadata **SHOULD** be included directly as children of the **itemRef** element, without any wrapper element (e.g. neither **itemMeta** nor **contentMeta**). The recipient **MUST NOT** consider that such hints constitute a complete representation of the Item.



The itemRef element MAY have a *rank* attribute which represents the rank of the Item among other Items in each group.

The itemRef element MAY also have time validity attributes (*validfrom* and *validto*) which express the date and time between which the reference is active.

Sample:

```
<groupSet root="g1">
  <group id="g1" mode="mode:seq" role="group:main">
    <groupRef idref="g2"/>
    <itemRef guidref="urn:newsml:iptc.org:20070530:tutorial-text-xhtml"/>
  </group>
  <group id="g2" role="group:gallery">
    <itemRef guidref="urn:newsml:iptc.org:20070530:tutorial-iptc-logo"/>
    <itemRef guidref="urn:newsml:iptc.org:20070530:tutorial-video"/>
  </group>
</groupSet>
```




7 Dealing with Controlled Values

7.1 {scheme, code} Pair, Scheme URI and Concept URI

Many properties usually have their value taken from a well defined scheme, i.e. a controlled vocabulary (i.e. a classification system, authority list, taxonomy, thesaurus etc ...).

These values are represented by a formal combination - a {scheme, code} pair - primarily intended to be consumed by processing software. A scheme is logically a closed set of related concepts, and a {scheme, code} pair unambiguously identifies a single concept.

A scheme is in practice a list of codes managed by a specific authority (which we shall refer to as the Scheme Authority), which may be the IPTC or any other well known standardisation body, or may be an individual news provider. A {scheme, code} pair therefore fully identifies a term from a controlled vocabulary (i.e. a scheme). A code **MUST** be persistent over time in order to avoid ambiguities when processing archives documents.

A scheme is fully and unambiguously identified by a scheme URI. The concept represented by a code is fully and unambiguously identified by a concept URI. The concept URI is obtained by appending the code to the scheme URI. **Qualified Code (QCode)** (page 31) shows how a more compact form of a concept identifier is used in the news workflow.

As an example, an IPTC scheme for news categories might be identified by the URI "http://cv.iptc.org/newscodes/theme/". If the code "15000000" represents the concept of "Sport", then the concept URI for "Sport" would be "http://cv.iptc.org/newscodes/theme/15000000".

It is not mandatory that the Scheme Authority maintains the complete list of codes making up a given scheme in any particular form, e.g. as an XML file. It is sufficient that an unambiguous identifier is defined for each scheme a provider uses, and that this identifier is known to the customers of the news feed this provider offers.

Common needs are:

- ◆ To access human readable information about a scheme.
- ◆ To retrieve all terms of a scheme (e.g. to display a list of choice).
- ◆ To access human readable information about a qualified code.
- ◆ To check that a qualified code belongs to a scheme.
- ◆ To retrieve the definition of the concept identified by a qualified code in a given scheme.

Therefore the scheme URI **SHOULD** resolve to a resource (or resources) containing information about the scheme in both human-readable and machine-readable forms. Meeting this requirement is mandatory for schemes which are to be compliant with the Semantic Web.

The concept URI **SHOULD** also resolve to a resource (or resources) containing information about the concept in both human-readable and machine-readable forms. Meeting this requirement is mandatory for concept URIs which are to be compliant with the Semantic Web.

If content negotiation is implemented using HTTP, then the HTTP Accept header should be used to request information in the required format and the HTTP Accept-Language header should be used to request information in the required human language.

When designing a scheme URI, the following points should be taken into consideration:

- ◆ Each scheme URI must end with a suitable terminating character, e.g. "/" or "#". Each of these has various advantages and disadvantages, which are discussed extensively in documents available on the Web.
- ◆ One point worth mentioning here is that not all strings which can be used to construct a legal URI are automatically legal in the context of HTML. For example, "http://cv.iptc.org/newscodes/theme.html#15000000" is not a legal HTML URI, as an HTML fragment name cannot start with a digit.



7.2 Qualified Code (QCode)

In order to manipulate controlled values in an efficient manner, a compact representation of a concept identifier is needed, a syntax which allows the use of a {scheme, code} pair as the value of an XML attribute.

For this purpose a short string called scheme alias (aka prefix) is defined by a provider as a substitute for a scheme URI in the scope of a single Item, and a compact notation of a scheme-code pair is defined, called qualified code or QCode.

The datatype for a compact notation of a scheme-code pair is called qualified code or more simply QCode. QCodes are the mandatory way to express controlled values in properties like **itemClass** (page 120) or **pubStatus** (page 154).

QCodes are notated by the following syntax: a scheme alias acting as a first part, followed by a colon (:) character, followed by a code from the scheme. They are case sensitive.

The value space of the **QCodeType** (page 214) datatype is a set of {scheme, code} pairs which identify concepts.

Note that:

- ◆ This is similar to the value space of the QName datatype, i.e. a set of {namespace, local part} pairs which identify element or attribute names.

Note: QNames cannot be used for this purpose, because the local part of QNames cannot be a numeric, but the News industry and the Financial industry are full of taxonomies making use of numeric codes. They aren't alone in this aspect (consider ISBN and ISSN).

- ◆ QCodes allow any sequence of legal URI characters in the code part, including, for example, digits only, dashes, slashes, etc.
- ◆ QCodes MUST have a non-empty scheme alias.

QCodes can be viewed to a certain extent as short, lexical representations of URIs. Be careful: the mapping from a qualified code to a URI is not bijective: a URI cannot be mapped back to a qualified code, because the separator of the tuple is not explicitly defined in the URI.

In order to resolve a qualified code, a processor MUST loop through the scheme elements defined in the scope of the Item. If the QCode scheme alias is found as value of the *alias* attribute of a scheme element, the scheme URI is the associated *uri* attribute and the controlled value is the resulting {scheme URI, code} pair. If no corresponding scheme alias is found, the processor SHOULD raise an error and consider that the property has no value.

7.2.1 Processing QCodes

For processing QCodes properly a processor has to comply to these three rules:

- ◆ Syntax Space for Aliases: all characters except colon (#x3A) and white space (#x20 | #x9 | #xD | #xA).
- ◆ Syntax Space for Codes: all characters except white space (#x20 | #x9 | #xD | #xA).
- ◆ Processing Rule: To split a QCode term into its alias and code part the parser has to identify the first colon searching from left to right. If it encounters one the string to the left is the alias, the string to the right is the code. If it encounters none the QCode is invalid.

7.3 Processing Catalogs

7.3.1 Structure of a Catalog

A **Catalog** (page 55) MUST have one or more scheme elements. A catalog MAY have one or more titles in different languages. It MAY also have a pointer to some additional information available on the Web, and especially its evolution and latest version. Such information will help people follow the evolution of a



shared catalog like the IPTC G2 catalog, and include in their Items a reference to the latest version if they wish.

It **MUST** have one or more scheme elements. A scheme element **MUST** have a scheme *alias* attribute and a corresponding scheme *uri* attribute.

Each Item defines its own set of scheme definitions, and there is no interaction between scheme definitions in different Items. Scheme alias declarations are local to the Item in which they appear and cannot be overridden in a given Item.

7.3.2 Processing Remote Catalogs

By activating the hyperlink of a remoteCatalog (see [catalogRef](#) on page 158), a plain catalog structure is returned, and **MUST** be processed as if were locally defined.

7.3.3 Caching a Catalog

It is recommended for a processor to cache a remote catalog indefinitely, so that provider's servers are not overcharged with file requests.

When a processor opens an Item, it **MUST** check the URL(s) of the catalog(s) found in its header. If a catalog has not been previously cached, the processor **MUST** fetch it, check it, and **SHOULD** store its content in a cache.

Different remote catalogs **MAY** define different mappings for a given scheme alias. An entry in a remote catalog cache is therefore a triple {remote catalog URL, scheme alias, scheme URI}.

7.3.4 Checking a Catalog

It is OK for one scheme URI to have two aliases. It is an error if one alias is mapped to two different URIs in the scope of a single Item (an issue called alias collision). Note that this error may arise within a catalog, as well as across a set of catalogs (local or remote) declared in a given Item.

Before processing an Item, a processor **MUST** check its catalogs. If an alias collision is found, the processor **MUST** reject the Item as it can lead to misinterpretation of the information.

Note: If an aggregator finds an alias collision (i.e. the same alias associated with two URIs) while creating a packageItem which aggregates content from various providers, the aggregator **MUST** change one or both of the aliases before publishing the packageItem. This can be done by creating and publishing one or more non-clashing external catalogs (which replace the original external catalogs) and/or by replacing one or more external catalogs with non-clashing in-line scheme declarations.

7.4 Processing Schemes

7.4.1 Evolution of Scheme URIs

Schemes evolve: terms are added, names are changed, terms are retired. An authority will release a new version after each update. A provider may not want to adopt the latest version of a scheme. The scheme URI **MUST** be stable as long as the evolution does not break backward compatibility rules.

7.4.2 Retrieving All Terms of a Scheme

Here we are interested in schemes defined as an explicit list of terms. Schemes defined via an algorithm are out of scope of this section. A scheme definition is defined as the finite set of terms composing a scheme. A scheme definition **MAY** be a subset of an original scheme, e.g. maintained by an external authority.

Note: An authority is not necessarily able to make scheme definitions available for operational use, and a provider may use only a subset of the scheme defined by an authority.

A provider **SHOULD** make a scheme definition available for its users for operational use as the content of a knowledgeItem, where each term is represented as a concept component, i.e. a concept identifier, a list of names in one or more languages, plus additional properties of the concept (all but the identifier being optional).



An authority MAY provide different variants of a scheme definition, e.g. a list of codes, a list of codes plus a name in a specific language, a list of codes plus names in all available languages.

For each variant of a scheme definition, the URL of the corresponding knowledgeitem SHOULD be available using e.g. content negotiation.

Selection from among the renditions MAY be performed automatically (if the processor is capable of doing so) or manually by the user selecting from a hypertext menu.

7.5 Qualified and Typed Properties

Qualified properties – of datatype **QualPropType** (page 215) – only support controlled values in the format of QCodes.

A large subset of these properties supports concepts of different types as a value. Therefore typed qualified properties – of datatype **TypedQualPropType** (page 221) – additionally provide a concept type relative to the value of the property.

For example, the type of the concept assigned as subject of a news story may be a theme (e.g. sport or football), a person, an organisation, a geographical area, a point of interest, an event, a business sector, a currency etc. The concept type of a **creator** (page 77), **contributor** (page 72) and **infoSource** (page 119) of an Item may be a person or an organisation

Qualified properties MAY be complemented by one or more names associated with the underlying concept. Names can be expressed in different languages or variants.

7.6 Flexible Properties

It is not always possible or sensible to use a QCode as metadata value. As an example, few news organisations maintain a formal listing of their editors, and therefore using a controlled value for the creator property is not always possible.

In order to fulfil this need, a large number of properties allow for literal values – i.e. uncontrolled free-text values – to be applied instead of controlled values.

Therefore flexible properties – of datatype Flexible Property Type or a derived datatype – support both controlled (qcode) and uncontrolled (literal) values.

QCodes and literals are mutually exclusive for one property, but either one or the other MUST be indicated.

The value of a flexible property identifies a given concept with a specific type. It is useful to express e.g. that the provider of a news item is a person or an organisation. The *type* of the concept MAY be indicated as an attribute of the flexible property.

One or more additional name properties MAY be provided in different languages and variants for display purpose.

Such metadata MAY be usually given when the property value is a QCode, but MAY also be provided when the property value is a literal. If the value is a literal and no additional name is given, the recipient MAY use the literal value for direct display.

Flexible properties MAY also be complemented by other information about the concept, like properties from Concept Relationships Group (see **Table 146** on page 183) and Concept Definition Group (see **Table 145** on page 183).

Flexible properties which value specifically identifies a person, an organisation or any other entity for which detailed properties are defined in this specification, MAY contain detailed information about this entity, e.g. a date of birth for a person or a location for an organisation.

Such information constitutes “hints” about the concept, which may be useful for display or indexing, but which should not be used to convey knowledge stored as-is in a knowledge repository. A specific mechanism, based on conceptItems and knowledgeItems, is set-up in the News Architecture for managing knowledge.



7.7 Composite Concepts

Several flexible properties support composite concepts. Composite concepts, a.k.a. pre-coordinated terms, are “glued” together to represent a concept made of atomic parts.

Therefore flexible concept properties – of datatype **Flexible 1 Concept Property Type** (page 197) – have a bag child element which is used to express a new concept, composed from multiple existing concepts. The description of each existing concept is placed in a bit child element of the bag wrapper.

Examples of possible composite concepts are:

- ◆ John Doe Smiling {John Doe + Smiling }
- ◆ Women's 100m Swimming Final {Women + Swimming + 100m + Final}
- ◆ Positive pre-announcement by Citigroup {Citigroup + Pre-announcement + Positive}
- ◆ Microsoft's share price has moved up {Microsoft + Share price + Up}
- ◆ The Clintons {Bill Clinton + Hillary Clinton}

7.8 Editing Attributes

In a professional and collaborative news workflow, it makes sense to identify all elements defined by the model in order to later act on them individually. Also, metadata is not always entered by one person at one time, but may be entered by different people, organisations or systems at different time. Therefore it may be needed to keep track of who is assigned the editing of specific properties, and when and by whom a property has been given a value.

For this purpose, all metadata properties share an Editing Attributes Group (see **Table 189** on page 223), i.e. an optional local identifier (id) and the optional indication of the creator and the date (and, optionally, the time) when the property was last modified.



8 Dealing with Labels and Blocks

8.1 Introduction

Labels expose aspects of news as natural language strings. They are assertions expressed as natural language strings intended to be consumed by human beings. They are typically displayed alongside the content of an Item or in place of Items in a list, providing a means of selection among them.

Blocks are simply labels with an additional line break. They are primarily used for notes, comments or instructions created by a news provider for use by recipient editorial teams.

Labels and blocks MAY have a *role* attribute, which refines the semantics of the property.

Labels and blocks MAY have a *media* attribute. When present, the value MUST conform to the Cascading Style Sheets specification [CSS]. Several media types can be given as space separated values.

All labels and blocks support rich text, i.e. text interspersed with some specific markup, identical to XHTML1.1 markup: the anchor ([a](#) (page 47)) for the inclusion of hyperlinks, the [span](#) (page 173) as a generic mechanism for adding information to text, simple [ruby](#) (page 164) markup used in Japanese publications and [inline](#) (page 111) for semantic inline markup.

The inline property identifies a concept present in a label or block either by a qualified code or a literal value, plus an optional type. Additional information about this concept can be represented using an [assert](#) (page 48) property.

8.2 Internationalization Attributes

In an international news workflow, fine grained control of language information in the hierarchy of nodes constituting an Item is needed.

For this purpose, all labels – and all ancestors of such an element – share an International Attributes Group (see [Table 188](#) on page 223) , i.e. an optional language tag (xml:lang) and indication of the directionality of textual content (dir).



9 Exchanging Items - newsMessage

A **newsMessage** (page 137) facilitates the exchange of all kinds of items by any kind of digital transmission, especially in a broadcast or multicast network.

The content of a newsMessage is an **itemSet** (page 123) component.

An itemSet contains a set of newsItems, packageItems, conceptItems and knowledgeItems. The model assigns no significance to the order of Items within the News Message.

The use of a News Message is totally optional in a news workflow. Alternatively, Items may be exchanged using SOAP, WebDAV, ICE, the Atom Publication Protocol (using Atom feeds, and items as payload of an Atom entry) or any other possible syndication protocol.

It may be useful for a recipient to store the information conveyed by a message, but this is not mandatory. Usually the messaging information will be maintained separately from the information relative to the contained items.

9.1 Message Information

A newsMessage **MUST** have a date of transmission (sent). The date of transmission **MAY** not be updated in case of retransmission of the message.

A newsMessage **MAY** have a sender child element, which may be an organisation or a person. The structure of this string is not specified by the IPTC. Best practice is to identify a sender by its domain name

It **MAY** have a transmission identifier (transmitId) and a priority of transmission. No two newsMessages sent by the same sender on the same date can have the same identifier. In case of retransmission it is not required to update this identifier. The structure of this string is not specified by the IPTC.

It **MAY** indicate the point of origin of the message, using a provider defined syntax.

It **MAY** have one or more **timestamp** (page 176)(s) associated with the message. The exact meaning of this timestamp may be refined by a *role* attribute.

It **MAY** have one or more destination(s) using a provider defined syntax, and the indication of one or more channel(s) of transmission.

Each particular provider is equally able to add to this set information of its own, by mutual agreement with the recipients of the Item.

9.2 About Using Schemes in a newsMessage

It is important to note that a newsMessage does not define any catalog that would be common to the Items it contains. There is no interaction between the scheme declarations present in different Items exchanged in a newsMessage.



10 Specification Reference

This section provides all specifications for this G2-Standards, the different specifications tables are cross referenced from other parts of this document.

10.1 Introduction to the Common Components

News exchange formats share many metadata properties as they are about the same data: something newsworthy to be exchanged. For that reason the family of IPTC G2-Standards share a large set of properties which are common to all family members and this common data model and set of specifications is called the IPTC News Architecture for G2-Standards (NAR).

This Specification Reference section provides a mix of specifications coming from the NAR and additionally from this G2-Standard.

The components specified in this Specification Reference can be split into these 3 groups:

1. Fine grained components, called a datatype. A datatype has no specific business meaning or semantics of its own and only takes on business meaning when used as the data type of a property. Datatypes fall in two groups:
 - Simple data types are primitive data types, as found in software languages or XML schema definitions (e.g.. integer, string). Some restriction may be imposed, such as `Int100Type` where an integer has been restricted to a value range of 0 to 100.
 - Complex data types are simple data types extended to add further information in order to correctly represent the value. Such ancillary information takes the form of attributes. For example a `LabelType` supports mixed content and is extended with language and role attributes.

For a G2-Standard the names of datatypes end with a "Type" suffix (e.g. `QCodeType`).

2. Medium grained components, called basic component or property. A property represents a single piece of business information and uses an existing data type or defines it own local datatype to provide its content model. It is capable of being used independently or as part of a group. Like a complex data type, a basic component can be qualified by ancillary data if required to complete its meaning. For example, a slugline element of data type string supports an additional separator attribute.
3. Coarse grained components, called aggregate component. It is a collection of properties that together is more than the sum of its constituent parts. The properties composing the whole can be properties or aggregate components. An aggregate component may be designed so it supports an extension point where news providers can extend its usage. For example, a descriptive component is defined as a group of properties like title and subject, and a person component is defined as a group of properties like name and date of birth.

10.2 General Specifications

10.2.1 XML Namespaces

Table 5. XML Namespaces

Namespace URI	Recommended Alias	Usage Note
http://iptc.org/std/nar/2006-10-01/	nar	For all common components of the IPTC G2-Standards.



10.2.2 MIME Types

Namespace URI	Usage Note
application/vnd.iptc.g2.newsitem+xml	For all kinds of G2 News Items.
application/vnd.iptc.g2.conceptitem+xml	For all kinds of G2 Concept Items.
application/vnd.iptc.g2.packageitem+xml	For all kinds of G2 Package Items.
application/vnd.iptc.g2.knowledgeitem+xml	For all kinds of G2 Knowledge Items.

10.2.3 Extension Points in XML

For attributes: each element of a G2-Standard allows to add provider specific attributes from any other XML namespace than the News Architecture for G2 namespace (see [XML Namespaces](#) on page 37).

For elements: Some elements which have child elements allow to add provider specific elements from any namespace other than the News Architecture for G2 namespace (see [XML Namespaces](#) on page 37). A few elements allow adding any element from any XML namespace - including the News Architecture for G2 namespace - but this is a special case only.

10.3 Implementation Design Rules

These design rules were applied while developing the G2-Standards. Some apply to all kinds of technical implementations, other only to one specific implementation. Further some rules are only applicable at one of the Conformance Levels CCL or PCL.

- ◆ Each element supports editing attributes (PCL).
- ◆ Each element has an extension point at the attribute level (XML implementation only).
- ◆ Each element containing an international string supports i18 attributes (CCL).
- ◆ Each ancestor of an element containing an international string supports i18 attributes (PCL).
- ◆ Children of wrapper elements: mandatory children come first, they are in a specific order, optional (and in most case multiple) elements follow, they can be inserted in an arbitrary order (XML implementation only).
- ◆ Each wrapper element has an extension point as its last child element (XML implementation only).

10.4 Processing Model Terminology

For many components of the G2-Standards this specification provides also a processing model. Find below how these processing instructions should be read.

- ◆ A Processing Model provides rules for the proper processing of metadata properties and their values. Each rule may be divided into steps.
- ◆ Each rule gets an integer number assigned, steps for this rules are indicated as decimals to this number. Example: rule 12, step 3 = 12.3
- ◆ Many rules can be considered like a function in programming, hence as a sequence of processing steps in the scope of a block. These terms will be used for defining the rules and are based on this basic layout:
 - “quit” = the processing of this function stops at this step and quits the current context to the calling context.
 - “quit and return ...” = see “quit”, plus: a value of “...” is returned to the calling context.
 - “if ... :” = a condition is expressed and right to the colon the processing that results from meeting this condition.
 - If the condition is NOT met the default processing is “proceed to the next step of this processing rule”. A specific processing for this case is preceded by the term “otherwise”.

10.5 Component Structure Format

Table 6 describes the component (element and datatype) specifications of the G2 data model. This table is divided into two sections:

- ◆ The upper section contains the specification of generic properties of the component.
- ◆ The lower section(s) contain the specification of the component based on the W3C XML Schema 1.0 (XMLSCHEMA-1.0) specifications. This section may contain different specifications at the Core Conformance Level (CCL) and the Power Conformance Level (PCL) of the G2 data model.

Descriptions of the individual specifications can be found in **Table 6**.

Table 6. Component Structure Format

(XML) Data Model	Defines a high-level data model for this component. The value is one out of: simple datatype/complex datatype/element/attribute group.
Namespace (Prefix)	Namespace for the name of this component. Is either <i>nar</i> for the generic G2-Standards namespace or a prefix for any other namespace. Which prefix is assigned to which namespace is defined by a heading section of a G2-Standard specification document.
Name	The technical reference of the component (must align with the name in the XML Schema!).
Title	The natural-language label of the component.
Definition	A concise definition of the semantics of the component.
User Note(s)	Any notes addressing the (end-)user of the component with a focus on its proper use.
Implementation Note(s)	Any notes addressing the implementer of the component into any technical system.
XML Schema Spec	At: Both CCL and PCL / CCL / PCL; indicates at which conformance levels this XML Schema specification applies.
Datatype	The XML Schema datatype or any datatype defined by a G2-Standard.
Internally Ctrl Values	A definition of one or more values if they are controlled by the XML Schema, e.g. an enumeration or regular expression.
Externally Ctrl Values	A definition of any controlled vocabulary with values to be (exclusively) used with this component.
Attribute(s)	One or more XML attributes defined for this component if it is either a complex datatype, an element, or an attribute group.
Child Element(s)	One or more child elements defined for this component if it is either a complex datatype or an element.
XML Schema Note(s)	Any notes regarding the implementation of this component into the XML Schema of this G2-Standard.
Example(s)	One or more XML snippets showing use-cases for this component.



10.6 Element Definitions

10.6.1 Access

Table 7. Access

(XML) Data Model	Element
Namespace (prefix)	nar
Name	access
Title	Access
Definition	Ways to access the place, including directions.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	BlockType (page 189)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.2 Accountable Person

Table 8. Accountable Person

(XML) Data Model	Element
Namespace (prefix)	nar
Name	accountable
Title	Accountable Person
Definition	An individual accountable for the content in legal terms.
User Note(s)	This property answers to a legal issue. In some countries (e.g. Germany, Sweden) it is needed to designate a person accountable for any legal issue related to the published content. The full translation from the German term is: accountable person in terms of the press law - (For reference in German: Verantwortlich im Sinne des Presserechts -acronym = ViSdP), in Swedish it is called "Ansvarig utgivare". In practice today, a news provider may send out a message each day which indicates the "accountable person". This may work for traditional feed services, but fails with profiled services (content selections) which filter such messages. The solution is to include this information in the Items themselves.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	FlexPersonPropType (page 203)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.3 Address Line

Table 9. Address Line

(XML) Data Model	Element
Namespace (prefix)	nar
Name	line
Title	Address Line
Definition	A line of address information, in the format expected by a recipient postal service. City, country area, country and postal code are expressed separately.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	IntlStringType (page 207)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.4 Affiliation

Table 10. Affiliation

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	affiliation		
Title	Affiliation		
Definition	An affiliation of the person with an organisation.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	FlexOrganisationPropType (page 201)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ timeValidityAttributes (page 224) 	Name	Datatype
		validfrom (0..1)	DateOptTimeType
		validto (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.5 Alternative Identifier

Table 11. Alternative Identifier

(XML) Data Model	Element
Namespace (prefix)	nar
Name	altId
Title	Alternative Identifier
Definition	Alternative identifier allocated to the content.
User Note(s)	If there is more than one alternative identifier, they SHOULD be qualified using the type qualifier to distinguish between different identification schemes.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	IntlStringType (page 207).
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ type (0..1); QCodeType (page 214); A qualifier which indicates the context within which the alternative identifier has been allocated. ▪ environment (0..1); QCodeListType (page 212); A qualifier which indicates the business environment in which the identifier can be used to access the content
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.6 Alternative Locator

Table 12. Alternative Locator

(XML) Data Model	Element
Namespace (prefix)	nar
Name	altLoc
Title	Alternative Locator
Definition	An alternative location of the asset representing the content.
User Note(s)	If there is more than one alternative locator, they SHOULD be qualified using the type attribute to distinguish between different identification schemes.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	IRIType (page 208)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ type (0..1); QCodeType (page 214); A qualifier which indicates the context within which the alternative locator has been allocated. ▪ role (0..1); QCodeType (page 214); A refinement of the semantics or business purpose of the property.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.7 Alternative Representation

Table 13. Alternative Representation

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	altRep		
Title	Alternative Representation		
Definition	An IRI which, upon dereferencing provides an alternative representation of the Item.		
User Note(s)	This property is particularly useful if the Item is available in different formats (for example NewsML 1, IIM or NITF) or with different levels of details (for instance with different granularity of metadata).		
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	IRIType (page 208)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ representation (0..1); QCodeType (page 214); A qualifier which specifies the way the targetItem is represented at this location. ▪ contenttype (0..1); XML Schema string; The IANA (Internet Assigned Numbers Authority) MIME type of the target resource. ▪ format (0..1); QCodeType; A refinement of a generic content type (i.e. IANA MIME type). ▪ size (0..1); XML Schema nonNegativeInteger; The size in bytes of the target resource. 		
	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
	▪ timeValidityAttributes (page 224)	Name	Datatype
		validfrom (0..1)	DateOptTimeType
		validto (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.8 Anchor

Table 14. Anchor

(XML) Data Model	Element									
Namespace (prefix)	nar									
Name	a									
Title	Anchor									
Definition	An anchor for inline linking like in HTML.									
User Note(s)										
Implementation Note(s)	This element is modelled after its XHTML 1.0 counterpart.									
XML Schema Spec	At: PCL									
Datatype										
Internally Ctrl Values										
Externally Ctrl Values										
Attribute(s)	<ul style="list-style-type: none"> ▪ class (0..1); XML Schema String; An equivalent of the HTML class attribute. ▪ href (0..1); IRIType (page 208); An equivalent of the HTML href attribute. ▪ hreflang (0..1); XML Schema NMTOKEN; An equivalent of the HTML hreflang attribute. ▪ rel (0..1); XML Schema string; An equivalent of the HTML rel attribute. ▪ rev (0..1); XML Schema string; An equivalent of the HTML rev attribute. 									
	▪ editAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>id (0..1)</td> <td>XML Schema ID</td> </tr> <tr> <td>creator (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>modified (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>	Name	Datatype	id (0..1)	XML Schema ID	creator (0..1)	QCodeType	modified (0..1)	DateOptTimeType
		Name	Datatype							
		id (0..1)	XML Schema ID							
	creator (0..1)	QCodeType								
	modified (0..1)	DateOptTimeType								
	▪ i18nAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>xml:lang (0..1)</td> <td>XML Schema language</td> </tr> <tr> <td>dir (0..1)</td> <td>XML Schema string: enumeration <i>ltr</i>, <i>rtl</i>.</td> </tr> </tbody> </table>	Name	Datatype	xml:lang (0..1)	XML Schema language	dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .		
		Name	Datatype							
		xml:lang (0..1)	XML Schema language							
	dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .								
Child Element(s)	<ul style="list-style-type: none"> ▪ span (page 173) (0..unbounded) ▪ ruby (page 164) (0..unbounded) ▪ inline (page 111) (0..unbounded) ▪ Extension Point (0..unbounded). Any set of provider-defined properties. 									
	XML Schema Note(s)									
	Implementation of the attributes aligns with the XHTML 1.0 specs.									
	Example(s)									



10.6.9 Assertion

Table 15. Assertion

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	assert		
Title	Assertion		
Definition	An assertion about a concept.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ qcode (1); QCodeType (page 214). A concept identifier.		
	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
	▪ i18nAttributes (page 223)	modified (0..1)	DateOptTimeType
		Name	Datatype
xml:lang (0..1)		XML Schema language	
dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .		
Child Element(s)	▪ Extension Point (0..unbounded). Any set of provider-defined properties.		
XML Schema Note(s)			
Example(s)			



10.6.10 Audience

Table 16. Audience

(XML) Data Model	Element
Namespace (prefix)	nar
Name	audience
Title	Audience
Definition	An intended audience for the content.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	AudienceType (page 188)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.11 Bag

Table 17. Bag

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	bag		
Title	Bag		
Definition	A group of existing concepts which express a new concept.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
	▪ i18nAttributes (page 223)	modified (0..1)	DateOptTimeType
		Name	Datatype
		xml:lang (0..1)	XML Schema language
dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .		
Child Element(s)	▪ bit (page 51) (1..unbounded)		
XML Schema Note(s)			
Example(s)			



10.6.12 Bag Item

Table 18. Bag Item

(XML) Data Model	Element
Namespace (prefix)	nar
Name	bit
Title	Bag Item
Definition	An individual concept, part of a composite concept expressed by a bag.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	QCodePropType (page 213)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.13 Broader

Table 19. Broader

(XML) Data Model	Element
Namespace (prefix)	nar
Name	broader
Title	Broader
Definition	An identifier of a more generic concept.
User Note(s)	<p><i>rank</i> (available at the PCL only) is suitable for use in a Knowledge Item representing a scheme. It is used when it is important that the Child Elements of a particular term are displayed in a user interface in a predefined order.</p> <p>For example, the major currencies could be given a rank of "1", while all other currencies could be given a rank of "2". Terms of the same rank are ordered alphabetically by name if this is available. If the name is not available, the terms are ordered by code value. Terms without a rank are treated as if they all have the same rank, which is higher than the rank of all other terms.</p> <p>The same concept may have different ranks in different concept trees. A lower rank results in a placement earlier in a display.</p>
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	RelatedConceptType (page 217)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> rank (0..1); XML Schema nonNegativeInteger; Specifies the rank of the concept among the children of a given broader concept.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.14 By

Table 20. *By*

(XML) Data Model	Element
Namespace (prefix)	nar
Name	by
Title	By
Definition	A natural-language statement about the creator (author, photographer etc.) of the content.
User Note(s)	The <i>by</i> label provides a natural-language statement of the author/creator information (commonly called the byline); it may include a byline title, i.e. the author's job title. Examples of bylines are RUPAK DE CHOWDHURI (a person), isotype.com (a provider) or STR (a stringer). It is up to the provider to decide if the label starts with a word like "By".
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Label1Type (page 209)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.15 Capacity

Table 21. Capacity

(XML) Data Model	Element
Namespace (prefix)	nar
Name	capacity
Title	Capacity
Definition	Total capacity of the place in natural language.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Label1Type (page 209)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.16 Catalog

Table 22. Catalog

(XML) Data Model	Element									
Namespace (prefix)	nar									
Name	catalog									
Title	Catalog									
Definition	A local or remote catalog.									
User Note(s)										
Implementation Note(s)										
XML Schema Spec	At: PCL									
Datatype										
Internally Ctrl Values										
Externally Ctrl Values										
Attribute(s)	<ul style="list-style-type: none"> ▪ additionalInfo (0..1); IRIType (page 208); A pointer to some additional information about the Catalog, especially its evolution and latest version. 									
	▪ editAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>id (0..1)</td> <td>XML Schema ID</td> </tr> <tr> <td>creator (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>modified (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>	Name	Datatype	id (0..1)	XML Schema ID	creator (0..1)	QCodeType	modified (0..1)	DateOptTimeType
		Name	Datatype							
		id (0..1)	XML Schema ID							
creator (0..1)	QCodeType									
modified (0..1)	DateOptTimeType									
Child Element(s)	<ul style="list-style-type: none"> ▪ title (page 124) (0..unbounded) ▪ scheme (page 169) (1..unbounded) 									
XML Schema Note(s)										
Example(s)										



10.6.17 Channel of Remote Content

Table 23. Channel of Remote Content

(XML) Data Model	Element
Namespace (prefix)	nar
Name	channel
Title	Channel of Remote Content
Definition	Information about a specific content channel.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	



Table 23. Channel of Remote Content (Continued)

Attribute(s)	<ul style="list-style-type: none"> ▪ chnlid (0..1); XML Schema positiveInteger; A logical identifier of the channel 		
	<ul style="list-style-type: none"> ▪ type (0..1); QCodeType (page 214); The media type of the data conveyed by the channel. 		
	<ul style="list-style-type: none"> ▪ role (0..1); QCodeType (page 214); The role the data of this channel plays in the scope of the full content. 		
	<ul style="list-style-type: none"> ▪ newsContentCharacteristics (page 225) 		
		Name	Datatype
		Word Count	XML Schema nonNegativeInteger
		Image Width	XML Schema nonNegativeInteger
		Image Height	XML Schema nonNegativeInteger
		Image Orientation	XML Schema nonNegativeInteger
		Image Colour Space	QCodeType
		Resolution	XML Schema positiveInteger
		Duration	XML Schema nonNegativeInteger
		Audio Codec	QCodeType
		Audio Bit Rate	XML Schema positiveInteger
		Audio Variable Bit Rate flag	XML Schema boolean
		Audio Sample Size	XML Schema positiveInteger
		Audio Sample Rate	XML Schema positiveInteger
		Audio Channels	QCodeType
		Video Codec	QCodeType
		Video Average Bit Rate	XML Schema positiveInteger
	Video Variable Bit Rate flag	XML Schema boolean	
	Video Frame Rate	XML Schema positiveInteger	
	Video Scan Technique	enumeration progressive/interlaced	
	Video Aspect Ratio	XML Schema normalizedString	
	Video Sampling Method	XML Schema normalizedString	
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.18 Channel for News Message

Table 24. Channel for News Message

(XML) Data Model	Element
Namespace (prefix)	nar
Name	channel
Title	Channel for News Message
Definition	A transmission channel used by the message.
User Note(s)	A channel identifier is used to provide recipients with information for selecting, routing, or handling otherwise the content of the message. The channels represent streams in a multiplex: a message may be sent on different channels – e.g. one for text, one for pictures – and each reception point will be able to filter on channel values. The structure of this string is not specified by the IPTC.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	XML Schema string
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.19 Concept

Table 25. Concept Definition

(XML) Data Model	Element													
Namespace (prefix)	nar													
Name	concept													
Title	Concept													
Definition	A set of properties defining a concept.													
User Note(s)														
Implementation Note(s)														
XML Schema Spec	At: Both CCL and PCL													
Datatype														
Internally Ctrl Values														
Externally Ctrl Values														
Attribute(s)	<ul style="list-style-type: none"> ▪ conceptId (page 61) (1) ▪ type (page 178) (0..1) ▪ name (page 63) (1..unbounded) ▪ definition (page 60) (0..unbounded) ▪ note (page 138) (0..unbounded) ▪ facet (page 99) (0..unbounded) 													
Child Element(s)	<ul style="list-style-type: none"> ▪ Concept Relationships Group (page 183) (0..1) 	<table border="1"> <thead> <tr> <th>Element Name</th> <th>Page</th> </tr> </thead> <tbody> <tr> <td>broader (0..unbounded)</td> <td>52</td> </tr> <tr> <td>narrower (0..unbounded)</td> <td>135</td> </tr> <tr> <td>related (0..unbounded)</td> <td>157</td> </tr> <tr> <td>sameAs (0..unbounded)</td> <td>168</td> </tr> </tbody> </table>	Element Name	Page	broader (0..unbounded)	52	narrower (0..unbounded)	135	related (0..unbounded)	157	sameAs (0..unbounded)	168		
		Element Name	Page											
		broader (0..unbounded)	52											
		narrower (0..unbounded)	135											
		related (0..unbounded)	157											
	sameAs (0..unbounded)	168												
	<ul style="list-style-type: none"> ▪ Entity Details Group (page 183) (0..1) 	<table border="1"> <thead> <tr> <th>Element Name</th> <th>Page</th> </tr> </thead> <tbody> <tr> <td>geoAreaDetails (1)</td> <td>105</td> </tr> <tr> <td>organisationDetails (1)</td> <td>142</td> </tr> <tr> <td>personDetails (1)</td> <td>146</td> </tr> <tr> <td>POIDetails (1)</td> <td>148</td> </tr> <tr> <td>objectDetails (1)</td> <td>139</td> </tr> </tbody> </table>	Element Name	Page	geoAreaDetails (1)	105	organisationDetails (1)	142	personDetails (1)	146	POIDetails (1)	148	objectDetails (1)	139
		Element Name	Page											
		geoAreaDetails (1)	105											
		organisationDetails (1)	142											
personDetails (1)		146												
POIDetails (1)	148													
objectDetails (1)	139													
<ul style="list-style-type: none"> ▪ Extension Point (0..1). Any set of provider-defined properties. 														
XML Schema Note(s)														
Example(s)														



10.6.20 Concept Definition

Table 26. Concept Definition

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	definition		
Title	Concept Definition		
Definition	A natural-language definition of the semantics of the concept. This definition is normative only for the scope of the use of this concept.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	BlockType (page 189)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ timeValidityAttributes (page 224)	Name	Datatype
		validfrom (0..1)	DateOptTimeType
		validto (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.21 Concept Identifier

Table 27. Concept Identifier

(XML) Data Model	Element
Namespace (prefix)	nar
Name	conceptId
Title	Concept Identifier
Definition	The preferred unambiguous identifier for the concept.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	ConceptIdType (page 190)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.22 Concept Item

Table 28. Concept Item

(XML) Data Model	Element
Namespace (prefix)	nar
Name	conceptItem
Title	Concept Item
Definition	An Item containing information about a concept.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	AnylItemType (page 186)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	▪ contentMeta (page 66) (0..1)
	▪ assert (page 48) (0..unbounded)
	▪ inlineRef (page 114) (?)
	▪ concept (page 59) (0..1)
XML Schema Note(s)	
Example(s)	



10.6.23 Concept Name

Table 29. Concept Name

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	name		
Title	Concept Name		
Definition	A natural-language name for the concept.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	IntlStringType (page 207).		
Internally Ctrl Values			
Externally Ctrl Values	Recommended IPTC NewsCodes for the <i>part</i> attribute: http://cv.iptc.org/newscodes/namepart/		
Attribute(s)	<ul style="list-style-type: none"> ▪ role (0..1); QCodeListType (page 212); A refinement of the semantics of the name. ▪ part (0..1); QCodeType (page 214); Specifies which part of a full name this property provides. 		
	▪ timeValidityAttributes (page 224)	Name	Datatype
		validfrom (0..1)	DateOptTimeType
	validto (0..1)	DateOptTimeType	
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.24 Concept Set

Table 30. Concept Set

(XML) Data Model	Element
Namespace (prefix)	nar
Name	conceptSet
Title	Concept Set
Definition	An unordered set of concepts.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	▪ concept (page 59) (0..unbounded)
XML Schema Note(s)	
Example(s)	



10.6.25 Contact Information

Table 31. Contact Information

(XML) Data Model	Element
Namespace (prefix)	nar
Name	contactInfo
Title	Contact Information
Definition	Information to get in contact with the entity expressed by the wrapping property.
User Note(s)	The <i>role</i> attribute addresses the role of the full set of contact information with regards to the entity defined by the concept. Examples: "privateOffice" vs "companyOffice" or "GlobalHeadquarters" vs "localHeadquarterUK".
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	Recommended IPTC NewsCodes for the "role" of an event's contact information: http://cv.iptc.org/newscodes/eventcontactinfo/
Attribute(s)	<ul style="list-style-type: none"> ▪ <i>role</i> (0..1); QCodeListType (page 212); A refinement of the semantics of the set of contact information.
Child Element(s)	<ul style="list-style-type: none"> ▪ email (page 95) (0..unbounded) ▪ im (page 118) (0..unbounded) ▪ phone (page 147) (0..unbounded) ▪ fax (page 100) (0..unbounded) ▪ web (page 182) (0..unbounded) ▪ address (page 149) (0..unbounded) ▪ note (page 138) (0..unbounded) ▪ Extension Point (0..unbounded). Any set of provider-defined properties.
XML Schema Note(s)	
Example(s)	

10.6.26 Content Metadata for Concept Items

Table 32. Content Metadata for Concept Items

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	contentMeta		
Title	Content Metadata for Concept Items		
Definition	Content Metadata for a Concept Item		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ i18nAttributes (page 223)	Name	Datatype
		xml:lang (0..1)	XML Schema language
		dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .
Child Element(s)	▪ Administrative Metadata Group (page 184) (0..1)	▪ icon (page 110) (0..1)	
		Element Name	Page
		audience (0..unbounded)	49
		contributor (0..unbounded)	72
		creator (0..unbounded)	77
		contentCreated (0..1)	79
		contentModified (0..1)	80
		located (0..unbounded)	130
		infoSource (0..unbounded)	119
		urgency (0..1)	179
	exclAudience (0..unbounded)	96	
	altId (0..unbounded)	44	
	▪ Extension Point (0..unbounded). Any set of provider-defined properties.		
XML Schema Note(s)			
Example(s)			



10.6.27 Content Metadata for Knowledge Items

Table 33. Content Metadata for Knowledge Items

(XML) Data Model	Element			
Namespace (prefix)	nar			
Name	contentMeta			
Title	Content Metadata for Knowledge Items			
Definition	Content Metadata for a Knowledge Item.			
User Note(s)				
Implementation Note(s)				
XML Schema Spec	At: PCL			
Datatype				
Internally Ctrl Values				
Externally Ctrl Values				
Attribute(s)	▪ i18nAttributes (page 223)	Name	Datatype	
		xml:lang (0..1)	XML Schema language	
		dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .	
Child Element(s)	▪ icon (page 110) (0..1)			
		▪ Administrative Metadata Group (page 184) (0..1)	Element Name	Page
			audience (0..1)	49
			contributor (0..unbounded)	72
			creator (0..unbounded)	77
			contentCreated (0..1)	79
			contentModified (0..1)	80
			located (0..unbounded)	130
			infoSource (0..unbounded)	119
			urgency (0..1)	179
			exclAudience (0..unbounded)	96
			altId (0..unbounded)	44
		▪ Knowledge Descriptive Metadata Group (page 184) (0..1)	Element Name	Page
description (0..unbounded)	91			
	subject (0..unbounded)	174		
	▪ Extension Point (0..unbounded). Any set of provider-defined properties.			
XML Schema Note(s)				
Example(s)				



10.6.28 Content Metadata for News Items

Table 34. Content Metadata for News Items

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	contentMeta		
Title	Content Metadata for News Items		
Definition	A set of properties about the content.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ i18nAttributes (page 223)	Name	Datatype
		xml:lang (0..1)	XML Schema language
		dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .
Child Element(s)	▪ icon (page 110) (0..1)	Element Name	Page
		audience (0..unbounded)	49
	▪ Administrative Metadata Group (page 184) (0..1)	contributor (0..unbounded)	72
		creator (0..unbounded)	77
		contentCreated (0..1)	79
		contentModified (0..1)	80
		located (0..unbounded)	130
		infoSource (0..unbounded)	119
		urgency (0..1)	179
		exclAudience (0..unbounded)	96
		altId (0..unbounded)	44
		▪ Descriptive Metadata Group (page 184) (0..1)	Element Name
	by (0..unbounded)		53
	creditline (0..unbounded)		78
	dateline (0..unbounded)		89
	description (0..unbounded)		91
	genre (0..unbounded)		103
headline (0..unbounded)	109		
language (0..unbounded)	126		
slugline (0..unbounded)	172		
subject (0..unbounded)	174		
▪ Extension Point (0..unbounded). Any set of provider-defined properties.			
XML Schema Note(s)			
Example(s)			



10.6.29 Content Metadata for Package Items

Table 35. Content Metadata for Package Items

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	contentMeta		
Title	Content Metadata for Package Items		
Definition	A set of properties about the content.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ i18nAttributes (page 223) 	Name	Datatype
		xml:lang (0..1)	XML Schema language
		dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .
Child Element(s)	<ul style="list-style-type: none"> ▪ icon (page 110) (0..1) 	Element Name	Page
		audience (0..unbounded)	49
	<ul style="list-style-type: none"> ▪ Administrative Metadata Group (page 184) (0..1) 	contributor (0..unbounded)	72
		creator (0..unbounded)	77
		contentCreated (0..1)	79
		contentModified (0..1)	80
		located (0..unbounded)	130
		infoSource (0..unbounded)	119
		urgency (0..1)	179
		exclAudience (0..unbounded)	96
		altId (0..unbounded)	44
		<ul style="list-style-type: none"> ▪ Descriptive Metadata Group (page 184) (0..1) 	Element Name
	by (0..unbounded)		53
	creditline (0..unbounded)		78
	dateline (0..unbounded)		89
	description (0..unbounded)		91
	genre (0..unbounded)		103
headline (0..unbounded)	109		
language (0..unbounded)	126		
slugline (0..unbounded)	172		
subject (0..unbounded)	174		
	<ul style="list-style-type: none"> ▪ Extension Point (0..unbounded). Any set of provider-defined properties. 		
XML Schema Note(s)			
Example(s)			



10.6.30 Content Provider

Table 36. Content Provider

(XML) Data Model	Element
Namespace (prefix)	nar
Name	provider
Title	Provider
Definition	The party responsible for the management and the release of the Item.
User Note(s)	This corresponds to the publisher of the Item.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	FlexPartyPropType (page 202)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.31 Content Set

Table 37. Content Set

(XML) Data Model	Element
Namespace (prefix)	nar
Name	contentSet
Title	Content Set
Definition	A set of alternate renditions of the Item content.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ original (0..1); XML Schema idref; A local reference to the original piece of content, from which all renditions have been derived.
Child Element(s)	<ul style="list-style-type: none"> ▪ inlineXML (page 115) (0..unbounded) or ▪ inlineData (page 112) (0..unbounded) or ▪ remoteContent (page 159) (0..unbounded)
XML Schema Note(s)	
Example(s)	



10.6.32 Contributor

Table 38. Contributor

(XML) Data Model	Element
Namespace (prefix)	nar
Name	contributor
Title	Contributor
Definition	A party (person or organisation) which modified or enhanced the content, preferably the name of a person.
User Note(s)	One may specify the role the party plays in the creation of the content (e.g. a caption writer for photos) at the PCL.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Extends FlexPartyPropType (page 202)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ role (0..1); QCodeListType (page 212); A refinement of the semantics of the property. ▪ jobtitle (0..1); QCodeType (page 214); The job title of the creator in the news provider organisation.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.33 Copyright Holder

Table 39. Copyright Holder

(XML) Data Model	Element
Namespace (prefix)	nar
Name	copyrightHolder
Title	Copyright Holder
Definition	The person or organisation claiming the intellectual property for the content.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	FlexPartyPropType (page 202)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.34 Copyright Notice

Table 40. Copyright Notice

(XML) Data Model	Element
Namespace (prefix)	nar
Name	copyrightNotice
Title	Copyright Notice
Definition	Any necessary copyright notice for claiming the intellectual property for the resource.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	RightsLabelType (page 218)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.35 Country

Table 41. Country

(XML) Data Model	Element
Namespace (prefix)	nar
Name	country
Title	Country
Definition	A country, part of the address.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Flex1PropType (page 199)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.36 Country Area

Table 42. Country Area

(XML) Data Model	Element
Namespace (prefix)	nar
Name	area
Title	Country Area
Definition	A subdivision of a country, part of the address.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Flex1PropType (page 199)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.37 Creator

Table 43. Creator

(XML) Data Model	Element
Namespace (prefix)	nar
Name	creator
Title	Creator
Definition	A party (person or organisation) which created the resource.
User Note(s)	One may specify the role the party plays in the creation of the content (e.g. a caption writer for photos) at the PCL.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Extends FlexPartyPropType (page 202)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ role (0..1); QCodeListType (page 212); A refinement of the semantics of the property. ▪ jobtitle (0..1); QCodeType (page 214); The job title of the creator in the news provider organisation.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.38 Credit Line

Table 44. Credit Line

(XML) Data Model	Element
Namespace (prefix)	nar
Name	creditline
Title	Credit Line
Definition	A free-text expression of the credit(s) for the content.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	IntlStringType
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.39 Date Content Created

Table 45. Date Content Created

(XML) Data Model	Element
Namespace (prefix)	nar
Name	contentCreated
Title	Date Content Created
Definition	The date (and optionally the time with the time zone) at which the content was created.
User Note(s)	In the case of a photo or live footage for audio and video, this date (and time) is always the same as the date (and time) of the event covered by the content. In the case of text and any audio and video report about an event, this date (and time) can be different from the date (and time) of the event covered by the content. This date (and time) may also be different from the date (and time) of the creation of an Item holding the content.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	TruncatedDateTimePropType (page 219)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.40 Date Content Modified

Table 46. Date Content Modified

(XML) Data Model	Element
Namespace (prefix)	nar
Name	contentModified
Title	Date Content Modified
Definition	The date (and optionally the time with the time zone) at which the content was last modified.
User Note(s)	The value of this property should be updated each time the content is modified in any manner, but should not be updated if only metadata are changed.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	TruncatedDateTimePropType (page 219)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.41 Date Item Embargo Ends

Table 47. Date Item Embargo Ends

(XML) Data Model	Element
Namespace (prefix)	nar
Name	embargoed
Title	Date Item Embargo Ends
Definition	The date and time (with the time zone) before which all versions of the Item are embargoed. If absent, the Item is not embargoed.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	DateTimePropType (page 194)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.42 Date Item First Created

Table 48. Date Item First Created

(XML) Data Model	Element
Namespace (prefix)	nar
Name	firstCreated
Title	Date Item First Created
Definition	The date and time (with the time zone) on which the first version of the Item was created.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	DateTimePropType (page 194)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.43 Date Item Version Created

Table 49. Date Item Version Created

(XML) Data Model	Element
Namespace (prefix)	nar
Name	versionCreated
Title	Date Item Version Created
Definition	The date and time (with the time zone) on which the current version of the Item was created.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	DateTimePropType (page 194)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.44 Date of Birth

Table 50. Date of Birth

(XML) Data Model	Element
Namespace (prefix)	nar
Name	born
Title	Date of Birth
Definition	The date of birth of the person.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	TruncatedDateTimePropType (page 219)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.45 Date of Death

Table 51. Date of Death

(XML) Data Model	Element
Namespace (prefix)	nar
Name	died
Title	Date of Death
Definition	The date of death of the person.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	TruncatedDateTimePropType (page 219)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.46 Date of Dissolution

Table 52. Date of Dissolution

(XML) Data Model	Element
Namespace (prefix)	nar
Name	dissolved
Title	Date of Dissolution
Definition	The date of dissolution of the organisation.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	TruncatedDateTimePropType (page 219)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.47 Date of Foundation

Table 53. Date of Foundation

(XML) Data Model	Element
Namespace (prefix)	nar
Name	founded
Title	Date of Foundation
Definition	The date of foundation/establishment of the organisation.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	TruncatedDateTimePropType (page 219)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.48 Date of Transmission

Table 54. Date of Transmission

(XML) Data Model	Element
Namespace (prefix)	nar
Name	sent
Title	Date of Transmission
Definition	The date and time (with the time zone) of transmission of the message.
User Note(s)	May not be updated in case of retransmission of the message.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	XML Schema dateTime
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.49 Dateline

Table 55. Dateline

(XML) Data Model	Element
Namespace (prefix)	nar
Name	dateline
Title	Dateline
Definition	A natural-language statement of the date and/or place of creation of the content.
User Note(s)	The dateline provides a natural-language statement of the date and/or place of the news content creation, to be displayed in situations where an abstract of the content is shown (case of search results) or the content is remote. Traditionally a dateline indicates when and where news content is created, not necessarily the time and place relative to the news event. As an example a dateline BAGHDAD, March 26, 2007 (AFP) could head a story about blast in Mosul, because the story was actually written in Baghdad. Also, by tradition a dateline will follow the stylebook of the information provider and possibly leave out certain time and location information that could be useful for specifying searches of a database. Editorial policy dictates the dateline; it is not automatically derivable from other markup (location, date, etc.). The dateline should not end with a separating character (of the kind that separates the dateline from the first sentence in a traditional wire story).
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Label1Type (page 209)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	

10.6.50 Recurrence Group

This group of properties defines the information required to specify a recurrence set. The recurrence set is the complete set of recurrence instances for a calendar component. The model follows the iCalendar specification [RFC2445].

At least one *rDate* or *rRule* element **MUST** be present. These elements **MUST** come first in the group. Then the *exDate* and *exRule* elements **MAY** be inserted in any order.

Table 56. Recurrence Group Elements

Element Title	Element Name	Card	Described on Page
Recurrence Date	rDate	(0..unbounded)	155
Recurrence Rule	rRule	(0..unbounded)	156
Exclusion Date	exDate	(0..unbounded)	97
Exclusion Rule	exRule	(0..unbounded)	98



10.6.51 Date Resource Created

Table 57. Date Resource Created

(XML) Data Model	Element
Namespace (prefix)	nar
Name	created
Title	Date Resource Created
Definition	The date (and optionally the time with the time zone) on which the resource was created.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	TruncatedDateTimePropType (page 219)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.52 Description

Table 58. Description

(XML) Data Model	Element
Namespace (prefix)	nar
Name	description
Title	Description
Definition	A free-form textual description of the content of the item. (For a Knowledge Item the content is its set of concepts as a whole.)
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	BlockType (page 189)
Internally Ctrl Values	
Externally Ctrl Values	Recommended IPTC NewsCodes for the <i>role</i> attribute: http://cv.iptc.org/newscodes/descriptionrole/
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.53 Destination

Table 59. Destination

(XML) Data Model	Element
Namespace (prefix)	nar
Name	destination
Title	Destination
Definition	The point(s) of destination of the message.
User Note(s)	In a broadcast delivery system, the destination is a group of reception points (using a provider-specific syntax, often geographically oriented). This is a way to address customers. Examples are "England", "USA", "Austria/Vienna", "France/Paris/LeParisien". The structure of this string is not specified by the IPTC.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	XML Schema string
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.54 Editorial Note

Table 60. Editorial Note

(XML) Data Model	Element
Namespace (prefix)	nar
Name	edNote
Title	Editorial Note
Definition	A note addressed to the editorial people receiving and processing the Item. If edNote is a child element to plannedCoverage (EventsML-G2) this property provides additional natural language information about the planned coverage.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	BlockType (page 189)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.55 Editorial Service

Table 61. Editorial Service

(XML) Data Model	Element
Namespace (prefix)	nar
Name	service
Title	Editorial Service
Definition	An editorial service to which an Item is assigned to by its provider. If service is a child element to plannedCoverage (EventsML-G2), this property indicates by which editorial service the planned G2 item(s) will be published.
User Note(s)	The values of this property are defined by each provider, and are often associated with the notion of a desk or a feed. Some examples are a “French wire service”, an “international picture service” or a “mobile news service”.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	QualPropType (page 215)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.56 Email Address

Table 62. Email Address

(XML) Data Model	Element
Namespace (prefix)	nar
Name	email
Title	Email Address
Definition	An email address.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	ElectronicAddressType (page 195)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.57 Excluded Audience

Table 63. Excluded Audience

(XML) Data Model	Element
Namespace (prefix)	nar
Name	exclAudience
Title	Excluded Audience
Definition	An excluded audience for the content.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	AudienceType (page 188)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.58 Exclusion Date

Table 64. Exclusion Date

(XML) Data Model	Element
Namespace (prefix)	nar
Name	exDate
Title	Exclusion Date
Definition	An explicit date (and optionally time with the time zone) to be excluded from the recurrence set.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	DateOptTimePropType (page 192)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.59 Exclusion Rule

Table 65. Exclusion Rule

(XML) Data Model	Element
Namespace (prefix)	nar
Name	exRule
Title	Exclusion Rule
Definition	A rule of recurrence exclusion.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	RecurrenceRuleType (page 216)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.60 Facet

Table 66. Facet

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	facet		
Title	Facet		
Definition	An intrinsic property of the concept.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	FlexPropType (page 204)		
Internally Ctrl Values			
Externally Ctrl Values	The default value and additional values for the rel attribute are defined by the IPTC Facet Relationship NewsCodes - http://cv.iptc.org/newscodes/facetrelation/		
Attribute(s)	<ul style="list-style-type: none"> rel (0..1); QCodeType (page 214); The identifier of the relationship between the current concept (containing the facet) and the concept identified by the facet value. The default value for <i>rel</i> is the "IsA" relationship, this applies also if the <i>rel</i> attribute is omitted. 		
	<ul style="list-style-type: none"> timeValidityAttributes (page 224) 	Name	Datatype
		validfrom (0..1)	DateOptTimeType
	validto (0..1)	DateOptTimeType	
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.61 Fax Number

Table 67. Fax Number

(XML) Data Model	Element
Namespace (prefix)	nar
Name	fax
Title	Fax Number
Definition	An international fax number.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	ElectronicAddressType (page 195)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.62 File Name

Table 68. File Name

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	filename		
Title	File Name		
Definition	The recommended file name for this Item.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	XML Schema normalizedString		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
		modified (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.63 Generator Tool

Table 69. Generator Tool

(XML) Data Model	Element
Namespace (prefix)	nar
Name	generator
Title	Generator Tool
Definition	The name and version of the software tool used to generate the Item.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	VersionedStringType (page 222)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.64 Genre

Table 70. Genre

(XML) Data Model	Element
Namespace (prefix)	nar
Name	genre
Title	Genre
Definition	A nature, intellectual or journalistic form of the news content.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Flex1ConceptPropType (page 197)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.65 Geographic Position

Table 71. Geographic Position

(XML) Data Model	Element
Namespace (prefix)	nar
Name	position
Title	Geographic Position
Definition	The geographic coordinates of the location.
User Note(s)	<p>These properties follow the syntax used by the major geocoders on the Web. Latitudes north of the equator shall be designated by use of the plus sign (+), latitudes south of the equator shall be designated by use of the minus sign (-). The equator shall be designated by use of the plus sign (+). Longitudes east of Greenwich shall be designated by use of the plus sign (+), longitudes west of Greenwich shall be designated by use of the minus sign (-). The Prime Meridian shall be designated by use of the plus sign (+). The 180th meridian shall be designated by use of the minus sign (-). The altitude is given in meters. A positive integer means a position above the zero elevation, a negative value below the zero elevation. In the absence of the <i>gpsdatum</i> attribute, WGS84 is the default system.</p>
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ latitude (1); XML Schema decimal; The latitude in decimal degrees (Positive value = northern latitude, negative value = southern latitude). ▪ longitude (1); XML Schema decimal; The longitude in decimal degrees (Positive value = eastern longitude, negative value = western longitude). ▪ altitude (0..1); XML Schema integer; The altitude in meters above the zero elevation of the reference system (sea level). ▪ gpsdatum (0..1); XML Schema string; The GPS datum associated with the measure.
Child Element(s)	<ul style="list-style-type: none"> ▪ Extension Point (0..unbounded). Any set of provider-defined properties.
XML Schema Note(s)	
Example(s)	



10.6.66 Geopolitical Area Details

Table 72. Geopolitical Area Details

(XML) Data Model	Element
Namespace (prefix)	nar
Name	geoAreaDetails
Title	Geopolitical Area Details
Definition	A set of properties specific for a geopolitical area.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	<ul style="list-style-type: none"> ▪ position (page 104) (0..1) ▪ Extension Point (0..unbounded). Any set of provider-defined properties.
XML Schema Note(s)	
Example(s)	



10.6.67 Group

Table 73. Group

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	group		
Title	Group		
Definition	A mixed set of group references and links.		
User Note(s)	<ul style="list-style-type: none"> ▪ Group Mode: By default the group is “complementary and unordered”. <ul style="list-style-type: none"> ▪ Complementary and Unordered: To be used for any kind of supporting content that does not require a sequence to be specified. ▪ Complementary and Ordered: The group starts with the first child of the group. To be used for any kind of content which must be displayed or consumed in a particular sequence, expressed by the order of the child elements of the group. The semantics of the role attribute value determine the required processing. ▪ Alternatives: To be used if a group contains equivalent pieces of content (e.g. translations of the same news story into different languages). The recipient may pick one or more of these. ▪ Group References and Item References: Can be included in any order, and this order may be relevant or not, depending the value of the mode attribute. Each link aggregates an external resource (Item or Web resource) to the package. Optionally, it indicates the relationship between the group and the target resource plus some additional hints about the resource itself. 		
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ role (1); QCodeType (page 214); The part this group plays within its container. ▪ mode (0..unbounded); QCodeType (page 214); An indication whether the elements in the group are complementary and unordered, complementary and ordered or a set of alternative elements. ▪ id (1); XML Schema id; The local identifier of the group. ▪ creator (0..1); QCodeType; party who has edited the property (or will edit the property) ▪ modified (0..1); DateOptTimeType; The date (and optionally the time) when the property was last modified. 		
	<ul style="list-style-type: none"> ▪ i18nAttributes (page 223) 	Name	Datatype
		xml:lang (0..1)	XML Schema language
		dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .
	Child Element(s)	<ul style="list-style-type: none"> ▪ groupRef (page 107) (0..unbounded) ▪ itemRef (page 122) (0..unbounded) 	
	XML Schema Note(s)	The local identifier (id) common to all elements at PCL provides a local identifier for groups.	
Example(s)			



10.6.68 Group Reference

Table 74. Group Reference

(XML) Data Model	Element
Namespace (prefix)	nar
Name	groupRef
Title	Group Reference
Definition	A reference to a group local to the package.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	▪ idref (1); XML Schema idref; The reference to the id of a local group.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.69 Group Set

Table 75. Group Set

(XML) Data Model	Element
Namespace (prefix)	nar
Name	groupSet
Title	Group Set
Definition	A hierarchical set of groups.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ root (1); XML Schema idref; The reference to a local group acting as the root of the hierarchy of groups.
Child Element(s)	<ul style="list-style-type: none"> ▪ group (page 106) (1..unbounded)
XML Schema Note(s)	
Example(s)	



10.6.70 Headline

Table 76. Headline

(XML) Data Model	Element
Namespace (prefix)	nar
Name	headline
Title	Headline
Definition	A brief and snappy introduction to the news content, designed to catch the reader's attention.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Label1Type (page 209)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.71 Icon

Table 77. Icon

(XML) Data Model	Element			
Namespace (prefix)	nar			
Name	icon			
Title	Icon			
Definition	An iconic visual representation of the content.			
User Note(s)				
Implementation Note(s)				
XML Schema Spec	At: PCL			
Datatype				
Internally Ctrl Values				
Externally Ctrl Values				
Attribute(s)	▪ targetResourceAttributes (page 225)	Name	Datatype	
		href (0..1)	IRIType	
		residref (0..1)	XML Schema string	
		version (0..1)	XML Schema positiveInteger	
		contenttype (0..1)	XML Schema string	
		format (0..1)	QCodeType	
		size (0..1)	XML Schema non NegativeInteger	
	▪ editAttributes (page 223)	Name	Datatype	
		id (0..1)	XML Schema ID	
		creator (0..1)	QCodeType	
		modified (0..1)	DateOptTimeType	
	Child Element(s)			
	XML Schema Note(s)			
Example(s)				



10.6.72 Inline Concept Marker

Table 78. Inline Concept Marker

(XML) Data Model	Element									
Namespace (prefix)	nar									
Name	inline									
Title	Inline Concept Marker									
Definition	An inline markup tag to be used with any concept.									
User Note(s)										
Implementation Note(s)										
XML Schema Spec	At: PCL									
Datatype	Mixed Content									
Internally Ctrl Values										
Externally Ctrl Values										
Attribute(s)	<ul style="list-style-type: none"> ▪ class (0..1); XML Schema String; An equivalent of the HTML <i>class</i> attribute. ▪ qcode (0..1); QCodeType (page 214); A qualified code assigned as property value. or ▪ literal (0..1); XML Schema normalizedString; A free-text value assigned as property value. ▪ type (0..1); QCodeType (page 214); The type of the concept assigned as controlled or uncontrolled property value. 									
	▪ i18nAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>xml:lang (0..1)</td> <td>XML Schema language</td> </tr> <tr> <td>dir (0..1)</td> <td>XML Schema string: enumeration <i>ltr</i>, <i>rtl</i>.</td> </tr> </tbody> </table>	Name	Datatype	xml:lang (0..1)	XML Schema language	dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .		
		Name	Datatype							
	xml:lang (0..1)	XML Schema language								
	dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .								
	▪ editAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>id (0..1)</td> <td>XML Schema ID</td> </tr> <tr> <td>creator (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>modified (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>	Name	Datatype	id (0..1)	XML Schema ID	creator (0..1)	QCodeType	modified (0..1)	DateOptTimeType
		Name	Datatype							
		id (0..1)	XML Schema ID							
	creator (0..1)	QCodeType								
	modified (0..1)	DateOptTimeType								
▪ quantifyAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>confidence (0..1)</td> <td>Int100Type</td> </tr> <tr> <td>relevance (0..1)</td> <td>Int100Type</td> </tr> <tr> <td>why (0..1)</td> <td>QCodeType</td> </tr> </tbody> </table>	Name	Datatype	confidence (0..1)	Int100Type	relevance (0..1)	Int100Type	why (0..1)	QCodeType	
	Name	Datatype								
	confidence (0..1)	Int100Type								
relevance (0..1)	Int100Type									
why (0..1)	QCodeType									
Child Element(s)	<ul style="list-style-type: none"> ▪ span (page 173) (0..unbounded) ▪ ruby (page 164) (0..unbounded) ▪ Extension Point (0..unbounded). Any set of provider-defined properties. 									
XML Schema Note(s)										
Example(s)										



10.6.73 Inline Data (NewsML-G2 Specific)

Table 79. *Inline Data (NewsML-G2 Specific)*

(XML) Data Model	Element
Namespace (prefix)	nar
Name	inlineData
Title	Inline Data (NewsML-G2 Specific)
Definition	The encoding applied to the content before inclusion.
User Note(s)	
Implementation Note(s)	For the encoding attribute at the CCL only the QCode for “base64” may be used. If the attribute does not exist, this QCode must be assumed as default.. In the absence of the encoding attribute, the content must be plain text, and the content type must be set accordingly.
XML Schema Spec	At PCL
Datatype	XML schema string
Internally Ctrl Values	
Externally Ctrl Values	



Table 79. Inline Data (NewsML-G2 Specific) (Continued)

Attribute(s)	<ul style="list-style-type: none"> encoding (0..1); QCodeType (page 214); Specifies the encoding applied to the content before inclusion in the content. 		
	<ul style="list-style-type: none"> contenttype (0..1); XML Schema string; The IANA (Internet Assigned Numbers Authority) MIME type of the target resource. 		
	<ul style="list-style-type: none"> format (0..1); QCodeType; Refinement of a generic content type (i.e. IANA MIME type). 		
	<ul style="list-style-type: none"> newsContentAttributes (page 224) 	Name	Datatype
		id (0..1)	XML Schema ID
		rendition (0..1)	QCodeType
		generator (0..1)	XML Schema string
	<ul style="list-style-type: none"> newsContentCharacteristics (page 225) 	Name	Datatype
		Word Count	XML Schema nonNegativeInteger
		Image Width	XML Schema nonNegativeInteger
		Image Height	XML Schema nonNegativeInteger
		Image Orientation	XML Schema nonNegativeInteger
		Image Colour Space	QCodeType
		Resolution	XML Schema positiveInteger
		Duration	XML Schema nonNegativeInteger
		Audio Codec	QCodeType
		Audio Bit Rate	XML Schema positiveInteger
		Audio Variable Bit Rate flag	XML Schema boolean
		Audio Sample Size	XML Schema positiveInteger
		Audio Sample Rate	XML Schema positiveInteger
		Audio Channels	QCodeType
		Video Codec	QCodeType
		Video Average Bit Rate	XML Schema positiveInteger
		Video Variable Bit Rate flag	XML Schema boolean
		Video Frame Rate	XML Schema positiveInteger
		Video Scan Technique	enumeration progressive/interlaced
		Video Aspect Ratio	XML Schema normalizedString
Video Sampling Method	XML Schema normalizedString		
<ul style="list-style-type: none"> i18nAttributes (page 223) 	Name	Datatype	
	xml:lang (0..1)	XML Schema language	
	dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .	
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.74 Inline Reference

Table 80. Inline Reference

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	inlineRef		
Title	Inline Reference		
Definition	A concept represented by the content identified by the local identifier(s).		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	Flex1PropType (page 199)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ idrefs (0..1); XML Schema IDREFS; A set of local identifiers of inline content. 		
	▪ quantifyAttributes (page 223)	Name	Datatype
		confidence (0..1)	Int100Type
		relevance (0..1)	Int100Type
	why (0..1)	QCodeType	
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.75 Inline XML (NewsML-G2 Specific)

Table 81. Inline XML (NewsML-G2 Specific)

(XML) Data Model	Element
Namespace (prefix)	nar
Name	inlineXML
Title	Inline XML (NewsML-G2 Specific)
Definition	A rendition of the content using an XML language.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	

Table 81. Inline XML (NewsML-G2 Specific) (Continued)

	<ul style="list-style-type: none"> contenttype (0..1); XML Schema string; The IANA (Internet Assigned Numbers Authority) MIME type of the target resource. 																																											
	<ul style="list-style-type: none"> format (0..1); QCodeType; Refinement of a generic content type (i.e. IANA MIME type). 																																											
Attribute(s)	<table border="1"> <tr> <td rowspan="5"> <ul style="list-style-type: none"> newsContentAttributes (page 224) </td> <th>Name</th> <th>Datatype</th> </tr> <tr> <td>id (0..1)</td> <td>XML Schema ID</td> </tr> <tr> <td>rendition (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>generator (0..1)</td> <td>XML Schema string</td> </tr> <tr> <td>generated (0..1)</td> <td>DateOptTimeType</td> </tr> </table>	<ul style="list-style-type: none"> newsContentAttributes (page 224) 	Name	Datatype	id (0..1)	XML Schema ID	rendition (0..1)	QCodeType	generator (0..1)	XML Schema string	generated (0..1)	DateOptTimeType																																
	<ul style="list-style-type: none"> newsContentAttributes (page 224) 		Name	Datatype																																								
			id (0..1)	XML Schema ID																																								
			rendition (0..1)	QCodeType																																								
			generator (0..1)	XML Schema string																																								
		generated (0..1)	DateOptTimeType																																									
	<table border="1"> <tr> <td rowspan="19"> <ul style="list-style-type: none"> newsContentCharacteristics (page 225) </td> <th>Name</th> <th>Datatype</th> </tr> <tr> <td>Word Count</td> <td>XML Schema nonNegativeInteger</td> </tr> <tr> <td>Image Width</td> <td>XML Schema nonNegativeInteger</td> </tr> <tr> <td>Image Height</td> <td>XML Schema nonNegativeInteger</td> </tr> <tr> <td>Image Orientation</td> <td>XML Schema nonNegativeInteger</td> </tr> <tr> <td>Image Colour Space</td> <td>QCodeType</td> </tr> <tr> <td>Resolution</td> <td>XML Schema positiveInteger</td> </tr> <tr> <td>Duration</td> <td>XML Schema nonNegativeInteger</td> </tr> <tr> <td>Audio Codec</td> <td>QCodeType</td> </tr> <tr> <td>Audio Bit Rate</td> <td>XML Schema positiveInteger</td> </tr> <tr> <td>Audio Variable Bit Rate flag</td> <td>XML Schema boolean</td> </tr> <tr> <td>Audio Sample Size</td> <td>XML Schema positiveInteger</td> </tr> <tr> <td>Audio Sample Rate</td> <td>XML Schema positiveInteger</td> </tr> <tr> <td>Audio Channels</td> <td>QCodeType</td> </tr> <tr> <td>Video Codec</td> <td>QCodeType</td> </tr> <tr> <td>Video Average Bit Rate</td> <td>XML Schema positiveInteger</td> </tr> <tr> <td>Video Variable Bit Rate flag</td> <td>XML Schema boolean</td> </tr> <tr> <td>Video Frame Rate</td> <td>XML Schema positiveInteger</td> </tr> <tr> <td>Video Scan Technique</td> <td>enumeration progressive/interlaced</td> </tr> <tr> <td>Video Aspect Ratio</td> <td>XML Schema normalizedString</td> </tr> <tr> <td>Video Sampling Method</td> <td>XML Schema normalizedString</td> </tr> </table>	<ul style="list-style-type: none"> newsContentCharacteristics (page 225) 	Name	Datatype	Word Count	XML Schema nonNegativeInteger	Image Width	XML Schema nonNegativeInteger	Image Height	XML Schema nonNegativeInteger	Image Orientation	XML Schema nonNegativeInteger	Image Colour Space	QCodeType	Resolution	XML Schema positiveInteger	Duration	XML Schema nonNegativeInteger	Audio Codec	QCodeType	Audio Bit Rate	XML Schema positiveInteger	Audio Variable Bit Rate flag	XML Schema boolean	Audio Sample Size	XML Schema positiveInteger	Audio Sample Rate	XML Schema positiveInteger	Audio Channels	QCodeType	Video Codec	QCodeType	Video Average Bit Rate	XML Schema positiveInteger	Video Variable Bit Rate flag	XML Schema boolean	Video Frame Rate	XML Schema positiveInteger	Video Scan Technique	enumeration progressive/interlaced	Video Aspect Ratio	XML Schema normalizedString	Video Sampling Method	XML Schema normalizedString
	<ul style="list-style-type: none"> newsContentCharacteristics (page 225) 		Name	Datatype																																								
			Word Count	XML Schema nonNegativeInteger																																								
			Image Width	XML Schema nonNegativeInteger																																								
			Image Height	XML Schema nonNegativeInteger																																								
			Image Orientation	XML Schema nonNegativeInteger																																								
			Image Colour Space	QCodeType																																								
			Resolution	XML Schema positiveInteger																																								
			Duration	XML Schema nonNegativeInteger																																								
			Audio Codec	QCodeType																																								
			Audio Bit Rate	XML Schema positiveInteger																																								
			Audio Variable Bit Rate flag	XML Schema boolean																																								
			Audio Sample Size	XML Schema positiveInteger																																								
			Audio Sample Rate	XML Schema positiveInteger																																								
Audio Channels			QCodeType																																									
Video Codec			QCodeType																																									
Video Average Bit Rate			XML Schema positiveInteger																																									
Video Variable Bit Rate flag			XML Schema boolean																																									
Video Frame Rate			XML Schema positiveInteger																																									
Video Scan Technique		enumeration progressive/interlaced																																										
Video Aspect Ratio	XML Schema normalizedString																																											
Video Sampling Method	XML Schema normalizedString																																											
<table border="1"> <tr> <td rowspan="3"> <ul style="list-style-type: none"> i18nAttributes (page 223) </td> <th>Name</th> <th>Datatype</th> </tr> <tr> <td>xml:lang (0..1)</td> <td>XML Schema language</td> </tr> <tr> <td>dir (0..1)</td> <td>XML Schema string: enumeration ltr, rtl.</td> </tr> </table>	<ul style="list-style-type: none"> i18nAttributes (page 223) 	Name	Datatype	xml:lang (0..1)	XML Schema language	dir (0..1)	XML Schema string: enumeration ltr, rtl.																																					
<ul style="list-style-type: none"> i18nAttributes (page 223) 		Name	Datatype																																									
		xml:lang (0..1)	XML Schema language																																									
	dir (0..1)	XML Schema string: enumeration ltr, rtl.																																										
Child Element(s)	<ul style="list-style-type: none"> Plug-in Point (0..1). XML content from any namespace. 																																											
XML Schema Note(s)																																												
Example(s)																																												



10.6.76 Instance Of

Table 82. Instance Of

(XML) Data Model	Element
Namespace (prefix)	nar
Name	instanceOf
Title	Instance Of
Definition	A frequently updated information object of which this Item is an instance.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Flex1PropType (page 199)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.77 Instant Messaging Address

Table 83. Instant Messaging Address

(XML) Data Model	Element
Namespace (prefix)	nar
Name	im
Title	Instant Messaging Address
Definition	An address of an instant messaging system.
User Note(s)	The tech attribute indicates the provider of the service (Yahoo!, Google etc.).
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	ElectronicAddressTechType (page 196)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.78 Information Source

Table 84. Information Source

(XML) Data Model	Element
Namespace (prefix)	nar
Name	infoSource
Title	Information Source
Definition	A party (person or organisation) which originated some information used to create or enhance the content.
User Note(s)	If an entity plays more than one role, the <i>infoSource</i> element has to be included multiple times, with different values of role.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Flex1PartyPropType (page 198)
Internally Ctrl Values	
Externally Ctrl Values	Recommended IPTC NewsCodes for the <i>role</i> attribute: http://cv.iptc.org/newscodes/infosourcerole/
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.79 Item Class

Table 85. Item Class

(XML) Data Model	Element
Namespace (prefix)	nar
Name	itemClass
Title	Item Class
Definition	Indicates the nature of the Item.
User Note(s)	This property gives a hint on the nature of the Item. IPTC values for News Items correspond to the media type of the original content component, i.e. "text", "photo", etc. Concept Items adopt the static value <i>concept</i> . The class of a Package Item reflects the nature of the items it contains, i.e. either one of the values above or the value "composite" which indicates that the package handles items of different natures. A recipient system may use this information to make a coarse selection of Items, based on their nature, without having to inspect the structure.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	QualPropType (page 215)
Internally Ctrl Values	
Externally Ctrl Values	Mandatory IPTC NewsCodes for News Items or Package Items: http://cv.iptc.org/newscodes/ninature/ Mandatory IPTC NewsCodes for Concept Items, Knowledge Items or Package Items: http://cv.iptc.org/newscodes/cinature/
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.80 Item Metadata

Table 86. Item Metadata

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	itemMeta		
Title	Item Metadata		
Definition	A set of properties directly associated with the Item.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)			
Child Element(s)	<ul style="list-style-type: none"> ▪ Item Management Group (page 185) (1) 	Element Name	Page
		provider (1)	70
		embargoed (0..1)	81
		firstCreated (0..1)	82
		versionCreated (1)	83
		edNote (0..unbounded)	93
		service (0..unbounded)	94
		filename (0..1)	101
		itemClass (1)	120
		pubStatus (0..1)	154
		role (0..1)	163
		title (0..unbounded)	124
		altRep (0..unbounded)	46
		generator (0..1)	102
		instanceOf (0..unbounded)	117
		memberOf (0..unbounded)	133
		profile (0..1)	152
signal (0..unbounded)	171		
	<ul style="list-style-type: none"> ▪ link (page 128) (0..unbounded) ▪ Extension Point (0..unbounded). Any set of provider-defined properties. 		
XML Schema Note(s)			
Example(s)			



10.6.81 Item Reference

Table 87. Item Reference

(XML) Data Model	Element
Namespace (prefix)	nar
Name	itemRef
Title	Item Reference
Definition	A reference to a target Item or Web resource.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Link1Type (page 210)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.82 Item Set

Table 88. Item Set

(XML) Data Model	Element
Namespace (prefix)	nar
Name	itemSet
Title	Item Set
Definition	A set of Items.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	<ul style="list-style-type: none"> ▪ newsItem (page 136) (1..unbounded) ▪ conceptItem (page 62) (1..unbounded) ▪ packageItem (page 143) (1..unbounded) ▪ knowledgeItem (page 125) (0..unbounded)
XML Schema Note(s)	To allow the validation of the structure beyond the root elements of the different items the extension point "any" for the nar XML namespace is the only child element. This allows schema based validation of the content of the items as the validation of the extension point is set to "lax".
Example(s)	



10.6.83 Item Title

Table 89. Item Title

(XML) Data Model	Element
Namespace (prefix)	nar
Name	title
Title	Item Title
Definition	A short, natural-language name for the Item.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Label1Type (page 209)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.84 Knowledge Item

Table 90. Knowledge Item

(XML) Data Model	Element
Namespace (prefix)	nar
Name	knowledgItem
Title	Knowledge Item
Definition	An Item used for collating a set of concept definitions to form the physical representation of a controlled vocabulary.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	▪ contentMeta (page 67) (0..1)
	▪ assert (page 48) (0..unbounded)
	▪ inlineRef (page 114) (0..unbounded)
	▪ conceptSet (page 64) (0..1)
XML Schema Note(s)	
Example(s)	



10.6.85 Language

Table 91. Language

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	language		
Title	Language		
Definition	A language associated with the content. For news this is a language used by the news content, for events this is a language used at this event, for Knowledge Items this is the major language used to describe the concepts		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values	<p><i>tag</i> values must be valid BCP 47 language tags. Recommended IPTC NewsCodes for the <i>role</i> attribute: http://cv.iptc.org/newscodes/languagerole/</p>		
Attribute(s)	<ul style="list-style-type: none"> ▪ <i>tag</i> (1); XML Schema language; Indicator of the language. ▪ <i>role</i> (0..1); QCodeListType (page 212); A refinement of the semantics of the property. 		
	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
	modified (0..1)	DateOptTimeType	
Child Element(s)	▪ name (page 153) (0..unbounded)		
XML Schema Note(s)			
Example(s)			



10.6.86 Line Break

Table 92. Line Break

(XML) Data Model	Element
Namespace (prefix)	nar
Name	br
Title	Line Break
Definition	A line break.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	Empty element
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.87 Link

Table 93. Link

(XML) Data Model	Element
Namespace (prefix)	nar
Name	link
Title	Link
Definition	A link from the current Item to a target Item or Web resource.
User Note(s)	<p>They are different variants of links: Links may allow for navigation from a newsItem to another related Item or a Web resource, and its title be displayed as supplemental information to the final user. Example: a newsItem representing a section of a transcript (a “take” in the news language) may be linked to the previous and next take; an article about a person may be linked to the biography of this person.</p> <p>Links may express a parent-child relationship. Example: a newsItem representing an article may be linked to the article it is a translation of; a wrap-up may be linked to the previous stories used as source material for the article; a cropped picture may be linked to its source picture.</p> <p>Links may express dependency on external Items which are required in order to fully present the composite content of the Item. If some target Items are not retrievable, then the recipient processor should fail gracefully. The most obvious example is a newsItem representing an illustrated article. The textual content of the newsItem (usually formatted as NITF or XHTML) includes a reference to a photo which is represented by another newsItem. As the NAR recipient processor is content agnostic, it cannot infer this dependency from processing the content. A dependency link from the article to the picture indicates that the recipient processor must retrieve the target newsItem before the article can be fully displayed.</p> <p>Pointing at the latest version of an Item while exposing content metadata may lead to unwanted display or selection criteria if these metadata were subsequently modified; therefore only the stable content properties should be exposed in a link.</p>
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Link1Type (page 210)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.88 Locality

Table 94. Locality

(XML) Data Model	Element
Namespace (prefix)	nar
Name	locality
Title	Locality
Definition	A city/town/village etc. part of the address.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Flex1PropType (page 199)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.89 Located

Table 95. Located

(XML) Data Model	Element
Namespace (prefix)	nar
Name	located
Title	Located
Definition	A location from which the content originates.
User Note(s)	<p>This information applies especially to news, and may also be expressed as free text in the “dateline” of a story, along with a date of content creation and the name of the content provider. The rules for determining the location are provider-dependent. The location is typically determined differently for different types of content:</p> <ul style="list-style-type: none"> - Text: The practices of news providers either identify the location the content relates to or the location the content was created by a reporter or a writer. If a correspondent is resident in town A but writes about an event in town B the name of town A or B can be used. But the provider's policy should be available as written document. - Photo: The location of origin of content is the place shown in the photo image. - Graphics: The location of origin of content should be the editorial office from where this graphics are distributed. - Audio and video: In the case of raw footage the location of origin of the content should be the place of event, if people can be heard/are shown from different places the news provider can decide by its own policy, but this policy should be available as written document.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	FlexLocationPropType (page 200)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.90 Location

Table 96. Location

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	location		
Title	Location		
Definition	A location (geographical area or point of interest).		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	FlexLocationPropType (page 200)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ timeValidityAttributes (page 224) 	Name	DataType
		validfrom (0..1)	DateOptTimeType
		validto (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.91 Location Details

Table 97. Location Details

(XML) Data Model	Element
Namespace (prefix)	nar
Name	details
Title	Location Details
Definition	Detailed information about the precise location of the point of interest.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	BlockType (page 189)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.92 Member Of

Table 98. Member Of

(XML) Data Model	Element
Namespace (prefix)	nar
Name	memberOf
Title	Member Of
Definition	A set of Items around the same theme of which this Item is a part.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Flex1PropType (page 199)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.93 Message Header

Table 99. Message Header

(XML) Data Model	Element
Namespace (prefix)	nar
Name	header
Title	Message Header
Definition	A set of properties facilitating the exchange of Items.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	<ul style="list-style-type: none"> ▪ sent (page 88) (1); May not be updated in case message retransmission. ▪ sender (page 170) (0..1); The structure of this string is not specified by the IPTC. Best practice is to identify a sender by its domain name. ▪ transmitId (page 177) (0..1); No two News Messages sent by the same sender on the same date can have the same identifier. In case of retransmission it is not required to update this identifier. This string structure is not specified by the IPTC. ▪ priority (page 151) (0..1) ▪ origin (page 141) (0..1); This string structure is not specified by the IPTC. ▪ destination (page 92) (0..unbounded) ▪ channel (page 58) (0..unbounded); A channel identifier is used to provide recipients with information on which select, route, or otherwise handle the content of the message. The channels represent streams in a multiplex: a message may be sent on different channels – e.g. one for text, one for pictures – and each reception point will be able to filter on channel values. This string structure is not specified by the IPTC. ▪ timestamp (page 176) (0..unbounded) ▪ Extension Point (0..unbounded). Any set of provider-defined properties.
XML Schema Note(s)	
Example(s)	



10.6.94 Narrower

Table 100. Narrower

(XML) Data Model	Element
Namespace (prefix)	nar
Name	narrower
Title	Narrower
Definition	An identifier of a more specific concept.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	RelatedConceptType (page 217)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.95 News Item (NewsML-G2 Specific)

Table 101. News Item (NewsML-G2 Specific)

(XML) Data Model	Element
Namespace (prefix)	nar
Name	newsItem
Title	News Item (NewsML-G2 Specific)
Definition	An Item containing news-related information.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	AnyItemType (page 186)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	▪ contentMeta (page 68) (0..1)
	▪ partMeta (page 144) (0..1)
	▪ assert (page 48) (0..unbounded)
	▪ inlineRef (page 114) (0..unbounded)
	▪ contentSet (page 71) (0..1)
XML Schema Note(s)	
Example(s)	



10.6.96 News Message

Table 102. News Message

(XML) Data Model	Element
Namespace (prefix)	nar
Name	newsMessage
Title	News Message
Definition	A container to exchange one or more items.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	<ul style="list-style-type: none"> ▪ header (page 134) (1) ▪ itemSet (page 123) (1)
XML Schema Note(s)	
Example(s)	



10.6.97 Note

Table 103. Note

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	note		
Title	Note		
Definition	Additional natural-language information about the concept.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	BlockType (page 189)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ timeValidityAttributes (page 224)	Name	Datatype
		validfrom (0..1)	DateOptTimeType
		validto (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.98 Object Details

Table 104. Object Details

(XML) Data Model	Element
Namespace (prefix)	nar
Name	objectDetails
Title	Object Details
Definition	A set of properties representing an object.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	<ul style="list-style-type: none"> ▪ created (page 90) (0..1) ▪ creator (page 77) (0..unbounded) ▪ copyrightNotice (page 74) (0..unbounded)
XML Schema Note(s)	
Example(s)	



10.6.99 Opening Hours

Table 105. Opening Hours

(XML) Data Model	Element
Namespace (prefix)	nar
Name	openHours
Title	Opening Hours
Definition	Opening-hours of the place, in natural language.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Label1Type (page 209)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.100 Origin

Table 106. Origin

(XML) Data Model	Element
Namespace (prefix)	nar
Name	origin
Title	Origin
Definition	The point of origin of the transmission of the message.
User Note(s)	This string's structure is not specified by the IPTC.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	XML Schema string
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.101 Organisation Details

Table 107. Organisation Details

(XML) Data Model	Element
Namespace (prefix)	nar
Name	organisationDetails
Title	Organisation Details
Definition	A group of properties specific to an organisation.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	▪ founded (page 87) (0..1)
	▪ dissolved (page 86) (0..1)
	▪ location (page 131) (0..unbounded)
	▪ contactInfo (page 65) (0..unbounded)
	▪ Extension Point (0..unbounded). Any set of provider-defined properties.
XML Schema Note(s)	
Example(s)	



10.6.102 Package Item

Table 108. Package Item

(XML) Data Model	Element
Namespace (prefix)	nar
Name	packageItem
Title	Package Item
Definition	An Item used for packaging references to other Items and Web resources.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	AnylItemType (page 186)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	▪ contentMeta (page 69) (0..1)
	▪ assert (page 48) (0..unbounded)
	▪ inlineRef (page 114) (0..unbounded)
	▪ groupSet (page 108) (0..1)
XML Schema Note(s)	
Example(s)	



10.6.103 Part Meta

Table 109. Part Meta

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	partMeta		
Title	Part Meta		
Definition	A set of properties associated with a specific part of the content of the Item.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ partid (0..1); XML Schema ID; The identifier of the part.		
	▪ seq (0..1); XML Schema nonNegativeInteger; The sequence number of the part.		
	▪ i18nAttributes (page 223)	Name	Datatype
		xml:lang (0..1)	XML Schema language
	dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .	



Table 109. Part Meta (Continued)

Child Element(s)	▪ icon (page 110) (0..1)		
	▪ timeDelim (page 175) (0..1)		
	▪ regionDelim (page 181) (0..1)		
	▪ Administrative Metadata Group (page 184)	Element Name	Page
		urgency (0..1)	179
		contentCreated (0..1)	79
		contentModified (0..1)	80
		located (0..unbounded)	130
		infoSource (0..unbounded)	119
		creator (0..unbounded)	77
		contributor (0..unbounded)	72
		audience (0..unbounded)	49
		exclAudience (0..unbounded)	96
	▪ Descriptive Metadata Group (page 184) (0..1)	Element Name	Page
		by (0..unbounded)	53
		creditline (0..unbounded)	78
		dateline (0..unbounded)	89
		description (0..unbounded)	91
		genre (0..unbounded)	103
headline (0..unbounded)		109	
language (0..unbounded)		126	
slugline (0..unbounded)		172	
subject (0..unbounded)	174		
▪ Extension Point (0..unbounded). Any set of provider-defined properties.			
XML Schema Note(s)			
Example(s)			



10.6.104 Person Details

Table 110. Person Details

(XML) Data Model	Element
Namespace (prefix)	nar
Name	personDetails
Title	Person Details
Definition	A group of properties specific to a person.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	▪ born (page 84) (0..1)
	▪ died (page 85) (0..1)
	▪ affiliation (page 43) (0..unbounded)
	▪ contactInfo (page 65) (0..unbounded)
	▪ Extension Point (0..unbounded). Any set of provider-defined properties.
XML Schema Note(s)	
Example(s)	



10.6.105 Phone Number

Table 111. Phone Number

(XML) Data Model	Element
Namespace (prefix)	nar
Name	phone
Title	Phone Number
Definition	An international phone number.
User Note(s)	The <i>tech</i> attribute indicates a land-line, cellular etc., service.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	ElectronicAddressTechType (page 196)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.106 POI Details

Table 112. POI Details

(XML) Data Model	Element
Namespace (prefix)	nar
Name	POIDetails
Title	POI Details
Definition	A group of properties specific to a point of interest.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	<ul style="list-style-type: none"> ▪ position (page 104) (0..1) ▪ openHours (page 140) (0..1) ▪ capacity (page 54) (0..1) ▪ access (page 40) (0..unbounded) ▪ details (page 132) (0..unbounded) ▪ contactInfo (page 65) (0..unbounded) ▪ Extension Point (0..unbounded). Any set of provider-defined properties.
XML Schema Note(s)	
Example(s)	



10.6.107 Postal Address

Table 113. Postal Address

(XML) Data Model	Element
Namespace (prefix)	nar
Name	address
Title	Postal Address
Definition	A postal address.
User Note(s)	A special value of the role attribute may indicate that this information is not used to make contacts but e.g. is the registered address of a company.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ role (0..1); QCodeListType (page 212); A refinement of the semantics of the postal address.
Child Element(s)	▪ line (page 42) (0..unbounded)
	▪ locality (page 129) (0..1)
	▪ area (page 76) (0..1)
	▪ country (page 75) (0..1)
	▪ postalCode (page 150) (0..1)
XML Schema Note(s)	
Example(s)	



10.6.108 Postal Code

Table 114. Postal Code

(XML) Data Model	Element
Namespace (prefix)	nar
Name	postalCode
Title	Postal Code
Definition	A postal code, part of the address.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	IntlStringType (page 207)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.109 Priority

Table 115. Priority

(XML) Data Model	Element
Namespace (prefix)	nar
Name	priority
Title	Priority
Definition	The priority of this message in the overall transmission process. A value of 1 corresponds to the highest priority, a value of 9 to the lowest.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	Int1To9Type (page 206)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.110 Profile

Table 116. Profile

(XML) Data Model	Element
Namespace (prefix)	nar
Name	profile
Title	Profile
Definition	The name of the structural template (aka profile) used for the generation of the Item.
User Note(s)	This property gives information about the precise structure of an Item, e.g. a simple package, article with one picture, and may be the name of the transformation stylesheet used for the generation of the Item.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	VersionedStringType (page 222)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.111 Property Value Name

Table 117. Property Value Name

(XML) Data Model	Element
Namespace (prefix)	nar
Name	name
Title	Property Value Name
Definition	A natural-language name of the concept assigned as property value.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	IntlStringType (page 207)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.112 Publish Status

Table 118. Publish Status

(XML) Data Model	Element
Namespace (prefix)	nar
Name	pubStatus
Title	Publish Status
Definition	The publishing status of the Item. If no value is provided the default value is “usable”.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	QualPropType (page 215)
Internally Ctrl Values	
Externally Ctrl Values	Mandatory IPTC NewsCodes: http://cv.iptc.org/newscodes/pubstatusg2/
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.113 Recurrence Date

Table 119. Recurrence Date

(XML) Data Model	Element
Namespace (prefix)	nar
Name	rDate
Title	Recurrence Date
Definition	An explicit date (and optionally time with the time zone) of recurrence.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	DateOptTimePropType (page 192)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.114 Recurrence Rule

Table 120. Recurrence Rule

(XML) Data Model	Element
Namespace (prefix)	nar
Name	rRule
Title	Recurrence Rule
Definition	A rule of recurrence.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	RecurrenceRuleType (page 216)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.115 Related Concept

Table 121. Related Concept

(XML) Data Model	Element
Namespace (prefix)	nar
Name	related
Title	Related Concept
Definition	An identifier of a related concept, where the relationship is different from elements <i>sameAs</i> , <i>broader</i> , or <i>narrower</i> .
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Extends RelatedConceptType (page 217)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	bag (page 50) (0..1)
XML Schema Note(s)	
Example(s)	



10.6.116 Remote Catalog Reference

Table 122. Remote Catalog Reference

(XML) Data Model	Element									
Namespace (prefix)	nar									
Name	catalogRef									
Title	Remote Catalog Reference									
Definition	A reference to a remote catalog.									
User Note(s)										
Implementation Note(s)										
XML Schema Spec	At: PCL									
Datatype										
Internally Ctrl Values										
Externally Ctrl Values										
Attribute(s)	<ul style="list-style-type: none"> ▪ href (1); IRIType (page 208); A hyperlink to a remote catalog. 									
	<ul style="list-style-type: none"> ▪ editAttributes (page 223) 	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>id (0..1)</td> <td>XML Schema ID</td> </tr> <tr> <td>creator (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>modified (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>	Name	Datatype	id (0..1)	XML Schema ID	creator (0..1)	QCodeType	modified (0..1)	DateOptTimeType
		Name	Datatype							
		id (0..1)	XML Schema ID							
creator (0..1)	QCodeType									
modified (0..1)	DateOptTimeType									
Child Element(s)	<ul style="list-style-type: none"> ▪ title (page 124) (0..unbounded) 									
XML Schema Note(s)										
Example(s)										



10.6.117 Remote Content (NewsML-G2 Specific)

Table 123. Remote Content (NewsML-G2 Specific)

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	remoteContent		
Title	Remote Content		
Definition	A rendition of the content using a reference/link to a resource representing the content data at a remote location.		
User Note(s)	To identify the remote resource either the residref attribute or the href attribute MUST be set, optionally both MAY be used in parallel. The residref attribute identifies a managed remote resource by its globally unique identifier (if the resource has such an identifier), while the href attribute identifies the location of the remote resource in e.g. a (remote) file system. If the remote resource is managed - like an item - and consequently the residref attribute is used, a version attribute MAY indicate the resource's version; in the absence of version information, the remote resource is the latest version available.		
Implementation Note(s)			
		Video Codec	QCodeType
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			



Table 123. Remote Content (NewsML-G2 Specific) (Continued)

Attribute(s)	▪ newsContentAttributes (page 224)	Name	Datatype
		id (0..1)	XML Schema ID
		rendition (0..1)	QCodeType
		generator (0..1)	XML Schema string
		generated (0..1)	DateOptTimeType
	▪ targetResourceAttributes (page 225)	Name	Datatype
		href (0..1)	IRIType
		residref (0..1)	XML Schema string
		version (0..1)	XML Schema positiveInteger
		contenttype (0..1)	XML Schema string
		format (0..1)	QCodeType
	▪ timeValidityAttributes (page 224)	Name	Data Type
		validfrom (0..1)	DateOptTimeType
		validto (0..1)	DateOptTimeType
	▪ newsContentCharacteristics (page 225)	Name	Datatype
		Word Count	XML Schema nonNegativeInteger
		Image Width	XML Schema nonNegativeInteger
		Image Height	XML Schema nonNegativeInteger
		Image Orientation	XML Schema nonNegativeInteger
		Image Colour Space	QCodeType
		Resolution	XML Schema positiveInteger
		Duration	XML Schema nonNegativeInteger
		Audio Codec	QCodeType
		Audio Bit Rate	XML Schema positiveInteger
		Audio Variable Bit Rate flag	XML Schema boolean
		Audio Sample Size	XML Schema positiveInteger
		Audio Sample Rate	XML Schema positiveInteger
		Audio Channels	QCodeType
		Video Codec	QCodeType
		Video Average Bit Rate	XML Schema positiveInteger
		Video Variable Bit Rate flag	XML Schema boolean
		Video Frame Rate	XML Schema positiveInteger
		Video Scan Technique	enumeration progressive/interlaced
		Video Aspect Ratio	XML Schema normalizedString
	Video Sampling Method	XML Schema normalizedString	
	▪ language (0..1); XML Schema language; The language used by the remote content.		



Table 123. Remote Content (NewsML-G2 Specific) (Continued)

Child Element(s)	<ul style="list-style-type: none"> ▪ altLoc (page 45) (0..unbounded) ▪ altId (page 44) (0..unbounded) ▪ channel (page 58) (0..unbounded) ▪ Extension Point (0..unbounded). Any set of provider-defined properties.
XML Schema Note(s)	
Example(s)	



10.6.118 Rights Information

Table 124. Rights Information

(XML) Data Model	Element											
Namespace (prefix)	nar											
Name	rightsInfo											
Title	Rights Information											
Definition	A set of properties representing the rights associated with the Item.											
User Note(s)												
Implementation Note(s)												
XML Schema Spec	At: PCL											
Datatype												
Internally Ctrl Values												
Externally Ctrl Values												
Attribute(s)	<p>idrefs; (0..1); XML Schema IDREFS; The reference to the part(s) of the content the rights are about.</p> <table border="1"> <thead> <tr> <th></th> <th>Name</th> <th>Data Type</th> </tr> </thead> <tbody> <tr> <td>▪ timeValidityAttributes (page 224)</td> <td>validfrom (0..1)</td> <td>DateOptTimeType</td> </tr> <tr> <td></td> <td>validto (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>				Name	Data Type	▪ timeValidityAttributes (page 224)	validfrom (0..1)	DateOptTimeType		validto (0..1)	DateOptTimeType
	Name	Data Type										
▪ timeValidityAttributes (page 224)	validfrom (0..1)	DateOptTimeType										
	validto (0..1)	DateOptTimeType										
Child Element(s)	<ul style="list-style-type: none"> ▪ accountable (page 41) (0..1) ▪ copyrightHolder (page 73) (0..1) ▪ copyrightNotice (page 74) (0..unbounded) ▪ usageTerms (page 180) (0..unbounded) ▪ Extension Point (0..unbounded). Any set of provider-defined properties. 											
XML Schema Note(s)												
Example(s)												



10.6.119 Role in the Workflow

Table 125. Role in the Workflow

(XML) Data Model	Element
Namespace (prefix)	nar
Name	role
Title	Role in the Workflow
Definition	The role of the Item in the editorial workflow.
User Note(s)	Among other possibilities this property may indicate the importance of the item in a fee by concepts like “flash”, “bulletin”, “alert”, “urgent”, “newsbreak”, and so on.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	QualPropType (page 215)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.120 Ruby

Table 126. Ruby

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	ruby		
Title	Ruby		
Definition	Ruby annotation for documents using an East Asian script.		
User Note(s)			
Implementation Note(s)	This implementation aligns with the Simple Ruby markup without and with parentheses of the W3C (see http://www.w3.org/TR/ruby/#simple-ruby1).		
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
	▪ i18nAttributes (page 223)	Name	Datatype
		xml:lang (0..1)	XML Schema language
		dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .
Child Element(s)	▪ rb (page 165) (1)		
	▪ rp (page 166) (see XML Schema note below)		
	▪ rt (page 167) (see XML Schema note below)		
XML Schema Note(s)	The alternative simple Ruby markup without and with parentheses is expressed by the use of either a single <i>rt</i> element or a single <i>rp-rt-rp</i> sequence of elements. Ruby parentheses (<rp>, empty elements) must be used as a pair: either both are present or none is present.		
Example(s)	<pre><ruby> <rb>IPTC</rb> <rp>(<rp/><rt>International Press Telecommunications Council</rt><rp>)<rp/> </ruby></pre>		



10.6.121 Ruby Base

Table 127. Ruby Base

(XML) Data Model	Element
Namespace (prefix)	nar
Name	rb
Title	Ruby Base
Definition	Ruby base text.
User Note(s)	Also see ruby (page 164).
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	XML Schema string
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.122 Ruby Parenthesis

Table 128. Ruby Parenthesis

(XML) Data Model	Element
Namespace (prefix)	nar
Name	rp
Title	Ruby Parenthesis
Definition	Visual parentheses for Ruby Text
User Note(s)	Also see ruby (page 164).
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	XML Schema string
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	Ruby parentheses elements must be used as a pair: either both are present or none is present.
Example(s)	<pre><ruby> <rb>IPTC</rb> <rp>(<rp/><rt>International Press Telecommunications Council</rt><rp>)<rp/> </ruby></pre>



10.6.123 Ruby Text

Table 129. Ruby Text

(XML) Data Model	Element
Namespace (prefix)	nar
Name	rt
Title	Ruby Text
Definition	Ruby text.
User Note(s)	Also see ruby (page 164).
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	XML Schema string
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.124 Same As

Table 130. Same As

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	sameAs		
Title	Same As		
Definition	An identifier of an equivalent concept.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	FlexPropType (page 204)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> timeValidityAttributes (page 224) 	Name	Data Type
		validfrom (0..1)	DateOptTimeType
		validto (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.125 Scheme Declaration

Table 131. Scheme Declaration

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	scheme		
Title	Scheme Declaration		
Definition	A scheme alias-to-URI mapping.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> alias (1); XML Schema NCName; A short string assigned by the provider as a representation of the scheme URI. uri (1); IRIType (page 208); The URI which identifies the scheme. 		
	<ul style="list-style-type: none"> editAttributes (page 223) 	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
	modified (0..1)	DateOptTimeType	
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.126 Sender

Table 132. Sender

(XML) Data Model	Element
Namespace (prefix)	nar
Name	sender
Title	Sender
Definition	The sender of the items, which may be an organisation or a person.
User Note(s)	The structure of this string is not specified by the IPTC. Best practice is to identify a sender by its domain name.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	XML Schema string
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.127 Signal

Table 133. Signal

(XML) Data Model	Element
Namespace (prefix)	nar
Name	signal
Title	Signal
Definition	An instruction to the processor of this item that the content requires special handling.
User Note(s)	This property might indicate major rewriting of the content, important correction, urgent handling etc. The processor might be required to perform specific actions, depending on the contract between the provider and the recipient. Users should be alerted of the reception of an Item containing a signal by some UI mechanism (sound or display). An editorial note (edNote) may be used to convey additional natural language information related to the processing of the content.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	QualPropType (page 215)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.128 Slugline

Table 134. Slugline

(XML) Data Model	Element
Namespace (prefix)	nar
Name	slugline
Title	Slugline
Definition	A sequence of tokens associated with the content. The interpretation is provider specific.
User Note(s)	<i>separator</i> providers may choose to use more complex separation rules. In such a case the meaning of the separators must be conveyed by some other means.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	IntlStringType (page 207)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ <i>separator</i> (0..1); XML Schema string; The character string acting as a separator between the tokens in the slugline. ▪ <i>role</i> (0..1); QCodeType (page 214); The role this slugline plays in the scope of the full content.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.129 Span

Table 135. Span

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	span		
Title	Span		
Definition	A generic mechanism for adding inline information to parts of the textual content.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ class (0..1); NMTOKENS; List of classes.		
	▪ i18nAttributes (page 223)	Name	Datatype
		xml:lang (0..1)	XML Schema language
		dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .
	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
creator (0..1)		QCodeType	
modified (0..1)	DateOptTimeType		
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.130 Subject

Table 136. Subject

(XML) Data Model	Element
Namespace (prefix)	nar
Name	subject
Title	Subject
Definition	An important topic of the content; what the content is about. For a Knowledge Item the content is the set of concepts, for an event the content is the event as such.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Flex1ConceptPropType (page 197)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.131 Time Delimiter

Table 137. Time Delimiter

(XML) Data Model	Element									
Namespace (prefix)	nar									
Name	timeDelim									
Title	Time Delimiter									
Definition	A delimiter for a piece of streaming media content by time expressions.									
User Note(s)	<p>The time unit may take the following values, taken from an IPTC defined controlled vocabulary:</p> <ul style="list-style-type: none"> - timeCode: the format of the timestamps is hh:mm:ss:ff (ff for frames). - timeCodeDropFrame: the format of the timestamps is hh:mm:ss:ff (ff for frames). - editUnit: the format of the timestamps is a long unsigned integer. - normalPlayTime: the format of the timestamps is hh:mm:ss:mmm (mmm for milliseconds). <p>If no time unit is present, the value editUnit MUST be assumed.</p>									
Implementation Note(s)										
XML Schema Spec	At: PCL									
Datatype										
Internally Ctrl Values										
Externally Ctrl Values	Mandatory IPTC NewsCodes: http://cv.iptc.org/newscodes/timeunit/									
Attribute(s)	<ul style="list-style-type: none"> ▪ start (1); XML Schema string; The timestamp corresponding to the start of the part. ▪ end (1); XML Schema string; The timestamp corresponding to the end of the part. ▪ timeunit (1); QCodeType (page 214); The unit used for start and end timestamps. 									
	▪ editAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>id (0..1)</td> <td>XML Schema ID</td> </tr> <tr> <td>creator (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>modified (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>	Name	Datatype	id (0..1)	XML Schema ID	creator (0..1)	QCodeType	modified (0..1)	DateOptTimeType
		Name	Datatype							
		id (0..1)	XML Schema ID							
		creator (0..1)	QCodeType							
modified (0..1)	DateOptTimeType									
Child Element(s)										
XML Schema Note(s)										
Example(s)										



10.6.132 Timestamp

Table 138. Timestamp

(XML) Data Model	Element
Namespace (prefix)	nar
Name	timestamp
Title	Timestamp
Definition	A date-and-time associated with the message, other than the date-and-time the message was sent.
User Note(s)	The exact meaning may be refined by the role qualifier.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	DateTimePropType (page 194)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	▪ role (0..1); QCodeType (page 214); A refinement of the semantics of the property.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.133 Transmission Identifier

Table 139. Transmission Identifier

(XML) Data Model	Element
Namespace (prefix)	nar
Name	transmitId
Title	Transmission Identifier
Definition	The transmission identifier associated with the message.
User Note(s)	This string's structure is not specified by the IPTC. No two News Messages sent by the same sender on the same date may have the same identifier. In case of retransmission it is not required to update this identifier.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	XML Schema string
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.134 Type of a Concept

Table 140. Type of a Concept

(XML) Data Model	Element
Namespace (prefix)	nar
Name	type
Title	Type of a Concept
Definition	The nature of the concept.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	QualPropType (page 215)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.135 Urgency

Table 141. Urgency

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	urgency		
Title	Urgency		
Definition	The editorial urgency of the content. A value of 1 corresponds to the highest urgency, a value of 9 to the lowest.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	Int1To9Type (page 206)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
		modified (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.136 Usage Terms

Table 142. Usage Terms

(XML) Data Model	Element
Namespace (prefix)	nar
Name	usageTerms
Title	Usage Terms
Definition	A natural-language statement about the usage terms pertaining to the content.
User Note(s)	This property includes the type of usage to which the rights apply, the geographical area or areas to which specified usage rights pertain, the indication of the rights holder, restrictions on the use of the content and the time period over which the stated rights apply. If no usage terms are specified, then no specific restrictions on use of the content beyond contractual ones are being asserted.
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	RightsLabelType (page 218)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.6.137 Visual Region Delimiter

Table 143. Visual Region Delimiter

(XML) Data Model	Element		
Namespace (prefix)	nar		
Name	regionDelim		
Title	Visual Region Delimiter		
Definition	A delimiter for a rectangular region in a piece of visual content.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	A: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ x (0..1); XML Schema integer; The x-axis coordinate of the side of the rectangle which has the smaller x-axis coordinate value in the current user coordinate system. ▪ y (0..1); XML Schema integer; The y-axis coordinate of the side of the rectangle which has the smaller y-axis coordinate value in the current user coordinate system. ▪ width (0..1); XML Schema integer; The width of the rectangle. ▪ height (0..1); XML Schema integer; The height of the rectangle. 		
	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
		modified (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.6.138 Web Address

Table 144. Web Address

(XML) Data Model	Element
Namespace (prefix)	nar
Name	web
Title	Web Address
Definition	A Web address.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	IRIType (page 208)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	▪ role (0..1); QCodeListType (page 212); A refinement of the semantics of the web address.
Child Element(s)	
XML Schema Note(s)	
Example(s)	

10.7 Element Group Definitions

10.7.1 Concept Definition Group

This group of properties defines a concept using free-text. The name property MUST come first, then the other elements may be inserted in any order.

Table 145. Concept Definition Group Elements

Element Title	Element Name	Card	Described on Page
Concept Name	name	(0..unbounded)	63
Concept Definition	definition	(0..unbounded)	60
Note	note	(0..unbounded)	138
Facet	facet	(0..unbounded)	99

10.7.2 Concept Relationships Group

This group of properties defines the relationship between a concept and other concepts. The elements may be inserted in any order.

Table 146. Concept Relationships Group Elements

Element Title	Element Name	Card	Described on Page
Same As	sameAs	(0..unbounded)	168
Broader	broader	(0..unbounded)	52
Narrower	narrower	(0..unbounded)	135
Related	related	(0..unbounded)	157

10.7.3 Entity Details Group

This group of aggregate components defines detailed properties for a specific type of concept. Only one element from this group MAY be present in the wrapping context.

Table 147. Entity Details Group Elements

Element Title	Element Name	Card	Described on Page
Person Details	personDetails	(1)	146
Organisation Details	organisationDetails	(1)	142
Geopolitical Area Details	geoAreaDetails	(1)	105
POI Details	POIDetails	(1)	148
Object Details	objectDetails	(1)	139

10.7.4 Administrative Metadata Group

This group of properties is related to the administrative facet of content. The order of the elements in this group is flexible: The non-repeatable elements **MUST** come first, then the repeatable elements may be inserted in any order.

Table 148. Administrative Metadata Group Elements

Element Title	Element Name	Card	Described on Page
Urgency	urgency	(0..1)	179
Date Content Created	contentCreated	(0..1)	79
Date Content Modified	contentModified	(0..1)	80
Located	located	(0..unbounded)	119
Information Source	infoSource	(0..unbounded)	179
Creator	creator	(0..unbounded)	77
Contributor	contributor	(0..unbounded)	72
Audience	audience	(0..unbounded)	49
Excluded Audience	exclAudience	(0..unbounded)	96
Alternative Identifier	altId	(0..unbounded)	44

10.7.5 Knowledge Descriptive Metadata Group

This group of properties is related to the descriptive facet of knowledge content. The order of the elements in this group is flexible: all elements are repeatable and may be inserted in any order.

Table 149. Knowledge Descriptive Metadata Group Elements

Element Title	Element Name	Card	Described on Page
Subject	subject	(0..unbounded)	174
Description	description	(0..unbounded)	91
Language	language	(0..unbounded)	126

10.7.6 Descriptive Metadata Group

This group of properties is related to the descriptive facet of news content. The order of the elements in this group is flexible: all elements are repeatable and may be inserted in any order.

Table 150. Descriptive Metadata Group Elements

Element Title	Element Name	Card	Described on Page
Language	language	(0..unbounded)	126
Genre	genre	(0..unbounded)	103
Subject	subject	(0..unbounded)	174
Slugline	slugline	(0..unbounded)	172
Headline	headline	(0..unbounded)	109
Dateline	dateline	(0..unbounded)	89
By	by	(0..unbounded)	53
CreditLine	creditline	(0..unbounded)	78
Description	description	(0..unbounded)	91



10.7.7 Item Management Group

This group of properties is related to the management of Items. They MUST appear in the order of the table below.

Table 151. Item Management Group Elements

Element Title	Element Name	Card	Described on Page
Item Class	itemClass	(1)	120
Content Provider	provider	(1)	70
Date Item Version Created	versionCreated	(1)	83
Date Item First Created	firstCreated	(0..1)	82
Date Item Embargo Ends	embargoed	(0..1)	81
Publish Status	pubStatus	(0..1)	154
Role in the Workflow	role	(0..1)	163
File Name	filename	(0..1)	101
Generator Tool	generator	(0..1)	102
Profile	profile	(0..1)	152
Editorial Service	service	(0..unbounded)	94
Item Title	title	(0..unbounded)	124
Editorial Note	edNote	(0..unbounded)	93
Member Of	memberOf	(0..unbounded)	133
Instance Of	instanceOf	(0..unbounded)	117
Signal	signal	(0..unbounded)	171
Alternative Representation	altRep	(0..unbounded)	46



10.8 Datatype Definitions

10.8.1 Any Item Type

Table 152. Any Item Type

(XML) Data Model	Type							
Namespace (prefix)	nar							
Name	AnyItemType							
Title	Any Item Type							
Definition	An abstract class. All G2 items are inherited from this class.							
User Note(s)								
Implementation Note(s)								
XML Schema Spec	At: PCL							
Datatype								
Internally Ctrl Values								
Externally Ctrl Values								
Attribute(s)	<ul style="list-style-type: none"> standard; (0..1); string value: default = "XML Schema string"; The IPTC standard to which the Item is conformant. 							
	<ul style="list-style-type: none"> standardversion; (1); XML Schema string; restricted to the format "integer.integer"; The major-minor version of the XML schema specifying the Item. 							
	<ul style="list-style-type: none"> conformance; (1); string value: fixed = "XML Schema string" - default = "core"; The conformance level to which the Item is conformant. 							
	<ul style="list-style-type: none"> guid; (1); XML Schema string; The persistent, universally unique identifier for the Item. 							
	<ul style="list-style-type: none"> version; (0..1); XML Schema positiveInteger; The version of the Item. 							
	<table border="1"> <thead> <tr> <th></th> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td rowspan="2">▪ i18nAttributes (page 223)</td> <td>xml:lang (0..1)</td> <td>XML Schema language</td> </tr> <tr> <td>dir (0..1)</td> <td>XML Schema string; enumeration <i>ltr, rtl</i>.</td> </tr> </tbody> </table>		Name	Datatype	▪ i18nAttributes (page 223)	xml:lang (0..1)	XML Schema language	dir (0..1)
	Name	Datatype						
▪ i18nAttributes (page 223)	xml:lang (0..1)	XML Schema language						
	dir (0..1)	XML Schema string; enumeration <i>ltr, rtl</i> .						
Child Element(s)	<ul style="list-style-type: none"> catalogRef (page 158) (0..unbounded) 							
	<ul style="list-style-type: none"> catalog (page 55) (0..unbounded) 							
	<ul style="list-style-type: none"> rightsInfo (page 162) (0..unbounded) 							
	<ul style="list-style-type: none"> itemMeta (page 121) (1) 							
XML Schema Note(s)	At least one of the elements catalogRef or catalog element MUST be present. These elements MAY be inserted in any order.							
Example(s)								



10.8.2 Approximate Date and Time Property Type

Table 153. Approximate Date and Time Property Type

(XML) Data Model	Type									
Namespace (prefix)	nar									
Name	ApproximateDateTimePropType									
Title	Approximate Date and Time Property Type									
Definition	A calendar date with an optional time (with time zone) part and an optional approximation range for the date.									
User Note(s)	If a start and/or end attribute exists, then the date is approximate, else it is defined precisely by the property's date. If only the approximation start date is provided the range ends with the property value; if only the approximation end date is provided the approximation range starts with the property value.									
Implementation Note(s)										
XML Schema Spec	At: PCL									
Datatype	Union of a XML Schema dateTime, date, gYearMonth, gYear, gMonth, gMonthDay, and gDay, with the addition of the following qualifiers.									
Internally Ctrl Values										
Externally Ctrl Values										
Attribute(s)	<ul style="list-style-type: none"> ▪ approxstart (0..1); TruncatedDateTimeType (page 220); The date (and optionally time) at which the approximation range begins. ▪ approxend (0..1); TruncatedDateTimeType (page 220); The date (and optionally time) at which the approximation range ends. 									
	▪ editAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>id (0..1)</td> <td>XML Schema ID</td> </tr> <tr> <td>creator (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>modified (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>	Name	Datatype	id (0..1)	XML Schema ID	creator (0..1)	QCodeType	modified (0..1)	DateOptTimeType
		Name	Datatype							
		id (0..1)	XML Schema ID							
creator (0..1)	QCodeType									
modified (0..1)	DateOptTimeType									
Child Element(s)										
XML Schema Note(s)										
Example(s)	<p>Examples of the format {reference date, range start date, range end date}: {2006-09-20, 2006-09-18, 2006-09-30} = on about 20 September 2006, not before the 18th, not after the 30th. {1855, 1850, 1860} = in about 1855, not before the 1850, not after the 1860. {--05-03, 1950, 1953} = on a 3 May, between 1950 and 1953.</p>									



10.8.3 Audience Type

Table 154. Audience Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	AudienceType		
Title	Audience Type		
Definition	An audience for the content.		
User Note(s)	<i>significance: 1</i> – corresponds to the highest significance. <i>significance: 9</i> – corresponds to the lowest significance.		
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	Extends Flex1PropType (page 199)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ <i>significance</i> (0..1); Int1To9Type (page 206). A qualifier which indicates the expected significance of the content for this specific audience. 		
	▪ quantifyAttributes (page 223)	Name	Datatype
		confidence (0..1)	Int100Type
		relevance (0..1)	Int100Type
	why (0..1)	QCodeType	
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.8.4 Block Type

Table 155. Block Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	BlockType		
Title	Block Type		
Definition	Information about the content as natural language string with minimal markup and line breaks.		
User Note(s)	Blocks are primarily used for notes, comments or instructions created by a news provider for use by recipient editorial teams.		
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	XML mixed content		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ role (0..1); QCodeListType (page 212); A refinement of the semantics of the block. ▪ media (0..1); XML Schema NMTOKENS; An indication of the target media type(s) values as defined by the Cascading Style Sheets (CSS) specification. 		
	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
	▪ i18nAttributes (page 223)	Name	Datatype
		xml:lang (0..1)	XML Schema language
		dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .
Child Element(s)	<ul style="list-style-type: none"> ▪ a (page 47) (0..unbounded) ▪ span (page 173) (0..unbounded) ▪ ruby (page 164) (0..unbounded) ▪ br (page 127) (0..unbounded) ▪ inline (page 111) (0..unbounded) ▪ Extension Point (0..unbounded). Any set of provider-defined properties. 		
	XML Schema Note(s)		
	Example(s)		



10.8.5 Concept Identifier Type

Table 156. Concept Identifier Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	ConceptIdType
Title	Concept Identifier Type
Definition	The preferred unambiguous identifier for the concept.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ qcode (1); QCodeType (page 214); A qualified code which identifies a concept. ▪ created (0..1); DateOptTimeType (page 193); The date (and optionally the time) when the identifier was created. ▪ retired (0..1); DateOptTimeType (page 193); The date (and optionally the time) after which the concept identifier should no longer be applied as the value of a property.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.6 Content Metadata Type

Table 157. Content Metadata Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	ContentMetadataType		
Title	Content Metadata Type		
Definition			
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ i18nAttributes (page 223)	Name	Datatype
		xml:lang (0..1)	XML Schema language
		dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .
Child Element(s)	▪ Administrative Metadata Group (page 184) (0..1)	Element Name	Page
		urgency (0..1)	179
		contentCreated (0..1)	79
		contentModified (0..1)	80
		located (0..unbounded)	130
		infoSource (0..unbounded)	119
		creator (0..unbounded)	77
		contributor (0..unbounded)	72
		audience (0..unbounded)	49
		exclAudience (0..unbounded)	96
	altId (0..unbounded)	44	
	▪ Extension Point (0..unbounded). Any set of provider-defined properties.		
XML Schema Note(s)			
Example(s)			



10.8.7 Date and Optional Time Property Type

Table 158. Date and Optional Time Property Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	DateOptTimePropType		
Title	Date and Optional Time Property Type		
Definition	A date plus optionally a time and a time zone.		
User Note(s)	The time may be expressed in Universal Time Coordinates (UTC), or in local time together with a time zone offset in hours and minutes.		
Implementation Note(s)	DateOptTimePropType is used as a property datatype.		
XML Schema Spec	At: PCL		
Datatype	The union of a XML schema dateTime and date.		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
		modified (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.8.8 Date and Optional Time Type

Table 159. *Date and Optional Time Type*

(XML) Data Model	Type
Namespace (prefix)	nar
Name	DateOptTimeType
Title	Date and Optional Time Type
Definition	A date plus optionally a time and a time zone.
User Note(s)	The time may be expressed in Universal Time Coordinates (UTC), or in local time together with a time zone offset in hours and minutes.
Implementation Note(s)	DateOptTimeType is used as a datatype for attributes only.
XML Schema Spec	At: Both CCL and PCL
Datatype	The union of a XML schema dateTime (year, month, day, hour, minute, second, optional decimal fraction of a second) and date (year, month and day plus an optional time zone indicator).
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.9 Date and Time Property Type

Table 160. Date and Time Property Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	DateTimePropType		
Title	Date and Time Property Type		
Definition	A date plus a mandatory time and an optional time zone.		
User Note(s)			
Implementation Note(s)	DateTimePropType is used as a property datatype.		
XML Schema Spec	At: PCL		
Datatype	XML Schema dateTime		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
		modified (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.8.10 Electronic Address Type

Table 161. Electronic Address Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	ElectronicAddressType
Title	Electronic Address Type
Definition	
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	XML Schema string
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ role (0..1); QCodeListType (page 212); A refinement of the semantics of the electronic address.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.11 Electronic Address Tech Type

Table 162. Electronic Address Tech Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	ElectronicAddressTechType
Title	Electronic Address Tech Type
Definition	
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	XML Schema string
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ role (0..1); QCodeListType (page 212); A refinement of the semantics of the electronic address. ▪ tech (0..1); QCodeType (page 214); The technical variant of the electronic address.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.12 Flexible 1 Concept Property Type

Table 163. Flexible 1 Concept Property Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	Flex1ConceptPropType		
Title	Flexible 1 Concept Property Type		
Definition			
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	Extends Flex1PropType (page 199)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ quantifyAttributes (page 223)	Name	Datatype
		confidence (0..1)	Int100Type
		relevance (0..1)	Int100Type
		why (0..1)	QCodeType
Child Element(s)	▪ bag (page 50) (0..1)		
XML Schema Note(s)			
Example(s)			



10.8.13 Flexible 1 Party Property Type

Table 164. Flexible 1 Party Property Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	Flex1PartyPropType
Title	Flexible 1 Party Property Type
Definition	
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	Extends FlexPartyPropType (page 202)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	▪ role (0..1); QCodeListType (page 212); A refinement of the semantics of the property.
Child Element(s)	
XML Schema Note(s)	
Example(s)	

10.8.14 Flexible 1 Property Type

Table 165. Flexible 1 Property Type

(XML) Data Model	Type			
Namespace (prefix)	nar			
Name	Flex1PropType			
Title	Flexible 1 Property Type			
Definition	Flexible generic data type for both controlled and uncontrolled values.			
User Note(s)				
Implementation Note(s)				
XML Schema Spec	At: PCL			
Datatype				
Internally Ctrl Values				
Externally Ctrl Values				
Attribute(s)	<ul style="list-style-type: none"> qcode (0..1); QCodeType (page 214); A qualified code assigned as a property value. or literal (0..1); XML Schema normalizedString; A free-text value assigned as a property value. type (0..1); QCodeType (page 214); The type of the concept assigned as controlled or uncontrolled property value. 			
	▪ editAttributes (page 223)	Name	Datatype	
		id (0..1)	XML Schema ID	
		creator (0..1)	QCodeType	
	▪ i18nAttributes (page 223)	modified (0..1)	DateOptTimeType	
		Name	Datatype	
		xml:lang (0..1)	XML Schema language	
		dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .	
	Child Element(s)	▪ Concept Definition Group (page 183) (0..1)	Element Name	Page
			name (1..unbounded)	63
definition (0..unbounded)			60	
facet (0..unbounded)			99	
▪ Concept Relationships Group (page 183) (0..1)		note (0..unbounded)	138	
		Element Name	Page	
		broader (0..unbounded)	52	
		narrower (0..unbounded)	135	
▪ related (0..unbounded)		157		
		sameAs (0..unbounded)	168	
	▪ Extension Point (0..unbounded). Any set of provider-defined properties.			
XML Schema Note(s)				
Example(s)				



10.8.15 Flexible Location Property Type

Table 166. Flexible Location Property Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	FlexLocationPropType		
Title	Flexible Location Property Type		
Definition	Flexible location (i.e. geo area or POI) data type for both controlled and uncontrolled values.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ qcode (0..1); QCodeType (page 214); A qualified code assigned as property value. or ▪ literal (0..1); XML Schema normalizedString; A free-text value assigned as property value. 		
	<ul style="list-style-type: none"> ▪ type (0..1); QCodeType (page 214); The type of the concept assigned as controlled or uncontrolled property value. 		
	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
		modified (0..1)	DateOptTimeType
	▪ i18nAttributes (page 223)	Name	Datatype
		xml:lang (0..1)	XML Schema language
		dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .
	Child Element(s)	▪ Concept Definition Group (page 183) (0..1)	Element Name
name (1..unbounded)			63
definition (0..unbounded)			60
facet (0..unbounded)			99
▪ Concept Relationships Group (page 183) (0..1)		Element Name	Page
		broader (0..unbounded)	52
		narrower (0..unbounded)	135
		related (0..unbounded)	157
▪ geoAreaDetails (page 105) (0..1) or ▪ POIDetails (page 148) (0..1) ▪ Extension Point (0..unbounded). Any set of provider-defined properties.			
XML Schema Note(s)			
Example(s)			



10.8.16 Flexible Organisation Property Type

Table 167. Flexible Organisation Property Type

(XML) Data Model	Type																					
Namespace (prefix)	nar																					
Name	FlexOrganisationPropType																					
Title	Flexible Organisation Property Type																					
Definition	Flexible organisation data type for both controlled and uncontrolled values.																					
User Note(s)																						
Implementation Note(s)																						
XML Schema Spec	At: PCL																					
Datatype																						
Internally Ctrl Values																						
Externally Ctrl Values																						
Attribute(s)	<ul style="list-style-type: none"> qcode (0..1); QCodeType (page 214); A qualified code assigned as property value. or literal (0..1); XML Schema normalizedString; A free-text value assigned as property value. type (0..1); QCodeType (page 214); The type of the concept assigned as controlled or uncontrolled property value. 																					
	▪ editAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>id (0..1)</td> <td>XML Schema ID</td> </tr> <tr> <td>creator (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>modified (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>	Name	Datatype	id (0..1)	XML Schema ID	creator (0..1)	QCodeType	modified (0..1)	DateOptTimeType												
		Name	Datatype																			
		id (0..1)	XML Schema ID																			
	creator (0..1)	QCodeType																				
	modified (0..1)	DateOptTimeType																				
▪ i18nAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>xml:lang (0..1)</td> <td>XML Schema language</td> </tr> <tr> <td>dir (0..1)</td> <td>XML Schema string: enumeration <i>ltr</i>, <i>rtl</i>.</td> </tr> </tbody> </table>	Name	Datatype	xml:lang (0..1)	XML Schema language	dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .															
	Name	Datatype																				
	xml:lang (0..1)	XML Schema language																				
dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .																					
Child Element(s)	<ul style="list-style-type: none"> ▪ organisationDetails (page 142) (0..1) ▪ Concept Definition Group (page 183) (0..1) <table border="1"> <thead> <tr> <th>Element Name</th> <th>Page</th> </tr> </thead> <tbody> <tr> <td>name (1..unbounded)</td> <td>63</td> </tr> <tr> <td>definition (0..unbounded)</td> <td>60</td> </tr> <tr> <td>facet (0..unbounded)</td> <td>99</td> </tr> <tr> <td>note (0..unbounded)</td> <td>138</td> </tr> </tbody> </table> ▪ Concept Relationships Group (page 183) (0..1) <table border="1"> <thead> <tr> <th>Element Name</th> <th>Page</th> </tr> </thead> <tbody> <tr> <td>broader (0..unbounded)</td> <td>52</td> </tr> <tr> <td>narrower (0..unbounded)</td> <td>135</td> </tr> <tr> <td>related (0..unbounded)</td> <td>157</td> </tr> <tr> <td>sameAs (0..unbounded)</td> <td>168</td> </tr> </tbody> </table> ▪ Extension Point (0..unbounded). Any set of provider-defined properties. 		Element Name	Page	name (1..unbounded)	63	definition (0..unbounded)	60	facet (0..unbounded)	99	note (0..unbounded)	138	Element Name	Page	broader (0..unbounded)	52	narrower (0..unbounded)	135	related (0..unbounded)	157	sameAs (0..unbounded)	168
Element Name	Page																					
name (1..unbounded)	63																					
definition (0..unbounded)	60																					
facet (0..unbounded)	99																					
note (0..unbounded)	138																					
Element Name	Page																					
broader (0..unbounded)	52																					
narrower (0..unbounded)	135																					
related (0..unbounded)	157																					
sameAs (0..unbounded)	168																					
XML Schema Note(s)																						
Example(s)																						



10.8.17 Flexible Party Property Type

Table 168. Flexible Party Property Type

(XML) Data Model	Type											
Namespace (prefix)	nar											
Name	FlexPartyPropType											
Title	Flexible Party Property Type											
Definition	Flexible party (i.e. person or organisation) data type for both controlled and uncontrolled values.											
User Note(s)												
Implementation Note(s)												
XML Schema Spec	At: PCL											
Datatype												
Internally Ctrl Values												
Externally Ctrl Values												
Attribute(s)	<ul style="list-style-type: none"> ▪ qcode (0..1); QCodeType (page 214); A qualified code assigned as property value. or ▪ literal (0..1); XML Schema normalizedString; A free-text value assigned as property value. ▪ type (0..1); QCodeType (page 214); The type of the concept assigned as controlled or uncontrolled property value. 											
	▪ editAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>id (0..1)</td> <td>XML Schema ID</td> </tr> <tr> <td>creator (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>modified (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>	Name	Datatype	id (0..1)	XML Schema ID	creator (0..1)	QCodeType	modified (0..1)	DateOptTimeType		
		Name	Datatype									
		id (0..1)	XML Schema ID									
	creator (0..1)	QCodeType										
	modified (0..1)	DateOptTimeType										
	▪ i18nAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>xml:lang (0..1)</td> <td>XML Schema language</td> </tr> <tr> <td>dir (0..1)</td> <td>XML Schema string: enumeration <i>ltr</i>, <i>rtl</i>.</td> </tr> </tbody> </table>	Name	Datatype	xml:lang (0..1)	XML Schema language	dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .				
Name		Datatype										
xml:lang (0..1)		XML Schema language										
dir (0..1)	XML Schema string: enumeration <i>ltr</i> , <i>rtl</i> .											
Child Element(s)	<ul style="list-style-type: none"> ▪ personDetails (page 146) (0..1) or ▪ organisationDetails (page 142) (0..1) 											
	▪ Concept Definition Group (page 183) (0..1)	<table border="1"> <thead> <tr> <th>Element Name</th> <th>Page</th> </tr> </thead> <tbody> <tr> <td>name (1..unbounded)</td> <td>63</td> </tr> <tr> <td>definition (0..unbounded)</td> <td>60</td> </tr> <tr> <td>facet (0..unbounded)</td> <td>99</td> </tr> <tr> <td>note (0..unbounded)</td> <td>138</td> </tr> </tbody> </table>	Element Name	Page	name (1..unbounded)	63	definition (0..unbounded)	60	facet (0..unbounded)	99	note (0..unbounded)	138
		Element Name	Page									
		name (1..unbounded)	63									
		definition (0..unbounded)	60									
	facet (0..unbounded)	99										
	note (0..unbounded)	138										
▪ Concept Relationships Group (page 183) (0..1)	<table border="1"> <thead> <tr> <th>Element Name</th> <th>Page</th> </tr> </thead> <tbody> <tr> <td>broader (0..unbounded)</td> <td>52</td> </tr> <tr> <td>narrower (0..unbounded)</td> <td>135</td> </tr> <tr> <td>related (0..unbounded)</td> <td>157</td> </tr> <tr> <td>sameAs (0..unbounded)</td> <td>168</td> </tr> </tbody> </table>	Element Name	Page	broader (0..unbounded)	52	narrower (0..unbounded)	135	related (0..unbounded)	157	sameAs (0..unbounded)	168	
	Element Name	Page										
	broader (0..unbounded)	52										
	narrower (0..unbounded)	135										
related (0..unbounded)	157											
sameAs (0..unbounded)	168											
▪ Extension Point (0..unbounded). Any set of provider-defined properties.												
XML Schema Note(s)												
Example(s)												



10.8.18 Flex Person Property Type

Table 169. Flex Person Property Type

(XML) Data Model	Type											
Namespace (prefix)	nar											
Name	FlexPersonPropType											
Title	Flex Person Property Type											
Definition	Flexible person data type for both controlled and uncontrolled values.											
User Note(s)												
Implementation Note(s)												
XML Schema Spec	At: PCL											
Datatype												
Internally Ctrl Values												
Externally Ctrl Values												
Attribute(s)	<ul style="list-style-type: none"> ▪ qcode (0..1); QCodeType (page 214); A qualified code assigned as property value. or ▪ literal (0..1); XML Schema normalizedString; A free-text value assigned as property value. ▪ type (0..1); QCodeType (page 214); The type of the concept assigned as controlled or uncontrolled property value. 											
	▪ editAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>id (0..1)</td> <td>XML Schema ID</td> </tr> <tr> <td>creator (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>modified (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>	Name	Datatype	id (0..1)	XML Schema ID	creator (0..1)	QCodeType	modified (0..1)	DateOptTimeType		
		Name	Datatype									
		id (0..1)	XML Schema ID									
	creator (0..1)	QCodeType										
	modified (0..1)	DateOptTimeType										
▪ i18nAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>xml:lang (0..1)</td> <td>XML Schema language</td> </tr> <tr> <td>dir (0..1)</td> <td>XML Schema string: enumeration <i>ltr, rtl</i>.</td> </tr> </tbody> </table>	Name	Datatype	xml:lang (0..1)	XML Schema language	dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .					
	Name	Datatype										
xml:lang (0..1)	XML Schema language											
dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .											
Child Element(s)	▪ personDetails (page 146) (0..1)											
	▪ Concept Definition Group (page 183) (0..1)	<table border="1"> <thead> <tr> <th>Element Name</th> <th>Page</th> </tr> </thead> <tbody> <tr> <td>name (1..unbounded)</td> <td>63</td> </tr> <tr> <td>definition (0..unbounded)</td> <td>60</td> </tr> <tr> <td>facet (0..unbounded)</td> <td>99</td> </tr> <tr> <td>note (0..unbounded)</td> <td>138</td> </tr> </tbody> </table>	Element Name	Page	name (1..unbounded)	63	definition (0..unbounded)	60	facet (0..unbounded)	99	note (0..unbounded)	138
		Element Name	Page									
		name (1..unbounded)	63									
		definition (0..unbounded)	60									
	facet (0..unbounded)	99										
note (0..unbounded)	138											
▪ Concept Relationships Group (page 183) (0..1)	<table border="1"> <thead> <tr> <th>Element Name</th> <th>Page</th> </tr> </thead> <tbody> <tr> <td>broader (0..unbounded)</td> <td>52</td> </tr> <tr> <td>narrower (0..unbounded)</td> <td>135</td> </tr> <tr> <td>related (0..unbounded)</td> <td>157</td> </tr> <tr> <td>sameAs (0..unbounded)</td> <td>168</td> </tr> </tbody> </table>	Element Name	Page	broader (0..unbounded)	52	narrower (0..unbounded)	135	related (0..unbounded)	157	sameAs (0..unbounded)	168	
	Element Name	Page										
	broader (0..unbounded)	52										
	narrower (0..unbounded)	135										
related (0..unbounded)	157											
sameAs (0..unbounded)	168											
▪ Extension Point (0..unbounded). Any set of provider-defined properties.												
XML Schema Note(s)												
Example(s)												



10.8.19 Flexible Property Type

Table 170. Flexible Property Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	FlexPropType		
Title	Flexible Property Type		
Definition	Flexible generic data type for both controlled and uncontrolled values.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ qcode (0..1); QCodeType (page 214); A qualified code assigned as a property value. or ▪ literal (0..1); XML Schema normalizedString; A free-text value assigned as a property value. ▪ type (0..1); QCodeType (page 214); The type of the concept assigned as a controlled or uncontrolled property value. 		
	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
	▪ i18nAttributes (page 223)	Name	Datatype
		xml:lang (0..1)	XML Schema language
dir (0..1)		XML Schema string: enumeration <i>ltr, rtl</i> .	
Child Element(s)	▪ name (page 153) (0..unbounded)		
XML Schema Note(s)			
Example(s)			



10.8.20 Integer 0 to 100 Type

Table 171. Integer 0 to 100 Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	Int100Type
Title	Integer 0 to 100 Type
Definition	An integer with a value range from 0 to 100.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	XML Schema integer, value restriction 0 to 100.
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.21 Integer 1 to 9 Type

Table 172. Integer 1 to 9 Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	Int1To9Type
Title	Integer 1 to 9 Type
Definition	An integer with a value range from 1 to 9.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	XML Schema integer, value restriction 1 to 9.
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.22 International String Type

Table 173. International String Type

(XML) Data Model	Type			
Namespace (prefix)	nar			
Name	IntlStringType			
Title	International String Type			
Definition	An internationalized string, where the language and directionality in which the information is written are indicated.			
User Note(s)				
Implementation Note(s)				
XML Schema Spec	At: PCL			
Datatype				
Internally Ctrl Values				
Externally Ctrl Values				
Attribute(s)	▪ i18nAttributes (page 223)	Name	Datatype	
		xml:lang (0..1)	XML Schema language	
	▪ editAttributes (page 223)	dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .	
		Name	Datatype	
		id (0..1)	XML Schema ID	
		creator (0..1)	QCodeType	
		modified (0..1)	DateOptTimeType	
Child Element(s)				
XML Schema Note(s)				
Example(s)				



10.8.23 IRI Type

Table 174. IRI Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	IRIType
Title	IRI Type
Definition	An Internationalized Resource Identifier reference, as defined by RFC3987.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	XML Schema anyURI
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	

10.8.24 Label 1 Type

Table 175. Label 1 Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	Label1Type		
Title	Label 1 Type		
Definition	Information about the content as natural language string with minimal markup.		
User Note(s)	Labels are assertions expressed as natural language strings intended to be consumed by human beings. They are typically displayed alongside the content of an Item or in place of Items in a list, providing a means of selection among them.		
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	XML mixed content		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> ▪ role (0..1); QCodeListType (page 212); A refinement of the semantics of the label. ▪ media (0..1); XML Schema NMTOKENS; An indication of the target media type(s), values as defined by the Cascading Style Sheets (CSS) specification. 		
	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
	▪ i18nAttributes (page 223)	Name	Datatype
		xml:lang (0..1)	XML Schema language
		dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .
Child Element(s)	<ul style="list-style-type: none"> ▪ a (page 47) (0..unbounded) ▪ span (page 173) (0..unbounded) ▪ ruby (page 164) (0..unbounded) ▪ inline (page 111) (0..unbounded) ▪ Extension Point (0..unbounded). Any set of provider-defined properties. 		
	XML Schema Note(s)		
	Anchor, Span and Ruby are modelled after their XHTML 1.1 counterparts.		
	Example(s)		



10.8.25 Link 1 Type

Table 176. Link 1 Type

(XML) Data Model	Type														
Namespace (prefix)	nar														
Name	Link1Type														
Title	Link 1 Type														
Definition	A datatype for linking this item to other items or resources.														
User Note(s)	To identify the target resource either the residref attribute or the href attribute MUST be set, optionally both MAY be used in parallel. The residref attribute identifies the target resource by its globally unique identifier (if the resource has such an identifier), while the href attribute identifies the location of the target resource in e.g. a (remote) file system. If the target resource is an Item and the residref attribute is used, a version attribute MAY indicate the target Item version; in the absence of version information, the target resource is the latest version available.														
Implementation Note(s)															
XML Schema Spec	At: PCL														
Datatype															
Internally Ctrl Values															
Externally Ctrl Values															
Attribute(s)	<ul style="list-style-type: none"> rank (0..1); XML Schema nonNegativeInteger; The rank of the link among other links. rel (0..1); QCodeType (page 214); The identifier of the relationship between the current Item and the target resource. 														
	▪ editAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>id (0..1)</td> <td>XML Schema ID</td> </tr> <tr> <td>creator (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>modified (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>	Name	Datatype	id (0..1)	XML Schema ID	creator (0..1)	QCodeType	modified (0..1)	DateOptTimeType					
		Name	Datatype												
		id (0..1)	XML Schema ID												
	creator (0..1)	QCodeType													
	modified (0..1)	DateOptTimeType													
	▪ i18nAttributes (page 223)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>xml:lang (0..1)</td> <td>XML Schema language</td> </tr> <tr> <td>dir (0..1)</td> <td>XML Schema string: enumeration <i>ltr, rtl</i>.</td> </tr> </tbody> </table>	Name	Datatype	xml:lang (0..1)	XML Schema language	dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .							
		Name	Datatype												
	xml:lang (0..1)	XML Schema language													
	dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .													
	▪ timeValidityAttributes (page 224)	<table border="1"> <thead> <tr> <th>Name</th> <th>Data Type</th> </tr> </thead> <tbody> <tr> <td>validfrom (0..1)</td> <td>DateOptTimeType</td> </tr> <tr> <td>validto (0..1)</td> <td>DateOptTimeType</td> </tr> </tbody> </table>	Name	Data Type	validfrom (0..1)	DateOptTimeType	validto (0..1)	DateOptTimeType							
		Name	Data Type												
	validfrom (0..1)	DateOptTimeType													
validto (0..1)	DateOptTimeType														
▪ targetResourceAttributes (page 225)	<table border="1"> <thead> <tr> <th>Name</th> <th>Datatype</th> </tr> </thead> <tbody> <tr> <td>href (0..1)</td> <td>IRIType</td> </tr> <tr> <td>residref (0..1)</td> <td>XML Schema string</td> </tr> <tr> <td>version (0..1)</td> <td>XML Schema positiveInteger</td> </tr> <tr> <td>contenttype (0..1)</td> <td>XML Schema string</td> </tr> <tr> <td>format (0..1)</td> <td>QCodeType</td> </tr> <tr> <td>size (0..1)</td> <td>XML Schema non NegativeInteger</td> </tr> </tbody> </table>	Name	Datatype	href (0..1)	IRIType	residref (0..1)	XML Schema string	version (0..1)	XML Schema positiveInteger	contenttype (0..1)	XML Schema string	format (0..1)	QCodeType	size (0..1)	XML Schema non NegativeInteger
	Name	Datatype													
	href (0..1)	IRIType													
	residref (0..1)	XML Schema string													
	version (0..1)	XML Schema positiveInteger													
	contenttype (0..1)	XML Schema string													
format (0..1)	QCodeType														
size (0..1)	XML Schema non NegativeInteger														
<ul style="list-style-type: none"> guidref (0..1); XML Schema string; The use of this attribute is DEPRECATED, use <i>residref</i> instead. hreftype (0..1); XML Schema normalizedString; The use of this attribute is DEPRECATED, use <i>contenttype</i> instead. 															



Table 176. Link 1 Type (Continued)

Child Element(s)	Extension Points (0..unbounded). Any set of hints, i.e. properties extracted from the target resource.
XML Schema Note(s)	Extension Point: a particular hint is a title, already defined at the CCL as a short natural language name representing the link and displayed to the users.
Example(s)	



10.8.26 QCode List Type

Table 177. QCode List Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	QCodeListType
Title	QCode List Type
Definition	A space-separated list of QCodeType values.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	List of QCodeType values.
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.27 QCode Property Type

Table 178. QCode Property Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	QCodePropType		
Title	QCode Property Type		
Definition	An element with a QCode value in a qcode attribute.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype			
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> qcode (1); QCodeType (page 214); A qualified code assigned as a property value. 		
	<ul style="list-style-type: none"> editAttributes (page 223) 	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
	modified (0..1)	DateOptTimeType	
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.8.28 QCode Type

Table 179. QCode Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	QCodeType
Title	QCode Type
Definition	A QCode value.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	A set of characters (no whitespace, no colon) followed by a colon (:) character, followed by a set of characters with no whitespace. The corresponding regular expression is: <code>[^\s:]+:[^\s]+</code>
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.29 Qualified Property Type

Table 180. Qualified Property Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	QualPropType		
Title	Qualified Property Type		
Definition	An element with a QCode value and optional names.		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	Extends QCodePropType (page 213)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ i18nAttributes (page 223)	Name	Datatype
		xml:lang (0..1)	XML Schema language
		dir (0..1)	XML Schema string: enumeration <i>ltr, rtl</i> .
Child Element(s)	▪ name (page 63) (0..unbounded)		
XML Schema Note(s)			
Example(s)			



10.8.30 Recurrence Rule Type

Table 181. Recurrence Rule Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	RecurrenceRuleType
Title	Recurrence Rule Type
Definition	A rule of recurrence applied to a date associated with an event.
User Note(s)	The different datatypes listed in the Attribute(s) row below correspond to iCalendar datatypes and enumerations.
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	<ul style="list-style-type: none"> ▪ freq (1); XML Schema string; The type of recurrence rule. ▪ interval (0..1); XML Schema positiveInteger; How often the recurrence rule repeats. ▪ until (0..1); DateOptTimeType (page 193); A date-time value which bounds the recurrence rule in an inclusive manner. ▪ count (0..1); XML Schema positiveInteger; The number of occurrences at which to range-bound the recurrence. ▪ bysecond (0..1); tokens of XML Schema nonNegativeInteger 0..59 ; The BYSECOND rule part specifies a space separated list of seconds within a minute. ▪ byminute (0..1); tokens of XML Schema nonNegativeInteger 0..59; The BYMINUTE rule part specifies a space separated list of minutes within an hour. ▪ byhour (0..1); tokens of XML Schema nonNegativeInteger 0..23; The BYHOUR rule part specifies space separated list of hours of the day. ▪ byday (0..1); tokens of XML Schema string, regEx pattern = "(\\- \\+)?([0-9]){0,2}(MO TU WE TH FR SA SU)": ; The BYDAY rule part specifies a space separated list of days of the week. ▪ bymonthday (0..1); tokens of XML Schema Integer -31..-1 and 1..31; The BYMONTHDAY rule part specifies a space separated list of days of the month. ▪ bymonth (0..1); tokens of XML Schema nonNegativeInteger 1..12; The BYMONTH rule part specifies a space separated list of months of the year. ▪ byyearday (0..1); tokens of XML Schema Integer -366..-1 and 1..366; The BYYEAR-DAY rule part specifies a space separated list of days of the year. ▪ byweekno (0..1); tokens of XML Schema Integer -53..-1 and 1..53; The BYWEEKNO rule part specifies a space separated list of ordinals specifying weeks of the year. ▪ bysetpos (0..1); tokens of XML Schema Integer -366..-1 and 1..366; The BYSET-POS rule part specifies a space separated list of values which corresponds to the nth occurrence within the set of events specified by the rule. ▪ wkst (0..1); XML schema string, enumeration; The day on which the workweek starts.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.31 Related Concept Type

Table 182. Related Concept Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	RelatedConceptType		
Title	Related Concept Type		
Definition	An identifier of a related concept, where the relationship is different from elements <i>sameAs</i> , <i>broader</i> , or <i>narrower</i> .		
User Note(s)			
Implementation Note(s)			
XML Schema Spec	At: PCL		
Datatype	Extends FlexPropType (page 204)		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	<ul style="list-style-type: none"> rel (0..1); QCodeType (page 214); The identifier of the relationship between the current concept and the target concept. 		
	<ul style="list-style-type: none"> rank (0..1); XML Schema positiveInteger; The rank of the current concept among concepts having a relationship to the target concept. 		
	<ul style="list-style-type: none"> timeValidityAttributes (page 224) 	Name	Data Type
		validfrom (0..1)	DateOptTimeType
	validto (0..1)	DateOptTimeType	
Child Element(s)	<ul style="list-style-type: none"> facet (page 99) (0..unbounded) 		
XML Schema Note(s)			
Example(s)			



10.8.32 Rights Label Type

Table 183. Rights Label Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	RightsLabelType
Title	Rights Label Type
Definition	
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	BlockType (page 189)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	▪ href (0..1); IRIType (page 208); The locator of a remote expression of rights.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.33 Truncated Date and Time Property Type

Table 184. Truncated Date and Time Property Type

(XML) Data Model	Type		
Namespace (prefix)	nar		
Name	TruncatedDateTimePropType		
Title	Truncated Date and Time Property Type		
Definition	An element with a calendar date as a value. The date has an optional time part: it is optionally possible to omit one to many less significant components, from right to left. "From right to left" means starting from the least significant component (i.e. fraction of a second) and to continue with the full time part, the day part and the month part. The year part must not be omitted.		
User Note(s)			
Implementation Note(s)	TruncatedDateTimePropType is used as a property datatype.		
XML Schema Spec	At: PCL		
Datatype	The union of a XML Schema dateTime, date, gYearMonth and gYear, and additionally supports provider-defined qualifiers.		
Internally Ctrl Values			
Externally Ctrl Values			
Attribute(s)	▪ editAttributes (page 223)	Name	Datatype
		id (0..1)	XML Schema ID
		creator (0..1)	QCodeType
		modified (0..1)	DateOptTimeType
Child Element(s)			
XML Schema Note(s)			
Example(s)			



10.8.34 Truncated Date and Time Type

Table 185. Truncated Date and Time Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	TruncatedDateTimeType
Title	Truncated Date and Time Type
Definition	A calendar date with an optional time part: it is optionally possible to omit one to many less significant components, from right to left. "From right to left" means starting from the least significant component (i.e. fraction of a second) and to continue with the full time part, the day part and the month part. The year part must not be omitted.
User Note(s)	
Implementation Note(s)	TruncatedDateTimeType is used as a qualifier datatype.
XML Schema Spec	At: Both CCL and PCL
Datatype	The union of a XML Schema dateTime, date, gYearMonth and gYear.
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.35 Typed Qualified Property Type

Table 186. Typed Qualified Property Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	TypedQualPropType
Title	Typed Qualified Property Type
Definition	An element with a QCode value and an additional type for this value.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: Both CCL and PCL
Datatype	QualPropType (page 215)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	▪ type (0..1); QCodeType (page 214); The type of the concept assigned as property value.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.8.36 Versioned String Type

Table 187. Versioned String Type

(XML) Data Model	Type
Namespace (prefix)	nar
Name	VersionedStringType
Title	Versioned String Type
Definition	The type extending IntlStringType by a version information.
User Note(s)	
Implementation Note(s)	
XML Schema Spec	At: PCL
Datatype	IntlStringType (page 207)
Internally Ctrl Values	
Externally Ctrl Values	
Attribute(s)	▪ versioninfo (0..1); XML schema string; The version of a processing resource.
Child Element(s)	
XML Schema Note(s)	
Example(s)	



10.9 Attribute Group Definitions

10.9.1 Internationalization Attributes Group

Table 188. *i18nAttributes*

Title	Name	Card	Datatype	Definition
Language Indicator	xml:lang	0..1	XML Schema language	The language of textual content.
Direction	dir	0..1	XML Schema string: enumeration <i>ltr, rtl</i> .	The directionality of textual content.

Notes:

- ◆ *xml:lang* values MUST follow RFC 4646 and RFC 4647 (as both replace RFC 3066) or its successor. See also IETF BCP47.
- ◆ The *dir* qualifier specifies the directionality of scripted text: left-to-right (“ltr”, the default) or right-to-left (“rtl”). Its definition follows the XHTML 1.0 production. Directionality – left-to-right or right-to-left – is assigned to characters in Unicode, in order to allow the text to be rendered properly. For example, while English characters are presented left-to-right, Hebrew characters are presented right-to-left. Unicode defines a bidirectional algorithm that must be applied whenever a document contains right-to-left characters. While this algorithm usually gives the proper presentation, some situations leave directionally neutral text and require the *dir* attribute to specify the base directionality.

10.9.2 Editing Attributes Group

These attributes are used only at PCL.

Table 189. *editAttributes*

Title	Name	Card	Datatype	Definition
Local Identifier	id	0..1	XML Schema ID	The local identifier of the element.
Creator	creator	0..1	QCodeType	If the supporting property has no value, specifies which party (person, organisation or system) will edit the property. If the supporting property has a value, specifies which party (person, organisation or system) has edited the property.
Date Modified	modified	0..1	DateOptTimeType	The date (and, optionally, the time) when the property was last modified. The initial value is the date (and, optionally, the time) of creation of the property.

10.9.3 Quantify Attributes Group

These attributes are used only at PCL.

Table 190. *quantifyAttributes*

Title	Name	Card	Datatype	Definition
Confidence	confidence	0..1	Int100Type	The confidence with which the metadata has been assigned.
Relevance	relevance	0..1	Int100Type	The relevance of the metadata to the news content to which it is attached.
Why	why	0..1	QCodeType	Why the metadata has been included.



Notes:

- ◆ An indication of confidence is usually obtained by automatic categorization means. 100 is the highest value.
- ◆ A high relevance indicates that this piece of metadata truly expresses what the piece of news is about, while a low relevance indicates a low correlation between the metadata and the essence of the piece of news.
- ◆ *why* indicates whether the metadata is directly extracted from the content by a tool and/or by a person, whether it is an ancestor of some other concept directly associated with the content (e.g. the concepts France and Europe are ancestors of the concept Paris), or whether it is derived by look-up in a thesaurus (e.g. the entity Merck may be associated with the concept Pharmaceutical Industry Sector).

10.9.4 Time Validity Attributes Group

These attributes are used only at PCL.

Table 191. *timeValidityAttributes*

Title	Name	Card	Datatype	Definition
Valid From	validfrom	0..1	DateOptTimeType	The date (and optionally the time) <i>before</i> which a relationship is not valid.
Valid To	validto	0..1	DateOptTimeType	The date (and optionally the time) <i>after</i> which a relationship is not valid.

10.9.5 News Content Attributes

Table 192. *newsContentAttributes*

Title	Name	Card	Datatype	Definition
Local Identifier	id	0..1	XML Schema ID	The local identifier of the element.
Rendition	rendition	0..1	QCodeType	The specific rendition of content this component represents.
Generator tool	generator	0..1	XML Schema string	The name and version of the software tool used to generate the content.
Generated	generated	0..1	DateOptTimeType	The date (and, optionally, the time) when the content was generated.

Notes:

- ◆ *rendition* helps the processor choosing between alternative content components. Thus a picture may have pieces of content rendered as “thumbnail” or “preview”, a text Item may contain an “sms”, a “web” and a “print” rendition; values may be extended by individual providers.
- ◆ Note that *contentType* and *itemClass* of **Item Metadata** (page 121) are complementary. *itemClass* indicates the nature of the Item's content, but not the format of the components it contains: an Item can be of class “video” with a gif thumbnail and a mpeg2 main rendition.
- ◆ *format* is used if no precise content type exists (e.g. “application/xml” or “text/plain” are the only mime types available for a given format). In such a case the Content Type information is complement with Format information. For example the NSK variant of the TIFF format can be expressed as: Content Type = “image/tiff” plus Format = “fmt:NSk”.

10.9.6 Target Resource Attributes Group

Table 193. *targetResourceAttributes*

Title	Name	Card	Data Type	Definition
Hyperlink	href	0..1	IRIType	The locator of the target resource
Resource Identifier Reference	residref	0..1	XML Schema string	The provider's identifier of the target resource
Item Version	version	0..1	XML Schema positiveInteger	The version of the target resource
Content Type	contenttype	0..1	XML Schema string	The IANA (Internet Assigned Numbers Authority) MIME type of the target resource
Format	format	0..1	QCodeType	A refinement of a generic content type (i.e. IANA MIME type)
Size	size	0..1	XML Schema non NegativeInteger	The size in bytes of the target resource

10.9.7 News Content Characteristics

To be implemented as an attribute group.

Table 194. *newsContentCharacteristics*

Title	Name	Card	Datatype	Definition
Word Count	wordcount	0..1	XML Schema nonNegativeInteger	The count of words of textual content. Applies to textual content.
Image Width	width	0..1	XML Schema nonNegativeInteger	The width of an image in pixels. Applies to image content. For video content, this is the number of pixels per lines.
Image Height	height	0..1	XML Schema nonNegativeInteger	The height of an image in pixels. Applies to image content. For video content, this is the number of lines per frame.
Image Orientation	orientation	0..1	XML Schema nonNegativeInteger	The orientation of the visual content of an image in regard to the standard rendition of the digital image data. Values in the range of 1 to 8 are compatible with the TIFF 6.0 and Exif 2.3 specifications. Applies to image content. Details about the values can be found in Table 195 .
Image Colour Space	colourspace	0..1	QCodeType	The colour space of an image. Applies to image content.
Resolution	resolution	0..1	XML Schema positiveInteger	The recommended printing resolution for an image in dots per inch. Applies to image content.
Duration	duration	0..1	XML Schema nonNegativeInteger	The clip duration in seconds. Applies to audio-visual content.
Audio Codec	audiocodec	0..1	QCodeType	The applicable codec for audio data. Applies to audio content.
Audio Bit Rate	audiobitrate	0..1	XML Schema positiveInteger	The audio bit rate in Kbps. Applies to audio content.

Table 194. *newsContentCharacteristics (Continued)*









Title	Name	Card	Datatype	Definition
Audio Variable Bit Rate flag	audiovbr	0..1	XML Schema boolean	An indication that the audio data is encoded with a variable bit rate. Applies to audio content.
Audio Sample Size	audiosamplesize	0..1	XML Schema positiveInteger	The number of bits per audio sample, e.g. 16. Applies to audio content. Aliases: audio bits per sample, audio resolution, audio encoding depth.
Audio Sample Rate	audiosamplerate	0..1	XML Schema positiveInteger	The number of audio samples per second, expressed as a sampling frequency in Hz, e.g. 44100. Applies to audio content.
Audio Channels	audiochannels	0..1	QCodeType	The audio sound system, e.g. <i>mono</i> , <i>stereo</i> , <i>surround</i> . Codes may represent e.g. <i>mono</i> , <i>stereo</i> , <i>surround</i> . Applies to audio content.
Video Codec	videocodec	0..1	QCodeType	The applicable codec for video data. Applies to video content.
Video Average Bit Rate	videoavgbitrates	0..1	XML Schema positiveInteger	The video average bit rate in Kbps. Used when the bit rate is variable. Applies to video content.
Video Variable Bit Rate flag	videovbr	0..1	XML Schema boolean	An indication that video data is encoded with a variable bit rate. Applies to video content.
Video Frame Rate	videoframerate	0..1	XML Schema positiveInteger	The number of video frames per second, i.e. the rate at which the material should be shown in order to achieve the intended visual effect. This is the rate at which the material should be shown in order to achieve the intended visual effect. Applies to video content.
Video Scan Technique	videoscan	0..1	enumeration progressive/interlaced	The video scan technique, progressive or interlaced. Applies to video content.
Video Aspect Ratio	videoaspectratio	0..1	XML Schema normalizedString	The video aspect ratio, e.g. 4:3 or 16:9. Applies to video content.
Video Sampling Method	videosampling	0..1	XML Schema normalizedString	The video sampling method, e.g. 4:1:1. Applies to video content.

Table 195 enumerates the allowed values for the **orientation** attribute. The values are integers from 1 to 8 and reflect the TIFF 6.0 and Exif 2.3 specification.

Remark on the Definition column: by the Exif specification the "0th row" is the first row which has been scanned for the digital image and the "0th column" the first column. The explanation describes how a picture having the orientation of value 1 has to be flipped and/or rotated to align with one of the values 2 through 8.

The column "Visual example" shows a picture of the character F having an orientation aligning with the value. For the viewer's convenience the visual top, bottom, left and right of an image are marked up with the initial character of the corresponding term.

Table 195. Orientation Values

Value	Definition and Explanation	Visual Example
1	The 0th row is at the visual top of the image, and the 0th column is the visual left-hand side. Explanation: upright, no flip, no rotation.	
2	The 0th row is at the visual top of the image, and the 0th column is the visual right-hand side. Explanation: upright, image flipped about the vertical axis.	
3	The 0th row is at the visual bottom of the image, and the 0th column is the visual right-hand side. Explanation: image rotated 180 degrees.	
4	The 0th row is at the visual bottom of the image, and the 0th column is the visual left-hand side. Explanation: image flipped about the vertical axis and rotated 180 degrees.	
5	The 0th row is the visual left-hand side of the image, and the 0th column is the visual top. Explanation: image flipped about the vertical axis and rotated 90 degrees counterclockwise.	
6	The 0th row is the visual right-hand side of the image, and the 0th column is the visual top. Explanation: image rotated 90 degrees counterclockwise.	
7	The 0th row is the visual right-hand side of the image, and the 0th column is the visual bottom. Explanation: image flipped about the vertical axis and rotated 90 degrees clockwise.	
8	The 0th row is the visual left-hand side of the image, and the 0th column is the visual bottom. Explanation: image rotated 90 degrees clockwise.	

11 Glossary

Table 196. Glossary

Term	Definition
alias	See scheme alias .
anonymous controlled vocabulary	A controlled vocabulary that is not a scheme .
catalog	A file containing information about scheme(s) .
code	A character sequence which forms a member of a controlled vocabulary .
concept	Anything that one may wish to refer to, e.g. Diplomacy, Paris, the Euro, OECD, the Japanese language, the IMF, Oil, Madonna, Olympic Games. Thus concept here has a broader meaning than is usual. This is because we are dealing with the idea of Paris, rather than with Paris itself, the idea of Oil, rather than Oil itself, and so on. Concepts fall in two broad categories: named entity and generic (or abstract) concepts. A concept may be defined by a ConceptItem .
ConceptItem	A specialised data structure containing data representing a concept . An identifier for the concept is mandatory and it may, optionally, provide information such as name, definition, relationships, etc. A concept defined by a ConceptItem is identified by a {scheme alias, code} pair. The reverse relationship does not necessarily hold. In other words, there is no requirement that each {scheme alias, code} pair has a corresponding ConceptItem. See also: representation of a ConceptItem .
concept type	A concept type allows the logical grouping of all similar concept(s) , regardless of the scheme(s) the concepts belong to. Examples of concept type might be: Person, Organisation, Language, Business Sector, News Subject or Geography. A concept type is itself a concept and, as such, is represented by a code in a scheme.
concept URI	A URI which identifies a concept . A concept URI is obtained by appending the code representing this concept to the scheme URI corresponding to the scheme to which the code belongs. An abbreviated notation of a concept URI is a Qualified code, QCode .
conformance level	A layer of functionality defined by a standard. The News Architecture power conformance level is a superset of the News Architecture core conformance level, both in terms of structure and processing.
controlled vocabulary	A set of code(s) , managed by some authority (e.g. a person or an organisation), employing some mechanism (e.g. an XML Schema, a Web page, an RFC, or KnowledgeItem) to maintain this set. A controlled vocabulary is either a scheme or is anonymous (i.e. an anonymous controlled vocabulary). Each code in a controlled vocabulary represents a concept .
constrained metadata container	A metadata container which either accepts only code(s) of a specified concept type or accepts only codes from a specified controlled vocabulary (which may be an anonymous controlled vocabulary or a scheme).
Definition	A human-readable string, held within a ConceptItem , which defines the concept which the item represents. Definitions will be implemented using free-form text .
formal metadata element	A metadata element designed to hold data that is not free-form text , e.g. code(s) , or formal text . Such data is usually consumed by software. An example of such an element with a code value is subject. An example value of <i>subject</i> is "nc:15062000".
free-form metadata element	A metadata element designed to hold free-form text . Such data is usually consumed by humans. An example of a free-form metadata element is title. An example value of title is "Ian Thorpe makes a splash". The News Architecture provides a couple of datatypes for free-form text, e.g. International String, Label or BlockText.

Table 196. Glossary (Continued)

Term	Definition
free-form text	Arbitrary text, i.e. text which does not consist of code(s) drawn from a controlled vocabulary . A headline or a description is an example of free-form text.
formal text	A set of one or more metadata container(s) for free-form text to express formal information about a specific concept , but without identifying it. Basic properties for formal text are literal, name, definition and note. An example for formal text is the Creator property with a value of name = "Alfred Hitchcock", definition = "Suspense movie director and producer, born 1899, died 1980".
globally unique identifier	An identifier that is unique, unambiguous, and persistent. Being unique and unambiguous means that there is a 1:1 relationship between the identifier and the identified object. Being persistent means that the identifier never changes as time passes, and that it is never reused as an identifier for another object even if the original object disappears. See also persistent identifier , unambiguous identifier , and unique identifier .
Identifier	A string used to identify a specific resource . See persistent identifier , unambiguous identifier , unique identifier , and globally unique identifier (GUID) .
KnowledgeItem	A Knowledge Item is a set of concept definitions to form a consistent structure, which is managed, protected and published as a whole. It facilitates the management and exchange of controlled vocabulary(ies) .
Label	A generic term for datatypes designed to hold free-form text .
Metadata	Data which asserts something about some other data.
metadata container	A location (e.g. an element or an attribute) in a data structure, designed to hold Meta-data . In XML it may be implemented as a metadata element .
metadata element	An XML element, which is either a formal metadata element or a free-form metadata element , it implements the notion of a metadata container .
named entity	A named entity may be a person, place, event, organization, product name, object name or any other news-related real life entity.
News Architecture	A framework of specifications common to all IPTC news exchange standards of the G2 Family of Standards.
news provider	A provider of news content, the entity responsible for the management of news items. May be a news agency, a syndication company, a newspaper, a magazine ... or a blogger.
ontology	See taxonomy .
persistent identifier	An identifier which is associated with the same resource for all time. See also unambiguous identifier , unique identifier , and globally unique identifier (GUID) .
processor	An application that supports the handling and processing of Items. Also known as a user agent.
property	A synonym term for a metadata container – may be implemented as XML element.
provider	See news provider .
publish	Make available to other parties involved in the news exchange process, according to the business practices of the provider.

Table 196. Glossary (Continued)

Term	Definition
Qualified code, QCode	A concept URI represented by a string of the form sss:ccc, where sss is a scheme alias and ccc is a code . Examples are iso4217:USD, rfc3066:zh-Hant, nc:15062000, nasdaq:msft and cusip:594918104. A QCode is not the same as a QName (qualified name) [W3C: Namespaces in XML (http://www.w3.org/TR/REC-xml-names/)], though there are substantial similarities. The two main differences are: (i) the code does not have to be a valid XML name (e.g. can start with a digit), and (ii) the scheme alias does not have to be declared using a namespace declaration.
representation	The physical form of something.
representation of a ConceptItem	A manifestation of a given ConceptItem that is suited for some particular purpose. The various representations of a given ConceptItem may differ, for example, in whether they are verbose or concise, or in which language(s) they use for name and definition.
resource	A resource is a set of data that has identity.
scheme	A controlled vocabulary which is identified by a scheme URI. A scheme is not an anonymous controlled vocabulary.
scheme alias	A character sequence which is used as an abbreviation for a scheme URI . A scheme alias is similar but not identical to an XML Namespace prefix.
scheme URI	The URI which identifies the scheme . It is recommended to make this URI a URL and resolving it should result in retrieving information about the scheme.
synonym	Synonyms are concept URI(s) that refer from one concept to another concept with equivalent semantics. Synonymy is a symmetric relationship, which means that if A is synonymous with B, then B is also synonymous with A. An example of synonyms is “cemetery” and “graveyard”. In the News Architecture synonyms are expressed by the sameAs (page 168) property.
target	The data being described by the metadata. The IPTC has chosen to use the term target rather than subject (the term used by RDF [http://www.w3.org/RDF/]), as subject has a special meaning in the context of News.
taxonomy	In a broad sense, taxonomy is the science of classification, but is often taken to mean a particular classification. In the context of the News Architecture , a taxonomy is a collection of concept(s) , with associated code(s) . A taxonomy may support typed relationships between concepts. Such a taxonomy is sometimes known as an ontology or thesaurus .
thesaurus	See taxonomy .
tuple	A set of values. The word tuple is a generalisation of the sequence: couple, triple, quadruple, quintuple, sextuple, etc. Tuples are conventionally written as a comma-separated list of items, enclosed within braces, e.g. { scheme alias, code }.
type	See concept type .
unambiguous identifier	An identifier is unambiguous if it identifies one and only one object (but an object may have several different unambiguous identifiers). See also globally unique identifier .
unconstrained metadata container	A metadata container that accepts code(s) from any controlled vocabulary and of any concept type .
unique identifier	The only identifier of a resource. See also persistent identifier , unambiguous identifier , and globally unique identifier (GUID)
Web resource	The data content that can be retrieved from a Web server using a Web-compliant transport protocol. See also resource .



12 References

Table 197. References

Subject	Description
IPTC Documents	
NML-BR	IPTC NewsML 2 Business Requirements: http://www.newsml.org/dl.php?fn=NewsML/2.0/specification/NewsML_2.0-spec-BusinessRequirements_1.pdf
EventsML-G2	Specifications for EventsML-G2: http://www.iptc.org/std/EventsML-G2/1.0/specification/
NewsML-G2	Specifications for NewsML-G2: http://www.iptc.org/std/NewsML-G2/2.0/specification
Other References	
XMLSCHEMA-1.0	W3C XML Schema 1.0 specifications at: http://www.w3.org/TR/xmlschema-1/ , http://www.w3.org/TR/xmlschema-2/
XSD	W3C XML schema: http://www.w3.org/XML/Schema
XMLDSIG	XML-Signature Syntax and Processing: http://www.w3.org/TR/xmlsig-core/
RDF	Resource Description Framework (RDF): http://www.w3.org/RDF/
BCP47	Tags for Identifying Languages, IETF: http://rfc.net/bcp47.html



13 Index

13.1 Elements

A

a ... 47
 access ... 40
 accountable ... 41
 address ... 149
 affiliation ... 43
 altId ... 44
 altLoc ... 45
 altRep ... 46
 area ... 76
 assert ... 48
 audience ... 49

B

bag ... 50
 bit ... 51
 born ... 84
 br ... 127
 broader ... 52
 by ... 53

C

capacity ... 54
 catalog ... 55
 catalogRef ... 158
 channel ... 58
 channel (NewsML-G2) ... 56
 concept ... 59
 conceptID ... 61
 conceptItem ... 62
 conceptSet ... 64
 contactInfo ... 65
 contentCreated ... 79
 contentMeta (Concept Items) ... 66
 contentMeta (Knowledge Items) ... 67
 contentMeta (News Items) ... 68
 contentMeta (Package Items) ... 69
 contentModified ... 80
 contentSet ... 71
 contributor ... 72
 copyrightHolder ... 73
 copyrightNotice ... 74
 country ... 75
 created ... 90
 creator ... 77
 creditline ... 78

D

dateline ... 89
 definition ... 60
 description ... 91
 destinaion ... 92
 details ... 132
 died ... 85
 dissolved ... 86

E

edNote ... 93
 email ... 95
 embargoed ... 81
 exclAudience ... 96
 exDate ... 97
 exRule ... 98

F

facet ... 99
 fax ... 100
 filename ... 101
 firstCreated ... 82
 founded ... 87

G

generator ... 102
 genre ... 103
 geoAreaDetails ... 105
 group ... 106
 groupRef ... 107
 groupSet ... 108

H

header ... 134
 headline ... 109

I

icon ... 110
 im ... 118
 infoSource ... 119
 inline ... 111
 inlineData (NewsML-G2) ... 112
 inlineRef ... 114
 inlineXML (NewsML-G2) ... 115
 instanceOf ... 117
 itemClass ... 120
 itemMeta ... 121
 itemRef ... 122
 itemSet ... 123

**K**

knowledgeItem ... 125

L

language ... 126

line ... 42

link ... 128

locality ... 129

located ... 130

location ... 131

M

memberOf ... 133

N

name (Concept Name) ... 63

name (Property Value Name) ... 153

narrower ... 135

newsItem (NewsML-G2) ... 136

newsMessage ... 137

note ... 138

O

objectDetails ... 139

openHours ... 140

organisationDetails ... 142

origin ... 141

P

packageItem ... 143

partMetadata ... 144

personDetails ... 146

phone ... 147

POIDetails ... 148

position ... 104

postalCode ... 150

priority ... 151

profile ... 152

provider ... 70

pubStatus ... 154

R

rb ... 165

rDate ... 155

regionDelim ... 181

related ... 157

remoteContent (NewsML-G2) ... 159

rightsInfo ... 162

role ... 163

rp ... 166

rRule ... 156

rt ... 167

ruby ... 164

S

sameAs ... 168

scheme ... 169

sender ... 170

sent ... 88

service ... 94

signal ... 171

slugline ... 172

span ... 173

subject ... 174

T

timeDelim ... 175

timestamp ... 176

title (Item Title) ... 124

transmitId ... 177

type ... 178

U

urgency ... 179

usageTerms ... 180

V

versionCreated ... 83

W

web ... 182



13.2 Datatypes

A

AnyltemType ... 186

ApproximateDateTimePropType ... 187

AudienceType ... 188

B

BlockType ... 189

C

ConceptIdType ... 190

ContentMetadataType ... 191

D

DateOptTimePropType ... 192

DateOptTimeType ... 193

DateTimePropType ... 194

E

ElectronicAddressTechType ... 196

ElectronicAddressType ... 195

F

Flex1ConceptPropType ... 197

Flex1PartyPropType ... 198

Flex1PropType ... 199

FlexLocationPropType ... 200

FlexOrganisationPropType ... 201

FlexPartyPropType ... 202

FlexPersonPropType ... 203

FlexPropType ... 204

I

Int100Type ... 205

Int1To9Type ... 206

IntIStringType ... 207

IRIType ... 208

L

Label1Type ... 209

Link1Type ... 210

Q

QCodeListType ... 212

QCodePropType ... 213

QCodeType ... 214

QualPropType ... 215

R

RecurrenceRuleType ... 216

RelatedConceptType ... 217

RightsLabelType ... 218

T

TruncatedDateTimePropType ... 219

TruncatedDateTimeType ... 220

TypedQualPropType ... 221

V

VersionedStringType ... 222



Contact Information

Contact the IPTC by:

Postal mail:
20 Garrick Street
London WC2E 9BT
United Kingdom

Web:

www.iptc.org

Email:

office@iptc.org